

Version 9.0

# Altera Product Catalog




## Contents

Glossary.....	2
Stratix® FPGA series.....	3
HardCopy® ASIC Series.....	15
Arria® FPGA Series .....	19
Cyclone® FPGA Series .....	25
MAX® CPLD Series .....	35
Quartus® II Software .....	39
Embedded Processing .....	42
Intellectual Property.....	45
Development Kits.....	50
Training .....	62
Protocols, Devices, and Data Rates .....	63
Configuration Devices .....	65
Ordering Codes .....	66

Altera delivers the broadest portfolio of custom logic devices—FPGAs, ASICs, and CPLDs. This uniquely positions us to bring your great ideas to life faster, better, and more cost effectively. You can count on it.

## FPGAs

Altera® FPGAs give you the best performance, the lowest power, and the widest range of densities. We have three classes of FPGAs to meet your needs, all optimized for value. Our flagship Stratix series delivers the industry's highest density and performance FPGAs, while our Arria series is perfect for high-performance computation functionality and keeping costs down. Choose the Cyclone series for the lowest power and cost in high-volume, cost-sensitive applications.



## ASICs

If you are looking for an ASIC, stop here. We provide a migration path from our Stratix series to HardCopy ASICs to deliver the shortest time to market, lowest risk, and lowest overall ASIC development costs.

## CPLDs

For glue logic, and any control functions, our non-volatile MAX series is comprised of the market's lowest cost CPLDs—a single-chip solution, great for interface bridging, level shifting, I/O expansion, or management of analog I/Os.

## Productivity-enhancing Design Software, Embedded Processing, Intellectual Property (IP), and Development Kits

With Altera you get a complete design environment and a wide choice of design tools, built to work together easily so your designs are up and running fast. You can try one of our training classes to get a jump start on your designs. Choose Altera and see how we will enhance your productivity and make a difference to your bottom line.

Turn the page to get the specification overview of our latest FPGAs, ASICs, and CPLDs, as well as our extended line of products and services. Our broad product portfolio ensures you get the complete and best design solution.

## Glossary

Below is a glossary of helpful terms to bring you up to speed on Altera devices.

Term	Definition
Adaptive logic module (ALM)	Logic building block, used by some Altera devices, which provides advanced features with efficient logic utilization. Each ALM contains a variety of look-up table (LUT)-based resources that can be divided between two combinational adaptive LUTs (ALUTs).
Configuration via PCIe (CvPCIe)	This capability enables you to configure the FPGA using the existing PCI Express® (PCIe®) link in your application, reducing configuration time to under 100 ms.
Embedded HardCopy Blocks	These metal-programmable hard IP blocks deliver up to 14M ASIC gates or up to 700K additional logic elements (LEs) to harden standard or logic-intensive applications.
Equivalent LE	Device density represented as a comparable amount of LEs, which uses the 4-input look-up table as a basis.
Fractional phase-locked loops (fPLL)	A phase-locked loop (PLL) in the core fabric, fPLLs provide increased flexibility as an additional clocking source for the transceiver, replacing external voltage-controlled crystal oscillators (VCXOs).
Global clock networks	Global clocks can drive throughout the entire device, serving as low-skew clock sources for functional blocks such as ALMs, DSP blocks, TriMatrix memory blocks, and PLLs. See regional clocks and periphery clocks for more clock network information.
LE	Logic building block, used by some Altera devices, that includes a 4-input LUT, programmable register, and a carry chain connection. See device handbooks for more information.
Macrocells	Similar to logic elements, this is the measure of density in MAX series CPLDs.
Memory logic array blocks (MLABs)	MLABs are dual-purpose blocks, configurable as regular logic array blocks or as memory blocks.
On-chip termination (OCT)	Support for driver impedance matching and series termination, which eliminates the need for external resistors, improves signal integrity, and simplifies board design. On-chip series, parallel, and differential termination resistors are configurable via Quartus II software.
Periphery clocks (PCLKs)	PCLKs are a collection of individual clock networks driven from the periphery of the device. PCLKs can be used instead of general-purpose routing to drive signals into and out of the device.
Plug & Play Signal Integrity	This capability, consisting of Altera's adaptive dispersion engine and hot socketing, lets you change the position of backplane cards on the fly, without having to manually configure your backplane equalization settings.
Programmable Power Technology	This feature automatically optimizes logic, DSP, and memory blocks for the lowest power at the required performance. Only the blocks with critical-path logic need to be in high-performance mode; all others are in low-power mode.
Real-time in-system programming (ISP)	This capability allows you to program a MAX II device while the device is still in operation. The new design only replaces the existing design when there is a power cycle to the device. This way, you can perform in-field updates to the MAX II device at any time without affecting the operation of the whole system.
Regional clocks	Regional clocks are device quadrant-oriented and provide the lowest clock delay and skew for logic contained within a single device quadrant.
Variable-precision DSP blocks	These integrated blocks provide native support for signal processing of varying precisions—for example, 9x9, 27x27, and 18x36—in a sum or independent mode.

The following features, packages, and I/O matrices give you an overview of our devices. To get the full story, check out our online selector guide: [www.altera.com/selector](http://www.altera.com/selector).

		Stratix V GX and GT FPGAs (0.85 V), Up to 28G Transceivers <sup>1</sup>									
		5SGXA3	5SGXA4	5SGXA5	5SGXA7	5SGXA9	5SGXAB	5SGXB5	5SGXB6	5SGTC5	5SGTC7
Density and Speed	ALMs	75,500	113,000	160,500	234,750	317,000	397,000	185,000	225,000	160,500	234,750
	Equivalent LEs	200,000	300,000	425,000	622,000	840,000	1,052,000	490,000	597,000	425,000	622,000
	Registers <sup>2</sup>	302,000	452,000	642,000	939,000	1,268,000	1,588,000	740,000	901,000	642,000	939,000
	M20K memory blocks	800	1,316	2,304	2,560	1,600	2,016	2,100	2,660	2,304	2,560
	MLAB memory (Mb)	2.3	3.44	4.89	7.16	9.67	12.12	5.65	6.87	4.89	7.16
	Embedded memory (Mb)	16	26	45	50	31	39	41	52	45	50
	18-bit x 18-bit multipliers	376	376	512	512	1,000	1,500	798	798	512	512
	Speed grades (fastest to slowest)	-2, -3, -4									
Architectural Features	Global clock networks	16									
	Regional clock networks	92									
	Design security	✓									
	HardCopy series device support	✓									
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3 <sup>2</sup>									
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-5, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2V HSTL (I and II), 1.5V HSTL (I and II), 1.8V HSTL (I and II)									
	LVDS channels, 1.4 Gbps (receive/transmit)	156	156	210	210	210	210	150	150	150	150
	Embedded DPA circuitry	✓									
	Series and differential OCT	✓									
	Transceiver (SERDES) channels (28 Gbps/14.1 Gbps)	0/24 or 36	0/24 or 36	0/24, 36, or 48	0/24, 36, or 48	0/36 or 48	0/36 or 48	0/66	0/66	4/32	4/32
	PCIe hard IP blocks	1 or 2	1 or 2	1 or 4	1 or 4	1 or 4	1 or 4	1 or 4	1 or 4	1	1
	100-Gbps Ethernet (100GbE) hard IP blocks	No	No	Yes	Yes	No	No	No	No	Yes	Yes
Memory devices supported	DDR3, DDR2, DDR, QDR II, RLDRAM II, SDR										

<sup>1</sup>All data is preliminary

<sup>2</sup>3.3-V compliant, requires a 3.0-V power supply

## Stratix V FPGA Features

		Stratix V GS and E FPGAs (0.85 V), Up to 14.1-Gbps Transceivers <sup>1</sup>							
		5SGSD2	5SGSD3	5SGSD4	5SGSD5	5SGSD6	5SGSD8	5SEE9	5SEEA
Density and Speed	ALMs	49,000	89,000	125,000	174,000	220,000	265,000	317,000	397,000
	Equivalent LEs	130,000	236,000	332,000	462,000	583,000	703,000	804,000	1,052,000
	Registers <sup>2</sup>	196,000	356,000	500,000	696,000	880,000	1,060,000	1,268,000	1,588,000
	M20K memory blocks	450	688	1,062	1,950	2,320	2,688	1,600	2,016
	MLAB memory (Mb)	1.50	2.70	3.80	5.30	6.70	8.10	9.67	12.12
	Embedded memory (Mb)	9	14	22	40	48	55	31	39
	18-bit x 18-bit multipliers	650	1,260	1,892	2,966	3,550	4,096	1,000	1,500
	Speed grades (fastest to slowest)	-2, -3, -4							
Architectural Features	Global clock networks	16							
	Regional clock networks	92							
	Design security	✓							
	HardCopy series device support	✓							
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3 <sup>2</sup>							
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-5, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2V HSTL (I and II), 1.5V HSTL (I and II), 1.8V HSTL (I and II)							
	LVDS channels, 1.4 Gbps (receive/transmit)	100	125	140	175	225	225	210	210
	Embedded DPA circuitry	✓						✗	
	Series and differential OCT	✓							
	Transceiver (SERDES) channels (14.1 Gbps)	12	18	36	36	48	48	0	0
	PCIe hard IP blocks	1	1	1	1	2	2	0	0
	100GbE hard IP blocks	No							
Memory devices supported	DDR3, DDR2, DDR, QDR II, RLD RAM II, SDR								

<sup>1</sup>All data is preliminary<sup>2</sup>3.3-V compliant, requires a 3.0-V power supply

## Stratix IV GT FPGA Features

		Stratix IV GT FPGAs (0.95 V), 11.3-Gbps Transceivers <sup>1</sup>					
		EP4S40G2	EP4S40G5	EP4S100G2	EP4S100G3	EP4S100G4	EP4S100G5
Density and Speed	ALMs	91,200	212,480	91,200	116,480	141,440	212,480
	Equivalent LEs	228,000	531,200	228,000	291,200	353,600	531,200
	Registers <sup>2</sup>	182,400	424,960	182,400	232,960	282,880	424,960
	M9K memory blocks	1,235	1,280	1,235	936	1,248	1,280
	M144K memory blocks	22	64	22	36	48	64
	MLAB memory (Kb)	2,850	6,640	2,850	3,640	4,420	6,640
	Embedded memory (Kb)	14,283	20,736	14,283	13,608	18,144	20,736
	18-bit x 18-bit multipliers	1,288	1,024	1,288	832	1,024	1,024
	Speed grades (fastest to slowest)	-1, -2, -3					
Architectural Features	Global clock networks	16					
	Regional clock networks	64	88	64	88	88	88
	Periphery clock networks	88	112	88	112	112	112
	PLLs/unique outputs	8/68	8/68	8/68	12/96	12/96	12/96
	Design security	✓					
	HardCopy series device support	-					
	Configuration file size (Mb)	95	172	95	172	172	172
Others	Plug & Play Signal Integrity, Programmable Power Technology						
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3 <sup>3</sup>					
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)					
	Emulated LVDS channels, 1,100 Mbps	192	256	192	256	256	256
	LVDS channels, 1,600 Mbps (receive/transmit)	46/46					
	Embedded DPA circuitry	✓					
	Series and differential OCT	✓					
	Transceiver (SERDES) channels <sup>4</sup> (11.3 Gbps/8.5 Gbps/6.5 Gbps)	12/12/12	12/12/12	24/0/12	24/8/16	24/8/16	32/0/16
	PCIe hard IP blocks	2	2	2	4	4	4
Memory devices supported	DDR3, DDR2, DDR, QDR II, RLDRAM II, SDR						

<sup>1</sup> Available in industrial temperatures only (0°C to 100°C).

<sup>2</sup> This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases total register count by an additional 50 percent.

<sup>3</sup> 3.3 V compliant, requires a 3-V power supply.

<sup>4</sup> The total transceiver count is the sum of 11.3-Gbps plus 8.5-Gbps plus 6.5-Gbps transceivers.

## Stratix IV GX FPGA Features

		Stratix IV GX FPGAs (0.9 V), 8.5-Gbps Transceivers <sup>1</sup>						
		EP4SGX70	EP4SGX110	EP4SGX180	EP4SGX230	EP4SGX290	EP4SGX360	EP4SGX530
Density and Speed	ALMs	29,040	42,240	70,300	91,200	116,480	141,440	212,480
	Equivalent LEs	72,600	105,600	175,750	228,000	291,200	353,600	531,200
	Registers <sup>2</sup>	58,080	84,480	140,600	182,400	232,960	282,880	424,960
	M9K memory blocks	462	660	950	1,235	936	1,248	1,280
	M144K memory blocks	16	16	20	22	36	48	64
	MLAB memory (Kb) <sup>2</sup>	908	1,320	2,197	2,850	3,640	4,420	6,640
	Embedded memory (Kb)	6,462	8,244	11,430	14,283	13,608	18,144	20,736
	18-bit x 18-bit multipliers	384	512	920	1,288	832	1,040 <sup>3</sup>	1,024
	Speed grades (fastest to slowest)	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4	-2, -2x <sup>4</sup> , -3, -4
Architectural Features	Global clock networks	16						
	Regional clock networks	64	64	64	64	88	88	88
	Periphery clock networks	56	56	88	88	88	88	112
	PLLs/unique outputs	4/34	4/34	8/68	8/68	12/96	12/96	12/96
	Design security	✓						
	HardCopy series device support	✓ <sup>5</sup>	✓ <sup>5</sup>	✓	✓	✓	✓	✓
	Configuration file size (Mb)	53	53	95	95	141	141	172
	Others	Plug & Play Signal Integrity, Programmable Power Technology						
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3 <sup>6</sup>						
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)						
	Emulated LVDS channels 1,100 Mbps	128	128	192	192	256	256	256
	LVDS channels, 1,600 Mbps (receive/transmit)	56/56	56/56	88/88	88/88	98/98	98/98	98/98
	Embedded DPA circuitry	✓						
	Series and differential OCT	✓						
	Transceiver (SERDES) channels (8.5 Gbps/6.5 Gbps) <sup>7</sup>	16/8	16/8	24/12	24/12	32/16	32/16	32/16
	PCIe hard IP blocks	2	2	2	2	4	4	4
Memory devices supported	DDR3, DDR2, DDR, QDR II, RLDRAM II, SDR							

<sup>1</sup>Maximum LVDS channels, transceiver channels, PLLs/unique outputs, and PCIe hard IP blocks for the product line shown. Various packages offer a variety of options to meet your design needs.

<sup>2</sup>This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases the total register count by an additional 50 percent.

<sup>3</sup>EP4SGX360N has 1,024 18x18 multipliers.

<sup>4</sup>Support for -2 core and -3 I/O speed-grade. Support for PCIe Gen1 and Gen2 x8. Selected devices only.

<sup>5</sup>For EP4SGX70D and EP4SGX110D/F devices.

<sup>6</sup>3.3 V compliant, requires a 3-V power supply.

<sup>7</sup>The total transceiver count is the sum of 8.5-Gbps transceivers plus 6.5-Gbps transceivers.

## Stratix IV E FPGA Features

		Stratix IV E FPGAs (0.9 V)			
		EP4SE230	EP4SE360	EP4SE530	EP4SE820
Density and Speed	ALMs	91,200	141,440	212,480	325,220
	Equivalent LEs	228,000	353,600	531,200	813,050
	Registers <sup>1</sup>	182,400	282,880	424,960	650,440
	M9K memory blocks	1,235	1,248	1,280	1,610
	M144K memory blocks	22	48	64	60
	MLAB memory (Kb)	2,850	4,420	6,640	10,163
	Embedded memory (Kb)	14,283	18,144	20,736	23,130
	18-bit x 18-bit multipliers	1,288	1,040	1,024	960
	Speed grades (fastest to slowest)	-2, -3, -4	-2, -3, -4	-2, -3, -4	-3, -4
	Architectural Features	Global clock networks	16		
Regional clock networks		64	88	88	88
Periphery clock networks		88	88	112	132
PLLs/unique outputs		4/34	12/96	12/96	12
Design security		✓			
Configuration file size (Mb)		95	141	172	230
HardCopy series device support		✓			
Others		Programmable Power Technology			
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3 <sup>2</sup>			
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)			
	Emulated LVDS channels, 1,100 Mbps	128	256	256	288
	LVDS channels, 1,600 Mbps (receive/transmit)	56/56	88/88	112/112	132/132
	Embedded DPA circuitry	✓			
	Series and differential OCT	✓			
	Memory devices supported	DDR3, DDR2, DDR, QDR II, RLDRAM II, SDR			

<sup>1</sup> This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which can increase the total register count by an additional 50 percent.

<sup>2</sup> 3.3 V compliant, requires a 3-V power supply.

## Stratix III L FPGA Features

		Stratix III L FPGAs (1.1 V, 0.9 V)					
		EP3SL50	EP3SL70	EP3SL110	EP3SL150	EP3SL200	EP3SL340
Density and Speed	ALMs	19,000	27,000	42,600	56,800	79,560	135,200
	Equivalent LEs	47,500	67,500	107,500	142,500	198,900	338,000
	Registers <sup>1</sup>	38,000	54,000	85,200	113,600	159,120	270,400
	M9K memory blocks	108	150	275	355	468	1,040
	M144K memory blocks	6	6	12	16	36	48
	MLAB memory (Kb) <sup>2</sup>	297	422	672	891	1,250	2,110
	Embedded memory (Kb)	1,836	2,214	4,203	5,499	9,396	16,272
	18-bit x 18-bit multipliers	216	288	288	384	576	576
	Speed grades (fastest to slowest)	-2, -3, -4					
Architectural Features	Global clock networks	16					
	Regional clock networks	48	48	48	48	88	88
	Periphery clock networks	104	104	208	208	208	208
	PLLs/unique outputs	4/34	4/34	8/68	8/68	12/96	12/96
	Design security	✓					
	Configuration file size (Mb)	22	22	47	47	66	120
	HardCopy series device support	✓					
	Others	Programmable Power Technology					
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3					
	I/O standards supported	LVDS, LVPECL, Differential SSTL-18, Differential SSTL-2, Differential HSTL, SSTL-18 (I and II), SSTL-15 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), PCI, PCI-X 1.0, LVTTTL, LVCMOS					
	Emulated LVDS channels, 1,100 Mbps	56	56	88	88	112	137
	LVDS channels, 1,600 Mbps (receive/transmit)	56/56	56/56	88/88	88/88	112/112	132/132
	Embedded DPA circuitry	✓					
	Series and differential OCT	✓					
	Memory devices supported	DDR3, DDR2, DDR, QDR II, RLDRAM II, SDR					

<sup>1</sup> This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases the total register count by an additional 50 percent.

<sup>2</sup> The size of the MLAB ROM is twice the size of the MLAB RAM.

## Stratix III E FPGA Features

		Stratix III E FPGAs (1.1 V)			
		EP3SE50	EP3SE80	EP3SE110	EP3SE260
Density and Speed	ALMs	19,000	32,000	42,600	101,760
	Equivalent LEs	47,500	80,000	107,500	254,400
	Registers <sup>1</sup>	38,000	64,000	85,200	203,520
	M9K memory blocks	400	495	639	864
	M144K memory blocks	12	12	16	48
	MLAB memory (Kb) <sup>2</sup>	297	500	672	1,594
	Embedded memory (Kb)	5,328	6,183	8,055	14,688
	18-bit x 18-bit multipliers	384	672	896	768
	Speed grades (fastest to slowest)	-2, -3, -4			
Architectural Features	Global clock networks	16			
	Regional clock networks	48	48	48	88
	Periphery clock networks	104	208	208	208
	PLLs/unique outputs	4/34	8/68	8/68	12/96
	Design security	✓			
	Configuration file size (Mb)	26	48	48	93
	HardCopy series device support	✓			
	Others	Programmable Power Technology			
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3			
	I/O standards supported	LVDS, LVPECL, Differential SSTL-18, Differential SSTL-2, Differential HSTL, SSTL-18 (I and II), SSTL-15 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), PCI, PCI-X 1.0, LVTTTL, LVCMOS			
	Emulated LVDS channels, 1,100 Mbps	56	88	88	112
	LVDS channels, 1,600 Mbps (receive/transmit)	56/56	88/88	88/88	112/112
	Embedded DPA circuitry	✓			
	Series and differential OCT	✓			
	Memory devices supported	DDR3, DDR2, DDR, QDR II, RDRAM II, SDR			

<sup>1</sup> This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases the total register count by an additional 50 percent.

<sup>2</sup> The size of the MLAB ROM is twice the size of the MLAB RAM.

## Stratix II GX FPGA Features

		Stratix II GX FPGAs (1.2 V), 6.375-Gbps Transceivers <sup>1</sup>			
		EP2SGX30	EP2SGX60	EP2SGX90	EP2SGX130
Density and Speed	ALMs	13,552	24,176	36,384	53,016
	Equivalent LEs	33,880	60,440	90,960	132,540
	Registers <sup>2</sup>	27,104	48,352	72,708	106,032
	M512 memory blocks	202	329	488	699
	M4K memory blocks	144	255	408	609
	M512K memory blocks	1	2	4	6
	Embedded memory (Kb)	1,338	2,485	4,415	6,590
	18-bit x 18-bit multipliers	64	144	192	252
	Speed grades (fastest to slowest)	-3, -4, -5			
Architectural Features	Global clock networks	48			
	Regional clock networks	48			
	PLLs/unique outputs	4/18	8/36	8/36	8/36
	Design security	✓			
	Configuration file size (Mb)	10	17	28	40
	HardCopy series device support	–	–	–	–
	Others	Plug & Play Signal Integrity			
I/O Features	I/O voltage levels supported (V)	1.5, 1.8, 2.5, 3.3			
	I/O standards supported	LVDS, LVPECL, HyperTransport™, Differential SSTL-18, Differential SSTL-2, Differential HSTL, SSTL-18 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), PCI, PCI-X 1.0, LVTTTL, LVCMOS			
	Emulated LVDS channels, 1,100 Mbps	31/29	42/42	59/59	73/71
	LVDS channels, 1,000 Mbps (receive/transmit)	31/29	42/42	59/59	73/71
	Embedded DPA circuitry	✓			
	Series and differential OCT	✓			
	Transceiver (SERDES) channels (6.375 Gbps)	8	12	16	20
Memory devices supported	DDR2, DDR, QDR II, RLDRAM II, SDR				

<sup>1</sup> Maximum PLLs/unique outputs, LVDS channels, and transceiver channels for the product line shown. Various packages offer a variety of options to meet your design needs.

<sup>2</sup> This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases the total register count by an additional 50 percent.

Stratix Series Package and I/O Matrices

Stratix V GX, GT, GS, and E FPGAs (0.85 V), Up to 28G Transceivers							
	Hybrid FPGA (H)		FBGA (F)				
	780 pin <sup>1</sup> 35 x 35 (mm) 1.0-mm pitch	1,152 pin <sup>2</sup> 40 x 40 (mm) 1.0-mm pitch	484 pin 23 x 23 (mm) 1.0-mm pitch	780 pin 29 x 29 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch
5SGXA3	264, 66, 24 				552, 138, 24 	444, 111, 36 	624, 156, 36 
5SGXA4	264, 66, 24 				552, 138, 24	444, 111, 36	624, 156, 36
5SGXA5					552, 138, 24	444, 111, 36	696, 174, 36
5SGXA7					552, 138, 24	444, 111, 36 	696, 174, 36
5SGXA9							696, 174, 36
5SGXAB							696, 174, 36
5SGXB5							
5SGXB6							
5SGTC5							
5SGTC7							
5SGSD2			240, 60, 9 	400, 100, 12 			
5SGSD3			240, 60, 9 	400, 100, 12 	500, 125, 18		
5SGSD4				400, 100, 12 	560, 140, 24		700, 175, 36
5SGSD5					560, 140, 24 		700, 175, 36
5SGSD6							700, 175, 36
5SGSD8							700, 175, 36 
5SEE9		552, 138, 0 					
5SEE9		552, 138, 0 					

<sup>288</sup> Number indicates available user I/O pins.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). User I/Os may be less than labelled for vertical migration.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

<sup>1</sup>These device and pincount combinations are supported in the Hybrid F780 (35 mm) package

<sup>2</sup>These device and pincount combinations may only be supported in the Hybrid (40 mm) or SuperHybrid (43 mm) package

## Stratix Series Package and I/O Matrices

Stratix V GX, GT, GS, and E FPGAs (0.85 V), Up to 28G Transceivers						
FBGA (F)						
	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,760 pin 43 x 43 (mm) 1.0-mm pitch	1,932 pin 45 x 45 (mm) 1.0-mm pitch	1,932 pin 45 x 45 (mm) 1.0-mm pitch
5SGXA3						
5SGXA4						
5SGXA5	600, 150, 48				840, 210, 48	
5SGXA7	600, 150, 48				840, 210, 48	
5SGXA9					840, 210, 48	
5SGXAB					840, 210, 48	
5SGXB5		432, 108, 66		600, 150, 66		
5SGXB6		432, 108, 66		600, 150, 66		
5SGTC5	600, 150, 48					
5SGTC7	600, 150, 48					
5SGSD2						
5SGSD3						
5SGSD4						
5SGSD5						
5SGSD6					900, 225, 48	
5SGSD8					900, 225, 48	
5SEE9			696, 174, 0			840, 210, 0
5SEE9			696, 174, 0			840, 210, 0

288 Number indicates available user I/O pins.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). User I/Os may be less than labelled for vertical migration.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

## Stratix Series Package and I/O Matrices

Stratix IV GT FPGAs (0.95 V), 11.3-Gbps Transceivers		
FBGA (F) <sup>1</sup>		
	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,932 pin 45 x 45 (mm) 1.0-mm pitch
EP4S40G2	646 12+12+12	
EP4S40G5	646 <sup>2</sup> 12+12+12	
EP4S100G2	646 24+0+12	
EP4S100G3		769 24+8+16
EP4S100G4		769 24+8+16
EP4S100G5	646 <sup>2</sup> 24+0+12	769 32+0+16

<sup>1</sup>FineLine ball grid array

<sup>2</sup>Hybrid package (flip chip) FBGA: 42.5 x 42.5 (mm) 1.0-mm pitch.

636  
12+12+12

Values on top indicate available user I/O pins; values on bottom indicate the 11.3-Gbps plus 8.5-Gbps plus 6.5-Gbps transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

Stratix IV GT devices are only offered in industrial temperatures (0°C to 100°C).

Stratix IV GX FPGAs (0.9 V), 8.5-Gbps Transceivers <sup>1</sup>						
FBGA (F)						
	780 pin 29 x 29 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,760 pin 42.5 x 42 (mm) 1.0-mm pitch	1,932 pin 45 x 45 (mm) 1.0-mm pitch
EP4SGX70	368 8+0		480 16+8			
EP4SGX110	368 8+0	368 16+0	480 16+8			
EP4SGX180	368 8+0	560 16+0	560 16+8	736 24+12		
EP4SGX230	368 8+0	560 16+0	560 16+8	736 24+12		
EP4SGX290	288 <sup>2</sup> 16+0	560 16+0	560 16+8	736 24+12	864 24+12	904 32+16
EP4SGX360	288 <sup>2</sup> 16+0	560 16+0	560 16+8	736 24+12	864 24+12	904 32+16
EP4SGX530			560 <sup>3</sup> 16+8	736 <sup>3</sup> 24+12	864 24+12	904 32+16

<sup>1</sup>I/O counts do not include dedicated clock inputs that can be used as data inputs.

<sup>2</sup>Hybrid package (flip chip) FBGA: 35.0 x 35.0 (mm) 1.0-mm pitch.

<sup>3</sup>Hybrid package (flip chip) FBGA: 42.5 x 42.5 (mm) 1.0-mm pitch.

636  
8+0

Values on top indicate available user I/O pins; values at the bottom indicate the 8.5-Gbps plus 6.5-Gbps transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

Stratix IV GT devices are only offered in industrial temperatures (0°C to 100°C).

## Stratix Series Package and I/O Matrices

		FBGA (F)				
		484 pin 23 x 23 (mm) 1.0-mm pitch	780 pin 29 x 29 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch	1,760 pin 42.5 x 42.5 (mm) 1.0-mm pitch
Stratix IV E FPGAs	EP4SE820			736 <sup>3</sup>	960 <sup>3</sup>	1,104
	EP4SE530			736 <sup>3</sup>	960 <sup>3</sup>	960
	EP4SE360		480 <sup>2</sup>	736		
	EP4SE230		480			
Stratix III E FPGAs <sup>1</sup>	EP3SE260 <sup>3</sup>		480 <sup>2</sup>	736	960	
	EP3SE110		480	736		
	EP3SE80		480	736		
	EP3SE50	288	480			
Stratix III L FPGAs <sup>1</sup>	EP3SL340			736 <sup>3</sup>	960	1,104
	EP3SL200		480 <sup>2</sup>	736	960	
	EP3SL150		480	736		
	EP3SL110		480	736		
	EP3SL70	288	480			
	EP3SL50	288	480			

<sup>1</sup> I/O counts do not include dedicated clock inputs that can be used as data inputs.

<sup>2</sup> Hybrid package (flip chip) FBGA: 35.0 x 35.0 (mm) 1.0-mm pitch.

<sup>3</sup> Hybrid package (flip chip) FBGA: 42.5 x 42.5 (mm) 1.0-mm pitch.

**288** Number indicates available user I/O pins.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages. Stratix IV GT devices are only offered in industrial temperatures (0° to 100°).

Stratix II GX FPGAs (1.2 V), 6.35-Gbps Transceivers <sup>1</sup>			
FBGA (F)			
	780 pin 29 x 29 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,508 pin 40 x 40 (mm) 1.0-mm pitch
EP2SGX30	361 8		
EP2SGX60	364 8	534 12	
EP2SGX90		558 12	650 16
EP2SGX130			734 20

<sup>1</sup> I/O counts do not include dedicated clock inputs that can be used as data inputs.

**636**  
**12** Values on top indicate available user I/O pins; values on bottom indicate the 6.35-Gbps transceiver count.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Stratix series devices are offered in commercial and industrial temperatures and RoHS-compliant packages. Stratix IV GT devices are only offered in industrial temperatures (0° to 100°).

## HardCopy IV ASIC Features

		HardCopy IV ASICs (0.9 V), 6.5-Gbps Transceivers				
		HC4GX15	HC4GX25	HC4GX35	HC4E25	HC4E35
Density and Speed	Usable ASIC gates	9.4M	11.5M	11.5M	9.4M	15M
	Equivalent LEs	353,600	531,600	531,600	353,600	813,050
	M9K memory blocks	660	936	1,280	864	1,320
	M144K memory blocks	24	36	64	32	48
	MLAB memory	Implemented in HCells				
	Embedded memory (Kb)	9,396	13,608	20,736	12,384	18,792
	18-bit x 18-bit multipliers <sup>1</sup>	1,288	1,288	1,288	1,288	1,040
Architectural Features	PLLs/unique outputs	3/27	6/54	8/68	4/34	12/96
	Design security <sup>2</sup>	✓				
	Stratix series prototyping support	EP4SGX70	EP4SGX110	EP4SGX180	EP4SE230	EP4SE360
		EP4SGX110	EP4SGX180	EP4SGX230	EP4SE360	EP4SE530
		EP4SGX180	EP4SGX230	EP4SGX290		EP4SE820
		EP4SGX230	EP4SGX290	EP4SGX360		
EP4SGX290		EP4SGX360	EP4SGX530			
EP4SGX360	EP4SGX530					
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0				
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)				
	Emulated LVDS channels 1,100 Mbps	184	236	280	120	216
	LVDS channels, 1,250 Mbps (receive/transmit)	28/28	44/44	88/88	56/56	88/88
	Embedded DPA circuitry	✓				
	Series and differential OCT	✓				
	Transceiver (SERDES) channels, 6.5 Gbps/6.5 Gbps PMA only	8/0	16/8	24/12	—	—
	PCIe hard IP blocks	1	2	2	—	—
External Memory Interfaces	Memory devices supported	DDR3, DDR2, DDR, QDR II, RDRAM II, SDR				

<sup>1</sup>Implemented in HCells.<sup>2</sup>Since all HardCopy ASICs contain hard-wired logic, they are inherently secure.

## HardCopy III ASIC Features

		HardCopy III ASICs (0.9 V)	
		HC325	HC335
Density and Speed	Usable ASIC gates	7.0M	7.0M
	Equivalent LEs	338,000	338,000
	M9K memory blocks	864	1,040
	M144K memory blocks	32	48
	MLAB memory	Implemented in HCells	
	Embedded memory (Kb)	12,384	16,272
	18-bit x 18-bit multipliers <sup>1</sup>	896	—
Architectural Features	PLLs/unique outputs	8/68	12/96
	Design security <sup>2</sup>	✓	
	Stratix series prototyping support	EP3SE110	EP3SE110
		EP3SL110	EP3SL150
EP3SL150		EP3SL200	
EP3SL200		EP3SE260	
EP3SE260		EP3SL340	
EP3SL340			
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0	
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)	
	Emulated LVDS channels 1,100 Mbps	120	216
	LVDS channels, 1,250 Mbps (receive/transmit)	56/56	88/88
	Embedded DPA circuitry	✓	✓
	Series and differential OCT	✓	
External Memory Interfaces	Memory devices supported	DDR3, DDR2, DDR, QDR II, RDRAM II, SDR	

<sup>1</sup>Implemented in HCells.

<sup>2</sup>Since all HardCopy ASICs contain hard-wired logic, they are inherently secure.

## HardCopy II ASIC Features

		HardCopy II ASICs					
		HC210W	HC210	HC220W	HC220	HC230	HC240
Density and Speed	Usable ASIC gates	1.0M	1.0M	1.9M	1.9M	2.9M	3.6M
	Equivalent LEs	90,960	90,960	132,540	132,540	179,400	179,400
	M512 memory blocks	Not available in HardCopy II ASICs					
	M4K memory blocks	190	190	408	408	614	768
	M512K memory blocks	0	0	2	2	6	9
	Embedded memory (Kb)	855	855	2,988	2,988	6,219	8,640
	18-bit x 18-bit multipliers <sup>1</sup>	192	192	252	252	384	384
Architectural Features	PLLs/unique outputs	4/32	4/32	4/32	4/32	8/64	12/88
	Design security <sup>2</sup>	✓					
	Stratix series prototyping support	EP2S30 EP2S60 EP2S90	EP2S30 EP2S60 EP2S90	EP2S60 EP2S90 EP2S130	EP2S60 EP2S90 EP2S130	EP2S90 EP2S130 EP2S180	EP2S180
I/O Features	I/O voltage levels supported (V)	1.5, 1.8, 2.5, 3.3					
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X 1.0, LVDS, LVPECL, Differential SSTL-18, Differential SSTL-2, Differential HSTL SSTL-18 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), HyperTransport					
	Emulated LVDS channels, 340 Mbps	Contact Altera					
	LVDS channels, 1,040 Mbps (receive/transmit)	17/13	21/19	26/24	30/29	46/44	116/116
	Embedded DPA circuitry	✓					
	Series and differential OCT	✓					
External Memory Interfaces	Memory devices supported	DDR2, DDR, QDR II, RLDRAM II, SDR					

<sup>1</sup>Implemented in HCells.<sup>2</sup>Since all HardCopy ASICs contain hard-wired logic, they are inherently secure.

## HardCopy Series Package and I/O Matrices

HardCopy IV ASICs (0.9 V), 6.5-Gbps Transceivers									
FBGA (F)									
	484 (WF <sup>1</sup> ) 23 x 23 (mm) 1.0-mm pitch	484 (FF <sup>2</sup> ) 23 x 23 (mm) 1.0-mm pitch	780 (WF) 29 x 29 (mm) 1.0-mm pitch	780 (LF <sup>3</sup> ) 29 x 29 (mm) 1.0-mm pitch	780 (FF) 29 x 29 (mm) 1.0-mm pitch	1,152 (LF) 35 x 35 (mm) 1.0-mm pitch	1,152 (FF) 35 x 35 (mm) 1.0-mm pitch	1,517 (LF) 40 x 40 (mm) 1.0-mm pitch	1,517 (FF) 40 x 40 (mm) 1.0-mm pitch
HC4GX15				372 8+0					
HC4GX25				289 16+0		564 16+0	564 16+8		
HC4GX35							564 16+8		744 24+12
HC4E25	296	296	392		488				
HC4E35						744	744	880	880

<sup>636</sup><sub>8+0</sub> Values on top indicate available user I/O pins; values at the bottom indicate the 6.5-Gbps physical media attachment (PMA) and physical coding sublayer (PCS) plus the 6.5-Gbps PMA-only transceiver count.

All HardCopy series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

HardCopy III ASICs (0.9 V)								
FBGA (F)								
	484 (WF) 23 x 23 (mm) 1.0-mm pitch	484 (FF) 23 x 23 (mm) 1.0-mm pitch	780 (WF) 29 x 29 (mm) 1.0-mm pitch	780 (FF) 29 x 29 (mm) 1.0-mm pitch	1,152 (LF) 35 x 35 (mm) 1.0-mm pitch	1,152 (FF) 35 x 35 (mm) 1.0-mm pitch	1,517 (LF) 40 x 40 (mm) 1.0-mm pitch	1,517 (FF) 40 x 40 (mm) 1.0-mm pitch
HC325	296	296	392	488				
HC335					744	744	880	880

<sup>636</sup> Number indicates available user I/O pins.

All HardCopy series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

HardCopy II ASICs (0.9 V)								
FBGA (F)								
	484 (WF) 23 x 23 (mm) 1.0-mm pitch	484 (F <sup>4</sup> ) 23 x 23 (mm) 1.0-mm pitch	672 (WF) 27 x 27 (mm) 1.0-mm pitch	672 (F) 27 x 27 (mm) 1.0-mm pitch	780 (WF) 29 x 29 (mm) 1.0-mm pitch	780 (F) 29 x 29 (mm) 1.0-mm pitch	1,020 (F) 33 x 33 (mm) 1.0-mm pitch	1,508 (F) 40 x 40 (mm) 1.0-mm pitch
HC210W	308							
HC210		334						
HC220W			442		444			
HC220				492		494		
HC230							698	
HC240							742	951

<sup>1</sup> WF = Wire bond.

<sup>2</sup> FF = Performance-optimized flip chip.

<sup>3</sup> LF = Cost-optimized flip chip.

<sup>4</sup> F = Performance-optimized flip chip.

<sup>636</sup> Number indicates available user I/O pins.

All HardCopy series devices are offered in commercial and industrial temperatures and RoHS-compliant packages.

## Arria V GX FPGA Features

		Arria V GX FPGAs (1.1 V) <sup>1</sup> , 6.375-Gbps Transceivers							
		5AGXA1	5AGXA3	5AGXA5	5AGXA7	5AGXB1	5AGXB3	5AGXB5	5AGXB7
Density and Speed	ALMs	28,302	57,358	71,698	90,943	113,208	136,226	158,491	186,792
	Equivalent LEs	75,000	152,000	190,000	241,000	300,000	361,000	420,000	495,000
	Registers	113,208	229,434	286,792	363,774	452,830	544,906	633,962	747,170
	M10K memory blocks	488	1,016	1,153	1,336	1,377	1,680	2,006	2,324
	MLAB memory (Kb)	463	901	1,173	1,408	1,852	2,253	2,532	3,087
	Embedded memory (Kb)	5,000	10,400	11,800	13,680	14,100	17,280	20,540	23,800
	DSP blocks	240	396	600	800	920	1,045	1,092	1,139
	Speed grades (fastest to slowest)	-4, -5, -6							
Architectural Features	Global clock networks	16							
	PLLs/unique outputs	10/40	10/40	12/48	12/48	12/48	12/48	16/64	16/64
	Configuration file size (Mb)	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	Design security	✓							
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0, 3.3 <sup>2</sup>							
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2V HSTL (I and II), 1.5V HSTL (I and II), 1.8V HSTL (I and II)							
	LVDS channels, 1,250 Mbps (receive/transmit)	68	68	120	120	160	160	152	152
	Embedded DPA circuitry	✓							
	Series and differential OCT	✓							
	Programmable drive strength	✓							
	Transceiver (SERDES) channels (6.375 Gbps)	12	12	24	24	24	24	36	36
	PCIe Gen2 x4 hard IP blocks	1	1	2	2	2	2	2	2
	DDR3/2 hard memory controller IP blocks	2	2	4	4	4	4	4	4
External Memory Interfaces	Memory devices supported	DDR3, DDR2, DDR, QDR II, QDR II+, RLDRAM II, LPDDR2, Mobile DDR, SDR							

<sup>1</sup> Maximum LVDS channels, transceiver channels, PLLs, and PCIe hard IP blocks for the product line shown. Various packages offer a variety of options to meet your design needs.

<sup>2</sup> 3.3-V compliant, requires a 3.0-V power supply

## Arria V GT FPGA Features

		Arria V GT FPGAs (1.1 V) <sup>1</sup> , Up to 10.375-Gbps Transceivers	
		5AGTD3	5AGTD5
Density and Speed	ALMs	136,226	186,792
	Equivalent LEs	361,000	495,000
	Registers	544,906	747,170
	M10K memory blocks	1,680	2,324
	MLAB memory (Kb)	2,253	3,087
	Embedded memory (Kb)	17,280	23,800
	DSP blocks	1,045	1,139
	Speed grades (fastest to slowest)	TBD	
Architectural Features	Global clock networks	16	
	PLLs/unique outputs	12/48	16/64
	Configuration file size (Mb)	TBD	TBD
	Design security	✓	
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0, 3.3 <sup>2</sup>	
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2V HSTL (I and II), 1.5V HSTL (I and II), 1.8V HSTL (I and II)	
	LVDS channels, 1,250 Mbps (receive/transmit)	120	150
	Embedded DPA circuitry	✓	
	Series and differential OCT	✓	
	Programmable drive strength	✓	
	Transceiver (SERDES) channels (10.375 Gbps, 6.375 Gbps)	4, 18	6, 24
	PCIe Gen2 x4 hard IP blocks	1	1
	DDR3/2 hard memory controller IP blocks	1	4
External Memory Interfaces	Memory devices supported	DDR3, DDR2, DDR, QDR II, QDR II+, RDRAM II, LPDDR2, Mobile DDR, SDR	

<sup>1</sup> Maximum LVDS channels, transceiver channels, PLLs, and PCIe hard IP blocks for the product line shown. Various packages offer a variety of options to meet your design needs.

<sup>2</sup> 3.3-V compliant, requires a 3.0-V power supply

## Arria II GX FPGA Features

		Arria II GX FPGAs (0.9 V), Up to 6.375-Gbps Transceivers					
		EP2AGX45	EP2AGX65	EP2AGX95	EP2AGX125	EP2AGX190	EP2AGX260
Density and Speed	ALMs	18,050	25,300	37,470	49,640	76,120	102,600
	Equivalent LEs	45,125	63,250	93,675	124,100	190,300	256,500
	Registers <sup>1</sup>	36,100	50,600	74,940	99,280	152,240	205,200
	M9K memory blocks	319	495	612	730	840	950
	MLAB memory (Kb)	564	791	1,171	1,551	2,379	3,206
	Embedded memory (Kb)	2,871	4,455	5,508	6,570	7,560	8,550
	18-bit x 18-bit embedded multipliers	232	312	448	576	656	736
	Speed grades (fastest to slowest)	-3, -4, -5, -6					
Architectural Features	Global clock networks	16					
	Regional clock networks	48					
	Periphery clock networks	50	50	59	59	84	84
	PLLs/unique outputs	4/28	4/28	6/42	6/42	6/42	6/42
	Configuration file size (Mb)	18	18	34	34	64	64
	Design security	✓					
	Others	Plug & Play Signal Integrity					
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0, 3.3					
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, BLVDS, Differential SSTL-18, Differential SSTL-15, Differential SSTL-2, Differential HSTL-18, Differential HSTL-12, Differential HSTL-15, SSTL-18 (I and II), SSTL-15 (I), SSTL-2 (I and II), 1.8-V HSTL (I and II), 1.5-V HSTL (I and II), 1.2-V HSTL (I and II)					
	Emulated LVDS channels	56	56	64	64	96	96
	LVDS channels (receive/transmit)	85/84	85/84	105/104	105/104	145/144	145/144
	Embedded DPA circuitry	✓					
	Series and differential OCT	✓					
	Transceiver (SERDES) channels	8	8	12	12	16	16
External Memory Interfaces	PCIe hard IP block Gen1	1					
	Memory devices supported	DDR3, DDR2, DDR, QDR II					

<sup>1</sup>This is the base core logic register count. The ALM can support three registers when used in LUTREG mode, which increases total register count by an additional 50 percent.

## Arria II GZ FPGA Features

		Arria II GZ FPGAs (0.9 V), Up to 6.375-Gbps Transceivers		
		EP2AGZ225	EP2AGZ300	EP2AGZ350
Density and Speed	ALMs	89,600	119,200	139,400
	Equivalent LEs	224,000	298,000	348,500
	Registers	179,200	238,400	278,800
	M9K memory blocks	1,235	1,248	1,248
	M144K memory blocks	0	24	36
	MLAB memory (Kb)	2,850	4,420	4,420
	Embedded memory (Kb)	11,100	14,700	16,400
	18-bit x 18-bit embedded multipliers	800	920	1,040
	Speed grades (fastest to slowest)	-3, -4		
Architectural Features	Global clock networks	16		
	Regional clock networks	64	88	88
	Periphery clock networks	88		
	PLLs/unique outputs	8/68	8/96	8/96
	Configuration file size (Mb)	95	141	141
	Design security	✓		
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.0		
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15 (I and II), Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), 1.2-V HSTL (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)		
	Emulated LVDS channels	184	184	184
	LVDS channels (receive/transmit)	Up to 86		
	Embedded DPA circuitry	✓		
	Series and differential OCT	✓		
	Transceiver (SERDES) channels, 6.375 Gbps	Up to 24		
	PCIe hard IP block (value as 1.1, 2.0, etc)	1		
External Memory Interfaces	Memory devices supported	DDR3, DDR2, DDR, QDR II, RDRAM II, SDR		

Arria Series Package and I/O Matrices

Arria V GX and GT FPGAs (1.1 V), Up to 10.375-Gbps Transceivers				
FBGA (F)				
	672 pin 27 x 27 (mm) 1.0-mm pitch	896 pin 31 x 31 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch
5AGXA1	336 9			
5AGXA3	336 9			
5AGXA5	288 9	384 18	544 24	
5AGXA7	288 9	384 18	544 24	
5AGXB1		384 18	544 24	704 24
5AGXB3		384 18	544 24	704 24
5AGXB5			528 24	668 36
5AGXB7			528 24	668 36
5AGTD3		322 12+4	504 16+4	656 18+4
5AGTD5			488 18+6	616 24+6

<sup>636</sup><sub>8+0</sub> Values on top indicate available user I/O pins; values at the bottom indicate the 6.375-Gbps plus 10.375-Gbps transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table

Arria Series Package and I/O Matrices

Arria II GX FPGAs (0.9 V), Up to 6.375-Gbps Transceivers				
	UBGA (U) <sup>1</sup>	FBGA (F)		
	358 pin 17 x 17 (mm) 0.8-mm pitch	572 pin 25 x 25 (mm) 1.0-mm pitch	780 pin 29 x 29 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch
EP2AGX45	156 4	252 8	364 8	
EP2AGX65	156 4	252 8	364 8	
EP2AGX95		260 8	372 12	452 12
EP2AGX125		260 8	372 12	452 12
EP2AGX190			372 12	612 16
EP2AGX260			372 12	612 16

<sup>1</sup>Ultra-FineLine ball grid array

726  
24 Values on top indicate available user I/O pins; values at the bottom indicate the transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Arria II GZ FPGAs (0.9 V), Up to 6.375-Gbps Transceivers			
	Hybrid FBGA (H)	FBGA (F)	
	780 pin 33 x 33 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch	1,517 pin 40 x 40 (mm) 1.0-mm pitch
EP2AGZ225		550 16	726 24
EP2AGZ300	280 16	550 16	726 24
EP2AGZ350	280 16	550 16	726 24

636  
12 Values on top indicate available user I/O pins; values at the bottom indicate transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

## Cyclone V E FPGA Features

		Cyclone V E FPGAs (1.1 V)				
		5CEA2	5CEA5	5CEA8	5CEB5	5CEB9
Core Fabric	LEs	25,000	48,000	75,000	150,000	300,000
	M10K memory blocks (Kb)	1,560	3,120	4,620	6,160	12,760
	MLAB	25% of ALMs can be configured as MLABs				
	PLLs	4	4	4	4	4
	Global clock networks	16	16	16	16	16
Hard IP	DSP blocks	39	78	132	220	406
	PCIe hard IP blocks	–				
	Memory controllers	1	1	2	2	2
Interconnect	I/O voltage levels supported (V)	1.1, 1.2, 1.5, 1.8, 2.5, 3.3				
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), HiSpi, SLVS, Sub-LVDS				
	LVDS channels (875 Mbps receive, 840 Mbps transmit)	48	100	100	122	122
	Memory devices supported	DDR3, DDR2, DDR, LPDDR, LPDDR2				

## Cyclone V GX FPGA Features

		Cyclone V GX FPGAs (1.1 V), 3.125-Gbps Transceivers				
		5CGXC3	5CGXC4	5CGXC5	5CGXC7	5CGXC9
Core Fabric	LEs	25,000	50,000	75,000	150,000	300,000
	M10K memory blocks (Kb)	1,200	2,920	4,620	6,160	12,760
	MLAB	25% of ALMs can be configured as MLABs				
	PLLs	5	6	6	7	8
	Global clock networks	16	16	16	16	16
Hard IP	DSP blocks	40	70	132	220	406
	PCIe hard IP blocks	1	1	1	1	1
	Memory controllers	1	2	2	2	2
Interconnect	I/O voltage levels supported (V)	1.1, 1.2, 1.5, 1.8, 2.5, 3.3				
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), HiSpi, SLVS, Sub-LVDS				
	LVDS channels (875 Mbps receive, 840 Mbps transmit)	48	100	100	122	122
	Transceiver (SERDES) channels	3	6	6	9	12
	Memory devices supported	DDR3, DDR2, DDR, LPDDR, LPDDR2				

## Cyclone V GT FPGA Features

		Cyclone V GT FPGAs (1.1 V), 5G Transceivers		
		5CGTD3	5CGTD5	5CGTD8
Core Fabric	LEs	75,000	150,000	300,000
	M10K memory blocks (Kb)	4,620	6,160	12,760
	MLAB	25% of ALMs can be configured as MLABs		
	PLLs	6	7	8
	Global clock networks	16	16	16
Hard IP	DSP blocks	132	220	406
	PCIe hard IP blocks	2	2	2
	Memory controllers	2	2	2
Interconnect	I/O voltage levels supported (V)	1.1, 1.2, 1.5, 1.8, 2.5, 3.3		
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), HiSpi, SLVS, Sub-LVDS		
	LVDS channels (875 Mbps receive, 840 Mbps transmit)	100	122	122
	Transceiver (SERDES) channels	6	9	12
	Memory devices supported	DDR3, DDR2, DDR, LPDDR, LPDDR2		

## Cyclone IV GX FPGA Features

		Cyclone IV GX FPGAs (1.2 V) <sup>1</sup> , 3.125-Gbps Transceivers <sup>2</sup>						
		EP4CGX15	EP4CGX22	EP4CGX30	EP4CGX50	EP4CGX75	EP4CGX110	EP4CGX150
Density and Speed	LEs	14,400	21,280	29,440	49,888	73,920	109,424	149,760
	M9K memory blocks	60	84	120	278	462	666	720
	Embedded memory (Kb)	540	756	1,080	2,502	4,158	5,490	6,480
	18-bit x 18-bit multipliers	0	40	80	140	198	280	360
	Speed grades (fastest to slowest)	-6,-7,-8	-6,-7,-8	-6,-7,-8	-6,-7,-8	-6,-7,-8	-7,-8	-7,-8
Architectural Features	Global clock networks	20	20	20	30	30	30	30
	PLLs/unique outputs	3/15	4/20	4/20	8/40	8/40	8/40	8/40
	Configuration file size (Mb)	3.8	7.6	7.6	24.5	24.5	47.6	47.6
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3						
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)						
	Emulated LVDS channels	9	40	40	73	73	139	139
	LVDS channels, 840 Mbps (receive/transmit)	7/7	14/14	14/14	49/49	49/49	59/59	59/59
	Transceiver (SERDES) channels (2.5/3.125 Gbps)	2/0	2/0, 4/0	4/0, 0/4 <sup>3</sup>	0/8	0/8	0/8	0/8
	PCIe hard IP blocks Gen1	1						
External Memory Interfaces	Memory devices supported	DDR2, DDR, QDR II, RDRAM II, SDR						

<sup>1</sup>Maximum LVDS channels, transceiver channels, PLLs, and PCIe hard IP blocks for the product line shown. Various packages offer a variety of options to meet your design needs.

<sup>2</sup>Transceiver performance varies by product line and package offering.

<sup>3</sup>EP4CGX30 supports 3.125 Gbps only in F484 package option.

## Cyclone IV E FPGA Features

		Cyclone IV E FPGAs								
		EP4CE6	EP4CE10	EP4CE15	EP4CE22	EP4CE30	EP4CE40	EP4CE55	EP4CE75	EP4CE115
Density and Speed	LEs	6,272	10,320	15,408	22,320	28,848	39,600	55,856	75,408	114,480
	M9K memory blocks	30	46	56	66	66	126	260	305	432
	Embedded memory (Kb)	270	414	504	594	594	1,134	2,340	2,745	3,888
	18-bit x 18-bit multipliers	15	23	56	66	66	116	154	200	266
	Speed grades (fastest to slowest)	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L	-6, -7, -8 -8L, -9L
Architectural Features	Global clock networks	10	10	20	20	20	20	20	20	20
	PLLs/unique outputs	2/10	2/10	4/20	4/20	4/20	4/20	4/20	4/20	4/20
	Configuration file size (Mb)	2.8	2.8	3.9	5.5	9.1	9.1	14.2	19	27.2
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3								
	I/O standards supported	LVTTTL, LVCMOS, PCI, PCI-X, LVDS, mini-LVDS, RSDS, LVPECL, Differential SSTL-15, Differential SSTL-18, Differential SSTL-2, Differential HSTL-12, Differential HSTL-15, Differential HSTL-18, SSTL-15 (I and II), SSTL-18 (I and II), SSTL-2 (I and II), 1.2-V HSTL (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II)								
	LVDS channels	66	66	137	52	224	224	160	178	230
External Memory Interfaces	Memory devices supported	DDR2, DDR, QDR II, RLDRAM II, SDR								

## Cyclone III FPGA Features

		Cyclone III FPGAs (1.2 V)							
		EP3C5	EP3C10	EP3C16	EP3C25	EP3C40	EP3C55	EP3C80	EP3C120
Density and Speed	LEs	5,136	10,320	15,408	24,624	39,600	55,856	81,264	119,088
	M9K memory blocks	46	46	56	66	126	260	305	432
	Embedded memory (Kb)	414	414	504	594	1,134	2,340	2,745	3,888
	18-bit x 18-bit embedded multipliers	23	23	56	66	126	156	244	288
	Speed grades (fastest to slowest) <sup>1</sup>	-6, -7, -8	-6, -7, -8	-6, -7, -8	-6, -7, -8	-6, -7, -8	-6, -7, -8	-6, -7, -8	-6, -7, -8
Architectural Features	Global clock networks	10	10	20	20	20	20	20	20
	PLLs/unique outputs	2/10	2/10	4/20	4/20	4/20	4/20	4/20	4/20
	Configuration file size (Mb)	2.8	2.8	3.9	5.5	9.1	14.2	19	27.2
	Design security	✓							
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3							
	I/O standards supported	LVDS, LVPECL, Differential SSTL-18, Differential SSTL-2, Differential HSTL, SSTL-18 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), PCI, PCI-X 1.0, LVTTTL, LVCMOS							
	Emulated LVDS channels, 840 Mbps	66	66	136	79	223	159	177	229
	Series and differential OCT	✓							
External Memory Interfaces	Memory device supported	QDR II, DDR2, DDR, SDR							

<sup>1</sup>Not all packages are supported in all speed grades.

## Cyclone III LS FPGA Features

		Cyclone III LS FPGAs (1.2 V)			
		EP3CLS70	EP3CLS100	EP3CLS150	EP3CLS200
Density and Speed	LEs	70,208	100,488	150,848	198,464
	M9K memory blocks	333	483	666	891
	Embedded memory (Kb)	2,997	4,347	5,994	8,019
	18-bit x 18-bit embedded multipliers	200	276	320	396
	Speed grades (fastest to slowest) <sup>1</sup>	-7, -8			
Architectural Features	Global clock networks	20			
	PLLs/unique outputs	4/20			
	Configuration file size (Mb)	26.8	26.8	50.6	50.6
	Design security	✓			
I/O Features	I/O voltage levels supported (V)	1.2, 1.5, 1.8, 2.5, 3.3			
	I/O standards supported	LVDS, LVPECL, Differential SSTL-18, Differential SSTL-2, Differential HSTL, SSTL-18 (I and II), SSTL-2 (I and II), 1.5-V HSTL (I and II), 1.8-V HSTL (I and II), PCI, PCI-X 1.0, LVTTTL, LVCMOS			
	LVDS channels, 840 Mbps	169			
	Series and differential OCT	✓			
External Memory Interfaces	Memory device supported	QDR II, DDR2, DDR, SDR			

<sup>1</sup>Not all packages are supported in all speed grades.

Cyclone Series Package and I/O Matrices

Cyclone V E, GX, and GT FPGAs (1.1 V), Up to 5G Transceivers							
EQFP (E)	UBGA (U)	FBGA (F)					
144 pin 22 x 22 (mm) 0.5-mm pitch	484 pin 19 x 19 (mm) 8.0-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch	324 pin 19 x 19 (mm) 1.0-mm pitch	484 pin 23 x 23 (mm) 1.0-mm pitch	672 pin 25 x 25 (mm) 1.0-mm pitch	896 pin 31 x 31 (mm) 1.0-mm pitch	1,152 pin 35 x 35 (mm) 1.0-mm pitch
5CEA2	90	300	140	300			
5CEA5	90	300	140	300			
5CEA8		260		260	360		
5CEB5				260	345	488	
5CEB9					345	488	
5CGXC3		194 3	97 3	114 3	194 3		
5CGXC4		238 6		120 6	238 6	360 6	
5CGXC5		238 6		120 6	238 6	360 6	
5CGXC7				230 6	345 9	488 9	
5CGXC9					345 9	488 9	688 12
5CGTD3		238 6		238 6	360 6		
5CGTD5				230 6	345 9	488 9	
5CGTD8					345 9	488 9	688 12

636  
12 Values on top indicate available user I/O pins; values at the bottom indicate the 3.125-Gbps or 5G transceiver count.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

## Cyclone Series Package and I/O Matrices

Cyclone IV GX FPGAs (1.2 V), Up to 3.125-Gbps Transceivers						
	QFN (N)	FBGA (F)				
	148 pin 11 x 11 (mm) 0.5-mm pitch	169 pin 14 x 14 (mm) 1.0-mm pitch	324 pin 19 x 19 (mm) 1.0-mm pitch	484 pin 23 x 23 (mm) 1.0-mm pitch	672 pin 27 x 27 (mm) 1.0-mm pitch	896 pin 31 x 31 (mm) 1.0-mm pitch
EP4CGX15	72 2	72 2				
EP4CGX22		72 2	150 4			
EP4CGX30		72 2	150 4	290 4		
EP4CGX50				290 4	310 8	
EP4CGX75				290 4	310 8	
EP4CGX110				270 4	393 8	475 8
EP4CGX150				270 4	393 8	475 8

636  
12

Values on top indicate available user I/O pins; values at the bottom indicate the 2.5-Gbps or 3.125-Gbps transceiver count.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Cyclone IV E FPGAs (1.0 V and 1.2 V)							
	EQFP (E) <sup>1</sup>	FBGA (F)		MBGA (M)	UBGA (U)		
	144 pin 22 x 22 (mm) 0.5-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch	484 pin 23 x 23 (mm) 1.0-mm pitch	780 pin 29 x 29 (mm) 1.0-mm pitch	164 pin 8 x 8 (mm) 0.5-mm pitch	265 pin 14 x 14 (mm) 0.8-mm pitch	484 pin 19 x 19 (mm) 0.8-mm pitch
EP4CE6	91	179				179	
EP4CE10	91	179				179	
EP4CE15	81	165	343		74	165	
EP4CE22	79	153				153	
EP4CE30			328	532			
EP4CE40			328	532			328
EP4CE55			324	374			324
EP4CE75			292	426			292
EP4CE115			280	528			

<sup>1</sup> Enhanced thin quad flat pack

636 Number indicates available user I/O pins.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

## Cyclone Series Package and I/O Matrices

	Cyclone III FPGAs (1.2 V)								
	EQFP1 (E)	MBGA (M) <sup>1</sup>	PQFP (Q) <sup>2</sup>	FBGA (F)				UBGA (U)	
	144 pin 22 x 22 (mm) 0.5-mm pitch	164 pin 8 x 8 (mm) 0.5-mm pitch	240 pin 34.6 x 34.6 (mm) 0.5-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch	324 pin 19 x 19 (mm) 1.0-mm pitch	484 pin 23 x 23 (mm) 1.0-mm pitch	780 pin 29 x 29 (mm) 1.0-mm pitch	256 pin 14 x 14 (mm) 0.8-mm pitch	484 pin 19 x 19 (mm) 0.8-mm pitch
EP3C5	94	106		182				182	
EP3C10	94	106		182				182	
EP3C16	84	92	160	168		346		168	346
EP3C25	82		148	156	215			156	
EP3C40			128		195	331	535		331
EP3C55						327	377		327
EP3C80						295	429		295
EP3C120						283	531		
EP3CLS70						278	413		278
EP3CLS100						278	413		278
EP3CLS150						210	413		
EP3CLS200						210	413		

<sup>1</sup>Micro FineLine BGA.

<sup>2</sup>Plastic quad flat pack.

636 Number indicates available user I/O pins.

Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

## MAX V CPLD Features

		MAX V CPLDs (1.8 V)							
		5M40Z	5M80Z	5M160Z	5M240Z	5M570Z	5M1270Z	5M2210Z	
Density and Speed	LEs	40	80	160	240	570	1270	2210	
	Equivalent macrocells <sup>1</sup>	32	64	128	192	440	980	1700	
	Pin-to-pin delay (ns)	7.5	7.5	7.5	7.5	9.0	6.2	7.0	
	User flash memory (Kb)	8							
	Total on-chip memory (bits) <sup>2</sup>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Architectural Features	Internal oscillator	✓							
	Digital PLL <sup>3</sup>	✓							
	Fast power on reset	✓							
	Boundary scan JTAG	✓							
	JTAG ISP	✓							
	Fast input registers	✓							
	Programmable register power up	✓							
	JTAG translator	✓							
Real-time ISP	✓								
I/O Features	MultiVolt I/Os (V)	1.2, 1.5, 1.8, 2.5, 3.3					1.2, 1.5, 1.8, 2.5, 3.3, 5.0 <sup>4</sup>		
	I/O power banks	2	2	2	2	2	4	4	
	Maximum output enables	54	54	79	114	159	271	271	
	LVTTTL/LVCMOS	✓							
	LVDS outputs	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
	32-bit, 66-MHz PCI compliant	-	-	-	-	-	✓ <sup>4</sup>	✓ <sup>4</sup>	
	Schmitt triggers	✓							
	Programmable slew rate	✓							
	Programmable pull-up resistors	✓							
	Programmable ground pins	✓							
	Open-drain outputs	✓							
	Bus hold	✓							

<sup>1</sup>Typical equivalent macrocells.

<sup>2</sup>Unused LEs can be converted to memory. The total number of available LE RAM bits depends on the memory mode, depth, and width configurations of the instantiated memory.

<sup>3</sup>Optional IP accessed via Quartus II megafuction GUI.

<sup>4</sup>An external resistor must be used for 5-V tolerance.

## MAX II CPLD Features

		MAX II CPLDs (3.3 V, 2.5 V, 1.8 V)			
		EPM240/Z	EPM570/Z	EPM1270	EPM2210
Density and Speed	Equivalent macrocells <sup>1</sup>	192	440	980	1,700
	Pin-to-pin delay (ns)	4.7, 7.5	5.4, 9.0	6.2	7.0
Architectural Features	User flash memory (Kb)	8			
	Boundary scan JTAG	✓			
	JTAG ISP	✓			
	Fast input registers	✓			
	Programmable register power up	✓			
	JTAG translator	✓			
	Real-time ISP	✓			
I/O Features	MultiVolt I/Os (V)	1.5, 1.8, 2.5, 3.3	1.5, 1.8, 2.5, 3.3	1.5, 1.8, 2.5, 3.3, 5.0 <sup>2</sup>	1.5, 1.8, 2.5, 3.3, 5.0 <sup>2</sup>
	I/O power banks	2	2	4	4
	Maximum output enables	80	160	212	272
	LVTTTL/LVCMOS	✓			
	32-bit, 66-MHz PCI compliant	-	-	✓ <sup>2</sup>	✓ <sup>2</sup>
	Schmitt triggers	✓			
	Programmable slew rate	✓			
	Programmable pull-up resistors	✓			
	Programmable ground pins	✓			
	Open-drain outputs	✓			
	Bus hold	✓			

<sup>1</sup>Typical equivalent macrocells.<sup>2</sup>An external resistor must be used for a 5-V tolerance.

## MAX 3000A CPLD Features

		MAX 3000A CPLDs (3.3 V)				
		EPM3032A	EPM3064A	EPM3128A	EPM3256A	EPM3512A
Density and Speed	Macrocells	32	64	128	256	512
	Equivalent LEs	40	80	160	320	640
	Pin-to-pin delay (ns)	4.5, 7.5, 10	4.5, 7.5, 10	5.0, 7.5, 10	7.5, 10	7.5, 10
Architectural Features	Boundary scan JTAG	✓				
	JTAG ISP	✓				
	Fast input registers	✓				
	Programmable register power up	✓				
I/O Features	MultiVolt I/Os (V)	2.5, 3.3, 5.0				
	I/O power banks	1				
	Maximum output enables	6	6	6	6	10
	LVTTTL/LVCMOS	✓				
	Programmable slew rate	✓				
	Open-drain outputs	✓				

MAX Series Package and I/O Matrices

MAX V CPLDs (1.8 V) <sup>1</sup>							
EQFP (E) <sup>2</sup>	TQFP (T) <sup>3</sup>		MBGA (M) <sup>4</sup>			FBGA (F)	
64 pin 7 x 7 (mm) 0.4-mm pitch	100 pin 14 x 14 (mm) 0.5-mm pitch	144 pin 20 x 20 (mm) 0.5-mm pitch	64 pin 4.5 x 4.5 (mm) 0.5-mm pitch	68 pin 5 x 5 (mm) 0.5-mm pitch	100 pin 6 x 6 (mm) 0.5-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch	324 pin 19 x 19 (mm) 1.0-mm pitch
5M40Z	54		30				
5M80Z	54	79	30	52			
5M160Z	54	79		52	79		
5M240Z		79		52	79		
5M570Z		74			74	159	
5M1270Z			114			211	271
5M2210Z						203	271

MAX II CPLDs (3.3 V, 2.5 V, 1.8 V) <sup>1</sup>								
TQFP (T)		FBGA (F)			MBGA (M)			
100 pin 16 x 16 (mm) 0.5-mm pitch	144 pin 22 x 22 (mm) 0.5-mm pitch	100 pin 11 x 11 (mm) 1.0-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch	324 pin 16 x 16 (mm) 0.5-mm pitch	68 pin 5 x 5 (mm) 0.5-mm pitch	100 pin 6 x 6 (mm) 0.5-mm pitch	144 pin 7 x 7 (mm) 0.5-mm pitch	256 pin 11 x 11 (mm) 0.5-mm pitch
EPM240Z					54	80		
EPM570Z						76	116	160
EPM240	80		80			80		
EPM570	76	116	76	160		76		160
EPM1270		116		212				212
EPM2210				204	272			

MAX 3000A CPLDs (3.3 V)					
PLCC (L) <sup>5</sup>	TQFP (T)		PQFP (Q) <sup>6</sup>		FBGA (F)
44 pin 17.5 x 17.5 (mm) 1.27-mm pitch	44 pin 12 x 12 (mm) 0.5-mm pitch	100 pin 16 x 16 (mm) 0.5-mm pitch	144 pin 22 x 22 (mm) 0.5-mm pitch	208 pin 28 x 28 (mm) 0.5-mm pitch	256 pin 17 x 17 (mm) 1.0-mm pitch
EPM3032A	34	34			
EPM3064A	34	34	66		
EPM3128A			80	96	98
EPM3256A				116	158
EPM3512A				172	208

<sup>1</sup>For temperature grades of specific packages (commercial, industrial, or extended temperatures), refer to Altera's online selector guide.

<sup>2</sup>Enhanced quad flat pack

<sup>3</sup>Thin quad flat pack

<sup>4</sup>Micro FineLine BGA (0.5 mm)

<sup>5</sup>Plastic J-lead chip carrier

<sup>6</sup>Plastic quad flat pack

 Number indicates available user I/O pins.

 Vertical migration (same V<sub>CC</sub>, GND, ISP, and input pins). For vertical migration, the number of user I/Os may be less than the number stated in the table.

Quartus II software is #1 in performance and productivity for CPLD, FPGA, and ASIC designs, providing the fastest path to convert your concept into reality. Quartus II software also supports many third-party tools in synthesis, static timing analysis, board-level simulation, signal integrity analysis, and formal verification.

Quartus II Design Flow			
Quartus II Key Features		Availability	
		Subscription Edition	Web Edition (Free)
<b>Design Entry</b>	Cyclone, Arria, and MAX series device support	✓	✓
	Arria II and Stratix series device support <sup>1</sup>	✓	
	HardCopy ASIC device support	✓	
	Multiprocessor support (Faster compile time support)	✓	
	IP Base Suite (Includes licenses for 15 popular IP cores)	✓	
	SOPC Builder (Legacy system development tool)	✓	✓
	Rapid Recompile (Faster compile for small design changes)	✓	
	Incremental compile (Performance preservation and team-based design)	✓	
<b>Functional Simulation</b>	ModelSim®-Altera Starter Edition	✓	✓
	ModelSim-Altera Edition	✓ <sup>2</sup>	✓ <sup>2</sup>
<b>Synthesis</b>	Quartus Integrated Synthesis (Synthesis tool)	✓	✓
<b>Placement and Route</b>	Fitter (Placement and routing tool)	✓	✓
<b>Timing and Power Verification</b>	TimeQuest tool (Static timing analysis)	✓	✓
	PowerPlay tool and optimization (Power analysis)	✓	✓
<b>In-system Debug</b>	SignalTap™ II logic analyzer (Embedded logic analyzer) <sup>3</sup>	✓	
	Transceiver toolkit (Transceiver interface and verification tool)	✓	
Operating System Support		Availability	
		Subscription Edition	Web Edition (Free)
Windows/Linux 32-bit support		✓	✓
Windows/Linux 64-bit support		✓	

<sup>1</sup>Lowest density devices for Arria II and Stratix series FPGAs may be included in Web Edition.

<sup>2</sup>Requires additional license.

<sup>3</sup>Available with talkback feature enabled in Web Edition.

## Quartus II Design Software

Quartus II Design Software Features Summary		
Design Flow Methodology	Incremental compilation <sup>1</sup>	Improves design timing closure and reduces design compilation times up to 70 percent. Supports team-based design.
	Pin planner	Eases the process of assigning and managing pin assignments for high-density and high pin-count designs.
	SOPC Builder	Automates adding, parameterizing, and linking IP cores—including embedded processors, coprocessors, peripherals, memories, and user-defined logic.
	Off-the-shelf IP cores	Lets you construct your system-level design using IP cores from Altera's megafunction library and from Altera's third-party IP partners.
	Parallel development in ASICs <sup>1</sup>	Allows for FPGA prototypes and HardCopy ASICs to be designed in parallel using the same design software and IP.
	Scripting support	Supports command-line operation and Tcl scripting, as well as GUI design.
	Rapid Recompile <sup>1</sup>	Maximizes your productivity by reducing your compilation time by 50 percent on average (for a small design change after a full compile). Improves design timing preservation.
Performance and Timing Closure Methodology	Physical synthesis	Uses post placement-and-route delay knowledge of a design to improve performance.
	Design space explorer (DSE)	Increases performance by automatically iterating through combinations of Quartus II software settings to find optimal results.
	Extensive cross-probing	Provides unmatched support for cross-probing between verification tools and design source files.
	Optimization advisors	Provides design-specific advice to improve design timing performance, resource usage, and power consumption.
	Chip planner	Reduces verification time (while maintaining timing closure) by enabling small, post placement-and-route design changes to be implemented in minutes.
Verification	TimeQuest timing analyzer	Provides native Synopsys Design Constraint (SDC) support and allows you to create, manage, and analyze complex timing constraints and quickly perform advanced timing verification.
	SignalTap II embedded logic analyzer	Supports the most channels, fastest clock speeds, largest sample depths, and most advanced triggering capabilities available in an embedded logic analyzer.
	PowerPlay technology	Enables you to accurately analyze and optimize both dynamic and static power consumption.
Third-party Support	EDA partners	Offers EDA software support for synthesis, functional and timing simulation, static timing analysis, board-level simulation, signal integrity analysis, and formal verification. To see a complete list of partners, follow the link: <a href="http://www.altera.com/products/software/partners/eda_partners/eda/index.html">http://www.altera.com/products/software/partners/eda_partners/eda/index.html</a>

<sup>1</sup> Included in Subscription Edition only.

### Getting Started Steps

#### Step 1: Download free Web Edition

[http://www.altera.com/support/software/download/sof-download\\_center.html](http://www.altera.com/support/software/download/sof-download_center.html)

#### Step 2: Get oriented with Quartus II interactive tutorial

After installation, open the interactive tutorial at the welcome screen.

#### Step 3: Sign up for training

<http://www.altera.com/education/training/trn-index.jsp>

## Quartus II Design Software

Purchase Quartus II software and increase your productivity today.

Pricing	Description
<b>\$2,995</b> (SW-QUARTUS-SE-FIX) Renewal \$2,495 (SWR-QUARTUS-SE-FIX)	Fixed-node license: Subscription for one year—Windows only
<b>\$3,995</b> (SW-QUARTUS-SE-FLT) Renewal \$2,495 (SWR-QUARTUS-SE-FLT) Add seat \$3,995 (SW-QUARTUS-SE-ADD)	Floating-node license: Subscription for one year—Windows/Linux

ModelSim-Altera Edition	
<b>\$945</b> (SW-MODELSIM-AE) Renewal \$945 (SWR-MODELSIM-AE)	ModelSim-Altera Edition is available as a \$945 option for both Quartus II Subscription Edition and Web Edition. It's 33 percent faster than Starter Edition with no line limitation.
ModelSim-Altera Starter Edition	
<b>Free</b>	Free for both Quartus II Subscription Edition and Web Edition with a 10,000 executable line limitation, ModelSim-Altera Starter Edition is recommended for simulating small FPGA designs.

Altera’s FPGA and HardCopy ASIC devices are increasingly being adopted for custom system-on-chip (SOC) applications. Altera offers the industry’s broadest selection of soft processors, software development tools, OS support, and embedded IP cores. All of these elements support a single FPGA design flow based on Quartus II design software.


Embedded Processor Portfolio		
Processor	Company	Description
Nios® II processor	Altera	The FPGA industry’s #1 soft processor, the Nios II processor has a versatile feature set that provides unprecedented real-time control for your custom SOC applications.
Cortex-M1 processor	ARM	The ARM® Cortex-M1 processor allows you to use your favorite ARM software development tools and the popular Thumb-2 Instruction Set Architecture (ISA) with Altera’s FPGA and HardCopy ASIC-based systems.
V1 ColdFire processor	Freescale	This small-footprint version of the popular processor allows you to reuse your code and development tools for custom solution development on FPGAs.

### Nios II Embedded Processors

The Nios II processor in any one of Altera’s FPGA and HardCopy devices offers a custom system-on-chip solution that has the flexibility of software and the performance of hardware. Through its innovative design, the Nios II processor leverages the logic resources of the device to provide unprecedented hard and soft real-time capabilities. You can:

- Lower overall system cost, complexity, and power consumption by integrating the processor with the FPGA.
- Scale performance with multiple processors, custom instructions (hardware acceleration of an instruction) or co-processing (hardware accelerator next to the soft processor).
- Target any Stratix, Cyclone, or Arria series FPGA or HardCopy series ASIC.
- Eliminate the risk of processor and ASSP obsolescence.
- Take advantage of a royalty-free Nios II core license that never expires, by buying a Nios II license as a standalone offering or part of the Embedded IP Suite.

### Nios II Processor Development Flow



Software and Operating System Support		
	Product Name	Vendors
Operating Systems	eCos	eCosCentric, ZYLin
	embOS	Segger
	Erika Enterprise	Evidence
	Euros RTOS	Euros
	Linux	Timesys, SLS, Wind River, community supported
	MicroC/OS II, MicroC/OS-III	Micrium
	osCAN (OSEK/VDX-OS)	Vector
	ThreadX	Express Logic
	µCLinux	SLS, community supported
	NORTi (uLTRON)	MiSPO
Tools	Nios II Embedded Design Suite (EDS)	Altera
	Trace32 Logic Development System	Lauterbach
	Wind River Workbench	Wind River
	Univers Unified Verification Solution	Adveda
	Tasking VX-toolset	Altium
	System Navigator	First Silicon Solutions

Nios II EDS Contents
Code Development Tool: Nios II Software Build Tools for Eclipse
<ul style="list-style-type: none"> <li>• New project wizards</li> <li>• Software templates</li> <li>• Source navigator and editor</li> <li>• Compiler for C and C++ (GNU)</li> <li>• Based on industry-standard Eclipse</li> </ul>
Source Debugger/Profiler
Flash Programmer
Embedded Software
<ul style="list-style-type: none"> <li>• Hardware Abstraction Layer (HAL)</li> <li>• MicroC/OS-II real-time operating system<sup>1</sup></li> <li>• NicheStack TCP/IP Network Stack—Nios II Edition<sup>1</sup></li> <li>• Newlib ANSI-C standard library</li> <li>• Simple file system</li> </ul>
Other Altera Command-line Tools and Utilities
Design Examples
C Acceleration Tools: Nios II C-to-Hardware (C2H) Acceleration Compiler <sup>1</sup>

### Embedded Design Tool Suite

The Nios II EDS is a collection of all of the tools, utilities, libraries, and drivers needed to develop embedded software for the Nios II processor. It includes the Nios II Software Build Tools for Eclipse for editing, compiling, debugging, and programming flash devices. The Nios II EDS automatically generates a BSP for your software application by adding C libraries and device drivers for Altera-provided peripheral IP. The BSP editor provides full control over your build options board support package management.

<sup>1</sup> Production license sold separately.

## Nios II Embedded Processors

### CPU Core Options

The Nios II processor family has three CPU core options with a common 32-bit instruction set architecture, binary code compatibility, and the same software design suite. Choose the CPU appropriate for your designs, create multi-core systems to scale performance, or break up software applications into simpler tasks.

Nios II Processor Family Members			
Features	Nios II/f (Fast) Processor	Nios II/s (Standard) Processor	Nios II/e (Economy) Processor*
Description	Optimized for maximum performance; optional memory management unit (MMU)	Balanced cost and performance	Optimized for minimum logic usage
Pipeline	6 stage	5 stage	1 stage
Multiplier	1 cycle	3 cycle	Emulated in software
Branch prediction	Dynamic	Static	None
Instruction cache	Configurable	Configurable	None
Data cache	Configurable	None	None
Custom instructions	Up to 256	Up to 256	Up to 256

\*The Nios II/e processor is now available for free. No license is required.

### Hardware Development Tools

- Quartus II design software
- SOPC Builder system integration tools
- SignalTap II embedded logic analyzer plug-in for Nios II processor
- System console for low-level debug of SOPC Builder systems

### Licensing

When you're ready to ship your product, you'll need the Nios II core license. This royalty-free license never expires and allows you to target your processor design on any Altera FPGA. The Embedded IP Suite is a value bundle that contains licenses of the Nios II processor IP core, DDR1/2 Memory Controller IP core, Triple Speed Ethernet (TSE) MAC IP core, and the NicheStack TCP/IP Network Stack, Nios II Edition software.

### Development Kits

Go to page 50 for information about embedded development kits.

### Nios II C2H Compiler

Right-click to convert your ANSI-C code into hardware accelerators in the FPGA using the Nios II C2H Acceleration Compiler. Accelerate Nios II embedded software performance from 10X to 70X without increasing clock frequency. The tool automates the creation and integration of hardware accelerators, reducing development time from weeks to minutes.

The following is a partial list of IP functions from Altera and its partners. To get the full story, check out our online selector guide.

	Product Name	Vendor Name
DSP	<b>Error Detection/Correction</b>	
	Reed-Solomon Compiler Decoder	Altera
	Reed-Solomon Compiler Encoder	Altera
	Reed Solomon Encoder/Decoder II	Altera
	Viterbi Compiler, High-speed Parallel Decoder	Altera
	Viterbi Compiler, Low-speed/Hybrid Serial Decoder	Altera
	DVB-RCS CTC Turbo Decoder	TurboConcept
	WiMAX CTC Decoder	TurboConcept
	3GPP/LTE CTC Decoder	TurboConcept
	Turbo Product Code Decoder	TurboConcept
	<b>Filters and Transforms</b>	
	Fast Fourier Transform (FFT)/Inverse FFT (IFFT)	Altera
	Cascaded Integrator Comb (CIC) Compiler	Altera
	Finite Impulse Response (FIR) Compiler	Altera
	FIR Compiler II	Altera
	2D Forward/Inverse Discrete Cosine Transform	CAST, Inc.
	2D Inverse Discrete Cosine Transform (IDCT)	CAST, Inc.
	Forward Discrete Cosine Transform (DCT)	CAST, Inc.
	<b>Modulation/Demodulation</b>	
	Numerically Controlled Oscillator Compiler	Altera
	DVB-C/J.83 (QAM) Modulator	Commsonic
	DVB/H T/H Modulator	Commsonic
	DVB-S2 Modulator	Commsonic
	<b>Video and Image Processing</b>	
	Video and Image Processing Suite	Altera
	Fast Black and White JPEG Decoder	Barco Silex
	Fast Color JPEG Decoder	Barco Silex
	JPEG2000 Encoder and Decoder	Barco Silex
	JPEG2000 Decoder	Barco Silex
	JPEG CODEC	CAST, Inc.

	Product Name	Vendor Name
DSP (Continued)	JPEG Encoders and Decoders	CAST, Inc.
	Lossless JPEG Encoder and Decoder	CAST, Inc.
	H.264 AVC High-definition (HD) Video Decoder	CAST, Inc.
	Color Space Converter	CAST, Inc.
	Forward Discrete Wavelet Transform (FDWT)	Barco Silex
	Inverse Discrete Wavelet Transform (IDWT)	Barco Silex
	V-by-One HS	Bitec
	DisplayPort Receiver	Bitec
	H.264 Main/Baseline Profile Encoder	EyeLytics
	Video LVDS Serializer/Deserializer (SERDES) Transmitter/Receiver	Microtronix
	<b>Additional Functions</b>	
	Floating-point Addition/Subtraction	Altera
	Floating-point Multiplication	Altera
	Floating-point Division	Altera
	Floating-point Square Root	Altera
	Floating-point Compare	Altera
	Floating Point Arithmetic Unit <sup>1</sup>	Digital Core Design
	Floating Point Mathematics Unit <sup>1</sup>	Digital Core Design
	Floating Point Pipelined Divider Unit	Digital Core Design
	Floating Point to Integer Pipelined Converter	Digital Core Design
	Integer to Floating Point Pipelined Converter	Digital Core Design
	SHA-1	CAST, Inc.
	SHA-256	CAST, Inc.
	AES CODEC	CAST, Inc.
	AES Programmable Codec	CAST, Inc.
	D/AVE 2D Vector Graphics	TES Electronic Solutions
	D/AVE 2D Graphics Hardware Accelerator	TES Electronic Solutions

<sup>1</sup>SOPC Builder-ready licensed core.

## Altera and Partner Functions

	Product Name	Vendor Name
Embedded Processors	<b>32-/16-bit</b>	
	Nios II Embedded Processor <sup>1</sup>	Altera
	ARM Cortex-M1 <sup>1</sup>	Arrow Electronics/ARM
	V1 ColdFire <sup>1</sup>	Freescale
	C68000 AHB Microprocessor	CAST, Inc.
	C68000 Microprocessor	CAST, Inc.
	C80186EC Microprocessor	CAST, Inc.
	C80186XL Microprocessor	CAST, Inc.
	<b>8-bit</b>	
	CZ80CPU Processor	CAST, Inc.
	T8051	CAST, Inc.
	8051XC2 Microcontroller	CAST, Inc.
	DR8051 8-bit RISC Microcontroller	Digital Core Design
	DR8052EX 8-bit RISC Extended Microcontroller	Digital Core Design
	DF6811CPU 8-bit Microcontroller CPU	Digital Core Design
	DFPIC1655X RISC Microcontroller	Digital Core Design
	Interface and Protocols	<b>Communication</b>
8B/10B Encoder/Decoder		Altera
AAL5		Modelware
Inverse Multiplexing for ATM (IMA) Version 1.0/1.1		Modelware
ATM Formatter and Deformatter		Adaptive Micro-Ware, Inc.
CRC Compiler		Altera
Frame-mapped GFP Controller		Nuvation
GEOS-10: 10:1 Gbps Ethernet to SONET Multiplexer		Nuvation
GEOS2+2		Nuvation
Multi-channel HDLC		Modelware
Single-channel HDLC <sup>1</sup>		Modelware
POS-PHY Level 2 and 3, Link and PHY		Modelware
POS-PHY Level 4		Altera
SDLC Controller		CAST, Inc.
SONET/SDH Deframer		Aliathon

	Product Name	Vendor Name
Interface and Protocols (Continued)	SONET/SDH Demapper	Aliathon
	SONET/SDH Framer	Aliathon
	SONET/SDH Mapper	Aliathon
	OTN Framer/Deframer	Avalon Microelectronics
	SFI-5.1	Avalon Microelectronics
	FlexBUS-3 Link Layer	Modelware
	SPI-4 Phase 1 (FlexBUS-4)	Modelware
	SPI-4.2 Foundation and Manager	Modelware
	T1 Framer <sup>1</sup>	Adaptive Micro-Ware, Inc.
	T1 Deframer	Adaptive Micro-Ware, Inc.
	UTOPIA Level 2 Master	Modelware
	UTOPIA Level 2 Slave	Modelware
	<b>Ethernet</b>	
	10-Gbps Ethernet	Altera
	Tri-speed Ethernet (MAC and PCS) <sup>1</sup>	Altera
	10G Base-R PHY	Altera
	10G Base-X (XAUI) PHY	Altera
	40G/100G Ethernet	Altera
	40G/100G Ethernet	MorethanIP
	MAC-1G/1G PCS GbE MAC and PCS	CAST, Inc.
	Ethernet MAC Controller with PCI Host Interface (MAC-PCI)	CAST, Inc.
GbE MAC <sup>1</sup>	IFI	
Advanced GbE MAC <sup>1</sup>	IFI	
10/100/1000 Ethernet MAC with SGMII	MorethanIP	
AnySpeed Ethernet MAC	MorethanIP	
10/100 Ethernet MAC	MorethanIP	
10/100 Ethernet MAC <sup>1</sup>	SLS Corp	
10GbE MAC and PCS	MorethanIP	
RXAUI PCS	MorethanIP	
SPAUI MAC	MorethanIP	

<sup>1</sup>SOPC Builder-ready licensed core.

## Altera and Partner Functions

	Product Name	Vendor Name
Interface and Protocols (Continued)	10 Gigabit Reduced XAUI PCS	MorethanIP
	Fast XAUI	Octera
	10G MAC Lite	Octera
	<b>High Speed</b>	
	Serial RapidIO® <sup>1</sup>	Altera
	CPRI	Altera
	Interlaken	Altera
	SerialLite II	Altera
	HyperTransport 16-bit	GDA Technologies
	HyperTransport 3.0	University of Heidelberg
	SATA 1.0/SATA 2.0	Intelliprop, Inc.
	Serial Attached SCSI (SAS) 1.0 and 2.0	Intelliprop, Inc.
	<b>PCI</b>	
	PCIe Gen1 x1, x4, x8 Controller (Soft IP) <sup>1</sup>	Altera
	PCIe Gen1 and Gen2 x1, x4, and x8 Lane (Hard IP)	Altera
	PCIe Controller	CAST, Inc.
	PCIe x8 Controller	CAST, Inc.
	PCIe Gen1 x1, x4, x8 Controller	Northwest Logic, Inc.
	PCIe Complete Core x1, x4, x8	Northwest Logic, Inc.
	PCIe, Gen1 and Gen2	PLDA
	PCI-X Master/Target Core 32-/64-bit	PLDA
	PCI-X Controller	Northwest Logic, Inc.
	PCI Compiler, 32-bit Master/Target <sup>1</sup>	Altera
	PCI Compiler, 32-bit Target <sup>1</sup>	Altera
	PCI Compiler, 64-bit Master/Target <sup>1</sup>	Altera
	PCI Compiler, 64-bit Target <sup>1</sup>	Altera
	32-bit PCI Bus Master/Target Interface <sup>1</sup>	Eureka Technology, Inc.

	Product Name	Vendor Name
Interface and Protocols (Continued)	32-bit PCI Host Bridge	Eureka Technology, Inc.
	64-bit PCI Bus Master/Target Interface <sup>1</sup>	Eureka Technology, Inc.
	64-bit PCI Host Bridge	Eureka Technology, Inc.
	Integrated PCI Core	Northwest Logic, Inc.
	PCI Interface	Northwest Logic, Inc.
	PCI 32-/64-bit PCI Master/Target 33-/66-MHz Controllers	CAST, Inc.
	PCI Multifunction Target Interface	CAST, Inc.
	PCI Bus Arbiter	Eureka Technology, Inc.
	PCI-ISA Bridge	Eureka Technology, Inc.
	PCI-PCI Bridge	Eureka Technology, Inc.
	<b>Serial</b>	
	I <sup>2</sup> C Bus Controller <sup>1</sup>	CAST, Inc.
	I <sup>2</sup> C Bus Controller Slave	CAST, Inc.
	DI2CM I <sup>2</sup> C Bus Interface-Master <sup>1</sup>	Digital Core Design
	DI2CSB I <sup>2</sup> C Bus Interface-Slave <sup>1</sup>	Digital Core Design
	I <sup>2</sup> C Master/Slave/PIO Controller	Microtronix, Inc.
	I <sup>2</sup> C Master and Slave	SLS
	C_CAN <sup>1</sup>	Bosch
	CAN <sup>1</sup>	CAST, Inc.
	Nios_CAN <sup>1</sup>	IFI
	Nios II Advanced CAN <sup>1</sup>	IFI
	ATA-4 Host Controller	Nuvation
	ATA-5 Host Controller	Nuvation
	MediaLB Device Interface	IFI
	PS2 Interface	SLS
	USB High-speed Function Controller <sup>1</sup>	SLS
	USB Full/Low-speed Function Controller <sup>1</sup>	SLS
	CUSB USB Function Controller	CAST, Inc.
	CUSB2 USB High-speed Function Controller	CAST, Inc.

<sup>1</sup>SOPC Builder-ready licensed core.

Altera and Partner Functions

	Product Name	Vendor Name
Interface and Protocols (Continued)	USB High-speed OTG Multi-point	CAST, Inc.
	USB 1.1 Host/Device	Microtronix
	USB 3.0 SuperSpeed Device Controller	PLDA
	USB 3.0 SuperSpeed Device Controller	SLS Corp
	USB 1.1 Host/Device	Microtronix
	SDIO/SD Memory/ Slave Controller	Eureka Technology, Inc.
	AHB Slave	Eureka Technology, Inc.
	AHB Master	Eureka Technology, Inc.
	AHB to SDRAM Controller	Eureka Technology, Inc.
	Local Interconnect Network (LIN) Controller	CAST, Inc.
	SPI Master/Slave	CAST, Inc.
	H16450S UART	CAST, Inc.
	H16550S UART <sup>2</sup>	CAST, Inc.
	D16550 UART with 16 Bytes FIFO <sup>2</sup>	Digital Core Design
	H16750S UART	CAST, Inc.
	SPI <sup>1</sup>	Altera
	SPI/Avalon <sup>®</sup> Master Bridge <sup>1</sup>	Altera
	UART <sup>1</sup>	Altera
	JTAG UART <sup>1</sup>	Altera
	JTAG/Avalon Master Bridge <sup>1</sup>	Altera
	UART	Eureka Technology, Inc.
	Programmable Interval Timer/ Counter, 8254	CAST, Inc.
	MD5	CAST, Inc.
	Smart Card Reader	CAST, Inc.
	DSPI Serial Peripheral Interface Master/Slave <sup>2</sup>	Digital Core Design
	SD Host Controller	SLS

	Product Name	Vendor Name	
Interface and Protocols (Continued)	SD/MMC SPI <sup>2</sup>	El Camino GmbH	
	SDIO/SD Memory/ MMC Host Controller	Eureka Technology, Inc.	
	PowerPC Bus Arbiter	Eureka Technology, Inc.	
	PowerPC Bus Master <sup>2</sup>	Eureka Technology, Inc.	
	PowerPC Bus Slave	Eureka Technology, Inc.	
	AHB to PCI Host Bridge	Eureka Technology, Inc.	
	PowerPC/SH/ 1960 System Controller	Eureka Technology, Inc.	
	<b>Audio and Video</b>		
	Character LCD <sup>1</sup>	Altera	
	Pixel Converter (BGR0 -> BGR) <sup>1</sup>	Altera	
	Video Sync Generator <sup>1</sup>	Altera	
	ASI <sup>2</sup>	Altera	
SD/HD/3G-HD SDI	Altera		
I2S Audio CODEC	SLS		
Memories and Memory Controllers	<b>DMA</b>		
	Scatter Gather DMA Controller <sup>1</sup>	Altera	
	DMA Controller <sup>1</sup>	Altera	
	DMA for Hard PCIe (EZDMA2)	PLDA	
	DMA Controller for AHB <sup>2</sup>	Eureka Technology, Inc.	
	<b>Flash</b>		
	NFlashCtrl NAND Flash Memory Controller	CAST, Inc.	
	NAND Flash Controller	Eureka Technology, Inc.	
	ONFI Controller	Octera	
	CompactFlash (True IDE) <sup>1</sup>	Altera	
	EPCS Serial Flash Controller <sup>1</sup>	Altera	
	Flash Memory <sup>1</sup>	Altera	
CompactFlash Interface	SLS		
ISA/PC Card/PCMCIA/ CompactFlash Host Adapter	Eureka Technology, Inc.		

<sup>1</sup>SOPC Builder component (no license required).

<sup>2</sup>SOPC Builder-ready licensed core.

## Altera and Partner Functions

	Product Name	Vendor Name
Memories and Memory Controllers (Continued)	SDRAM	
	Streaming Multi-port SDRAM Memory Controller	Microtronix
	HyperDrive Multi-port DDR2 Memory Controller	Microtronix
	DDR and DDR2 SDRAM Controllers <sup>2</sup>	Altera
	DDR and DDR2 SDRAM Controllers supporting ALTMEMPHY <sup>2</sup>	Altera
	DDR2 and DDR3 SDRAM Controllers supporting UniPHY and ALTMEMPHY	Altera
	DDR3 SDRAM Controller supporting ALTMEMPHY <sup>2</sup>	Altera
	DDR SDRAM Controller	CAST, Inc.
	DDR SDRAM Controller	Northwest Logic, Inc.
	DDR2 SDRAM Controller	Northwest Logic, Inc.
	Mobile DDR SDRAM Controller	Northwest Logic, Inc.
	Mobile SDR SDRAM Controller	Northwest Logic, Inc.
	SDR SDRAM <sup>1</sup>	Altera
	SDR SDRAM Controller	CAST, Inc.
	SDR SDRAM Controller	Northwest Logic, Inc.
	Avalon Multi-port SDRAM Memory Controller <sup>2</sup>	Microtronix
	RLDRAM II Controller supporting UniPHY	Altera
	RLDRAM II Controller	Northwest Logic, Inc.
	SRAM	
	SSRAM (Cypress CY7C1380C) <sup>1</sup>	Altera
QDR II / II+ Controller supporting UniPHY	Altera	
QDR II SRAM Controller supporting ALTMEMPHY	Altera	

<sup>1</sup>SOPC Builder component (no license required).<sup>2</sup>SOPC Builder-ready licensed core.

The following is a list of Altera and partner development kits. To get the full story, check out our online selector guide.

	Product and Vendor Name	Device	Description
DSP	DSP Development Kit, Cyclone III Edition <sup>1</sup> <b>Altera</b>	Cyclone III EP3C120N	This kit is for general DSP or wireless design engineers, regardless of whether you need pre-processing, DSP plus FPGA coprocessing, or post-processing. This kit includes complete 16-bit high-speed analog-to-digital (A/D) and digital-to-analog (D/A) converters (operating at up to 200 MSPS), as well as interfaces to DM642 and DaVinci. Altera's DSP Builder GUI simplifies the information flow between the FPGA toolset and MATLAB/Simulink (30-day evaluation copy included).
	Cyclone III Video and Image Processing Development Kit <sup>1</sup> <b>Bitec</b>	Cyclone III EP3C120N	This kit is designed to help you start developing complex video applications. It supports various video I/O interfaces, allowing you to get your video data in and out of the Cyclone III FPGA. Different video interfaces are supported using the different daughtercards included in this kit: cards supporting ASI/SDI, composite, component, and digital video interfaces (DVI).
	Software Programmable Reconfiguration (SPR) Development System <b>BittWare</b>	Cyclone III FPGA	This development system provides a system platform to explore software reconfiguration of waveform functionality for high-end signal processing applications such as software-defined radio (SDR). The platform provides a flexible, portable, low-cost environment for SPR development in an Advanced Mezzanine Card (AdvancedMC) and Micro Telecommunications Computing Architecture (MicroTCA) environment, enabling you to quickly and cost-effectively bring your waveform designs to life.
	Audio Video Development Kit, Stratix IV GX Edition <b>Altera</b>	Stratix IV GX EP4SGX230	This kit provides a complete video and image processing development environment for design engineers. It features the Stratix IV GX FPGA development board along with an SDI high-speed mezzanine card (HSMC) and associated reference designs.
	DSP Development Kit, Stratix III Edition <b>Altera</b>	Stratix III EP3SL150	This kit comprises a Stratix III development board with a HSMC equipped with 16-bit A/D and D/A converters (operating at up to 200 MSPS). The HSMC also has interfaces to TI DSP processors (DM642 and DaVinci), allowing the designs that use Stratix III FPGAs to be created both as standalone devices and as companion devices. The kit also contains Altera's Quartus II development software, DSP Builder software, and a 30-day trial of MATLAB/Simulink.
	GT-3U-cPCI CompactPCI Board <b>BittWare</b>	Stratix II GX EP2SGX90	This is a ruggedized hybrid signal processing board that features a Stratix II FPGA, a TigerSHARC DSP cluster, DDR2 SRAM/QDR SDRAM, flash memory, and an external I/O throughput of 2 Gbps achieved via BittWare's ATLANTiS Framework.
	GX-AMC <b>BittWare</b>	Stratix II GX FPGA	The GX-AMC (GXAM) is a mid-size, single-width AdvancedMC that can be attached to Advanced Telecommunications Computing Architecture (AdvancedTCA) carriers or other cards equipped with AdvancedMC bays, and used in MicroTCA systems. The GXAM features a high-density Altera Stratix II GX FPGA, BittWare's ATLANTiS Framework (implemented in the FPGA), a front panel I/O interface, a control plane interface via BittWare's FINE interface bridge, an IPMI system management interface, and a configurable x8 SERDES interface supporting a variety of protocols. It also provides 10/100 Ethernet, GbE, two banks of DDR2 SDRAM, one bank of QDR II SRAM, and flash memory for booting the FPGA and FINE.

<sup>1</sup>RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
DSP (Continued)	SC DVI Output Module <b>Bitec</b>	Daughtercard	This module supports all Altera development kits with Altera DVI expansion slots.
	THDB-ADA <b>Terasic Technologies, Inc.</b>	Daughtercard	This card provides dual A/D channels with 14-bit resolution with data rates up to 65 MSPS and dual D/A channels with 14-bit resolution with data rates up to 125 MSPS. It supports both Altera HSMC and Terasic DE-style connectors.
	HSMC Dual-Link DVI Board <b>Bitec</b>	Daughtercard	This is a two-channel, dual-link DVI output board for Altera FPGA development kits with HSMC expansion port.
	SDI HSMC <b>Terasic Technologies, Inc.</b>	Daughtercard	This SDI HSMC card is for the development of SDI and AES systems based on transceiver-based host boards with HSMC connectors.
	DE3 Stratix III High Speed Rapid Prototyping System <b>Terasic Technologies, Inc.</b>	Stratix III EP3SL150F1152C2N EP3SE260F1152C2N EP3SL340F1152C2N	This board uses the Stratix III devices. Starting with the Stratix III EP3SL150 with 142K LEs, this is the perfect platform for creating your design in programmable logic. DE3 boards are available with either the EP3SL150, the EP3SL340, or the EP3SL260 (DE3-260) devices that are optimized with the extra on-chip multipliers needed for DSP research and development. All of the DE3s can be stacked and all feature the same connector for expanding the base functionality with daughtercards.
	GT-6U-VME <b>BittWare</b>	Stratix II GX EP2SGX90FF1508I4	This is a ruggedized 6U VME/VXS (VITA 41) board designed for demanding multiprocessor-based applications. The hybrid processing architecture takes advantage of both FPGA and DSP technology to provide a complete solution for applications requiring flexibility and adaptability along with high-end signal processing. The board features two high-density Stratix II GX FPGAs, a front panel interface supplying four channels of high-speed SERDES transceivers, and an extensive back panel interface including VXS. The board can achieve simultaneous onboard and offboard data transfers at a rate of 5 Gbps. It also provides up to 3 GB of DDR2 SDRAM, as well as 128 MB of flash memory for booting the FPGAs and DSP devices.
	OmniTek Audio Video <b>OmniTek</b>	Arria II GX EP2AGX125EF35	This Arria II GX audio and video development kit combines Altera's proven FPGA-based development hardware and associated IP with OmniTek's expertise in video algorithm IP and PCIe interface design to offer a PCIe Gen1 image processing environment.
	DSP Compute Board <b>Iris Technologies</b>	Cyclone II EP2C70	This board features four Cyclone II EP2C70 FPGAs, two DDR2 SODIMMs, and a PCIe x4 Gen 1.1 host interface. It is used for Hardware in the Loop (HIL) simulation and emulation, processor and system simulation and emulation, algorithm acceleration, co-processing, and so on. The kit contains drivers, programming cables, Quartus II software, a test design, and C/C++ and MATLAB application programming interfaces (APIs).

<sup>1</sup> RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
I/O Interconnect	Cyclone IV GX FPGA Development Kit <b>Altera</b>	Cyclone IV GX EP4CGX150DF31C7N	This kit provides a comprehensive design environment that allows you to quickly develop low-cost and low-power FPGA system-level designs. This kit includes the PCIe short card form factor, two HSMC connectors, and a 10/100/1000 Mbps Ethernet interface. Onboard memory includes 128-MB DDR2 SDRAM, 64-MB flash, and 4-MB SSRAM. This kit also includes SMA connectors, 50-, 100-, and 125-MHz clock oscillators, as well as user interfaces including push buttons, LEDs, and a 7-segment LCD display.
	Arria II GX FPGA Development Kit <b>Altera</b>	Arria II GX EP2AGX120F1152	This kit provides a full-featured hardware development platform for prototyping and testing high-speed serial interfaces to an Arria II GX FPGA. This kit includes PCIe x4 form factor, one HSMC connector, 32-MB DDR2 SDRAM, and 512-MB flash.
	Transceiver Signal Integrity Kit, Stratix IV GX Edition <b>Altera</b>	Stratix IV GX EP4S- GX230F1517	This kit features eight full-duplex transceiver channels with SMA connectors, 156.25-, 155.52-, 125-, 100-, and 50-MHz clock oscillators, six user push buttons, eight dual in-line package (DIP) switches, eight user LEDs, a 7-segment LCD display, power and temperature measurement circuitry, Ethernet, USB, and JTAG ports.
	Stratix IV GX FPGA Development Kit <b>Altera</b>	Stratix IV GX EP4S- GX230F1517	This kit provides a full-featured hardware development platform for prototyping and testing high-speed serial interfaces to a Stratix IV GX FPGA. This kit includes PCIe x8 form factor, two HSMC connectors for expandability, Ethernet, USB, SDI, and HDMI interfaces. Memory includes one x64 DDR3 SDRAM, one x16 DDR3 SDRAM, two x18 QDR II+ SRAM, flash, and SSRAM. This kit also includes five SMA connectors for differential transmitter/receiver, along with 156.25-, 155.52-, 125-, 100-, and 50-MHz clock oscillators. User interfaces include six user push buttons, eight DIP switches, eight user LEDs, 7-segment LCD display, and power and temperature measurement circuitry.
	S4GX-AMC <b>BittWare</b>	Stratix IV GX EP4S- GX230F1517	This board is based on Altera's Stratix IV GX FPGA and is a mid-size, single-width AdvancedMC that can be attached to AdvancedTCA carriers or other cards equipped with AdvancedMC bays, and used in MicroTCA systems. This board has two banks of DDR3 SDRAM (up to 1 GB each), and two banks of QDR II SRAM (up to 9 MB). Includes IP support for Serial RapidIO, PCIe, GbE, 10G Ethernet (XAUI), CPRI, and OBSAI interfaces.
	SF/GX-AMC <b>BittWare</b>	Stratix II GX EP2SGX130	This board is based on Altera's Stratix II GX FPGA and is a full-size, single-width AdvancedMC that can be attached to AdvancedTCA carriers or other cards equipped with AdvancedMC bays, and used in MicroTCA systems. The SF/GX-AMC has all the features of the GX-AMC card and includes four small form factor pluggable-plus (SFP/SFP+) compact optical transceiver connectors.
	Ethernet USB Expansion Kit <b>Microtronix Inc.</b>	Daughtercard	This kit includes a wireless 802.11b CompactFlash card and a Microtronix CompactFlash board.
	I <sup>2</sup> C Design Kit <b>Microtronix Inc.</b>	Daughtercard	This kit provides an easy way to design, develop, and test the Microtronix I <sup>2</sup> C IP core.
	10/100/1000 Ethernet PHY Daughter Board with Marvell PHY <b>MorethanIP</b>	Daughtercard	This kit provides the ability to implement high-speed Ethernet PHY solutions for prototyping and evaluation and embedded software development.
	10/100/1000 Ethernet PHY Daughter Board with National Semiconductor PHY <b>MorethanIP</b>	Daughtercard	This kit provides the ability to implement fast Ethernet solutions for prototyping and evaluation and embedded software development.
SFP HSMC <b>Terasic Technologies, Inc.</b>	Daughtercard	This SFP HSMC card is for the development of SGMII Ethernet, Fiber Channel, CPRI/OBSAI, and SONET designs based on transceiver-based host boards with HSMC connectors.	

<sup>1</sup> RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
I/O Interconnect (Continued)	Xpress GX4 Kit <b>PLDA</b>	Stratix IV GX EP4SGX230KF40C2N	This kit provides a complete hardware and software environment for Altera Stratix IV GX FPGAs. It is built around a PCI form factor card compliant with PCI-SIG® and targets the development of designs using PCIe Gen1 or Gen2.
	PCI-X Development Board <b>Terasic Technologies, Inc.</b>	Cyclone III FPGA	This board provides a hardware platform for developing and prototyping low-power, high-performance, logic-intensive PCI-based designs on an Altera Cyclone III FPGA. External memory is provided to facilitate the development of designs that need extra storage capacity or higher bandwidth memory. It also includes a LVDS interface using high-speed Terasic connectors (HSTCs) for high-speed interface applications.
	Xpress AGX2 Kit <b>PLDA</b>	Arria II GX EP2AGX125EF35	This kit provides a complete hardware and software environment for Altera Arria II GX FPGAs. It is built around a PCI form factor card compliant with PCI-SIG and targets the development of designs using PCIe Gen1.
	Xpress AGX Kit <b>PLDA</b>	Arria GX EP1AGX60DF780C6	This kit provides a complete hardware and software environment for Altera Arria GX FPGAs. It is built around a PCI form factor card compliant with PCI-SIG and targets the development of designs using PCIe Gen1.
	Cyclone IV GX Transceiver Starter Kit <b>Altera</b>	Cyclone IV GX EP4CGX15	This kit provides a low-cost platform for developing transceiver I/O-based FPGA designs. It includes the complete hardware and software you need to develop your FPGA design for cost-sensitive applications. You can measure the FPGA's power consumption, test the signal quality of the FPGA transceiver I/Os (up to 2.5 Gbps), and develop and test PCIe Gen1 designs.
	Transceiver Signal Integrity Development Kit, Stratix IV GT Edition <b>Altera</b>	Stratix IV EP4S100G2F40I1N	This kit enables a thorough evaluation of transceiver interoperability and SERDES signal integrity by allowing you to evaluate transceiver performance up to 11.3 Gbps. You can generate and check pseudo-random binary sequence (PRBS) patterns via a simple-to-use GUI, change differential output voltage ( $V_{OD}$ ), pre-emphasis, and equalization settings to optimize transceiver performance for your channel, perform jitter analysis, verify PMA compliance to 40G/100G Ethernet, Interlaken, CEI-6G/11G, PCIe (Gen1, Gen2, and Gen3), Serial RapidIO, and other major standards, and validate interoperability between optical modules.
	B2-AMC <b>BittWare</b>	Stratix II EP2S90F1020C3	This board supports universal baseband processing for wireless communication infrastructures such as 2G, 2.5G, 3G, WiMAX, and SDR. It attaches to AdvancedTCA carriers or other cards equipped with AdvancedMC bays, and is completely hot-swappable. It uses an Altera Stratix II FPGA, and provides a 10/100/1000 Ethernet interface for command, control, and reprogramming, as well as flash memory for booting the DSP devices and FPGAs.
	Gt-3U-VPX <b>BittWare</b>	Stratix II GX EP2SGX90FF1508I4	This is a ruggedized 3U CompactPCI board designed for demanding multi-processor applications requiring complete flexibility and adaptability. It features a large Altera Stratix II GX FPGA, a front panel interface supplying four channels of high-speed SERDES transceivers, and a back panel interface providing RS-232/RS-422 and 10/100 Ethernet. Simultaneous onboard and offboard data transfers can be achieved at a rate of 2 Gbps. It also provides 1 GB of DDR2 SDRAM and 64 MB of flash memory for booting the FPGA and DSP devices.
	TREX S2 Prototyping System <b>Terasic Technologies, Inc.</b>	Stratix II FPGA	This is a Stratix II FPGA prototyping system providing almost 700 user I/Os and high-speed I/O connections. This board is flexible and configurable, and it provides default motherboards for free—with schematic/ schematic and design libraries for you to develop your own motherboards.

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
I/O Interconnect (Continued)	QuickUSB Starter Kit Bitwise Systems	Cyclone II EP2C20F256C7	This kit includes one QuickUSB module and one QuickUSB Cyclone II Evaluation Board. The evaluation board has a QuickUSB module site on headers that provide access to the signals. The EP2C20F256C7 FPGA connects to nearly every pin of the QuickUSB module, and extra I/O pins go to the headers so you can wire in your circuitry. The kit gets its power from the USB bus, but if you need more power, there is a power connector and a 5V/2A power supply included in the kit.
	C3 Digital Radio Kit CEPD	Cyclone III EP3C16	This kit aids in the development and testing of algorithms and signal processing applications including digital radio, modulator/demodulator development, SDR, high-speed data acquisition and signal processing, and audio data acquisition and signal processing. The acquired signals are sampled and then digitally processed by a Cyclone III FPGA. The FPGA card comes with a JTAG programming connector and a configuration PROM to retain the FPGA settings. The PCI card provides interfaces for the FPGA card to a computer PCI bus, RS232 interface, and user push buttons and includes a digital radio reference design example and full documentation.
	Cyclone III FPGA/ PCI Development Board CEPD	Cyclone III EP3C16F484C8N	This board provides a platform for fast and easy prototyping and design verification with the Cyclone III EP3C16F484C8N FPGA. It can be accessed either through the PCI bus or powered standalone and accessed through an RS232 port. It comes with an onboard configuration PROM to retain the FPGA settings, an RS232 level shifter, voltage monitor, oscillator, buttons, and LEDs. There is a prototyping area on the board for user circuits and all FPGA pins are accessible through connectors and clearly labeled test points. The connectors are designed to mate with other CEPD daughterboards.
	XpressGXII Kit System Level Solutions	Stratix II GX EP2SGX130FF1508C3	This kit provides a complete hardware and software environment for Altera Stratix II GX FPGAs. It is built around a PCI form factor card compliant with PCI-SIG and targets the development of designs using PCIe Gen1.
	SuperUSBC3-55 PLDA	Cyclone III EP3C55U484C6N	This kit provides a low-cost hardware and software environment for prototyping and deploying SuperSpeed USB applications. It targets the Altera Cyclone III FPGA (EP3C55F484C6N) and includes everything you need to implement a complete USB 3.0 subsystem.
	A01 LVDS FPGA AMC Dallas Logic	Arria GX EP1AGX60	This LVDS transceiver card features the Arria GX FPGA in the F780 BGA package. The backplane interface is user configurable to support several interface standards including PCIe, Serial RapidIO, and GbE. The front panel VHDCI connector supports 28 transmit and 28 receive LVDS links sourced from the FPGA (and 2 clock signals for each transmit and receive connector). Additional features include two 512 Kb x36 synchronous SRAMs, an IPMI 1.5-compliant Module Management Controller (MMC), a 32-Mb serial flash memory, two onboard temperature sensors, USB communication and debug interface, and a 32-bit Mictor debug connector.
	Stratix IV GX/GT 40G/ 100G Interlaken HiTech Global	Stratix IV EP4S100G5 EP4SGX530	This board integrates the most fundamental electrical and optical interfaces for building 200G subsystems. It implements CAUI and Interlaken high-speed serial interfaces, industry-leading, high-speed DDR3 and QDR II+ interfaces, and high-speed parallel interconnect for NetLogic knowledge-based processors (KBPs). The modular design enables expansion to support legacy and emerging optical modules.

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
I/O Interconnect (Continued)	HD FIFO Modules <b>Averlogic</b>	Daughtercard	This board is designed for evaluating the AL460A HD-FIFO. It has two embedded AL460A-7-PBF (or AL460A-13-PBF) devices operating in parallel, expanding the bus width to 32 bits. Control signals and data bus signals are available on two 50-pin connectors. A separate adaptor board (HSMC interface) is available for connecting the module directly to a Cyclone III FPGA starter kit.
	Broadcast Video Card <b>Bitec</b>	Daughtercard	This card is designed for professional video equipment developers. The dual ASI/SD-SDI interfaces allow access to industry-standard video transport signals. Based on the latest adaptive cable equalizers and drivers, the ASI/SDI interfaces provide excellent noise immunity up to cable lengths of 350 meters. A VCXO allows precise synchronization to incoming ASI signals. A DVB-T reference design using the Bitec BVDC daughtercard and a Cyclone III FPGA Development Kit is available.
	Quad Video Board <b>Bitec</b>	Daughtercard	This board is based on the Texas Instruments TVP5154 quad video decoder. The analog video inputs include composite video and S-video. Video output is based on the Chromtel CH7010B device, enabling single-link DVI, component analog, and composite analog outputs. The device accepts digital, parallel video data, and clocking from the host FPGA via the HSMC connector, which configures and monitors the device over an I <sup>2</sup> C link. A DVI output connector and mini-DIN output connector are provided.
	HDMI Receiver/Transmitter <b>Microtronix</b>	Daughtercard	This daughtercard interfaces a HDMI receiver and transmitter to your Altera FPGA development kit using the HSMC expansion connector. The receiver also supports an analog component video (YCbCr) interface. The card uses the Analog Device AD9889 HDMI Transmitter and AD9880 HDMI Receiver to support HDTV formats up to 1080p at 60 Hz. The receiver offers the flexibility of both an analog interface and an HDMI receiver integrated on a single chip.
	Quad Link LVDS Interface <b>Microtronix</b>	Daughtercard	This daughtercard supports receive and transmit LVDS links, each consisting of five data channels and one clock for a total of 48 LVDS channels. The standard configuration of 20 TX + 4 clk and 20 RX + 2 clk, is capable of supporting LCD display panels up to 1080p at 100/120 Hz. Onboard LVDS termination resistors can be removed to convert receiver channels into transmitters as required to support 12- or 14-bit color applications. It is used for capturing LVDS video data, connecting to a camera link interface, or for connecting to LCD panels using LVDS, Mini-LVDS, RSDS, and PPDS low-voltage panel interface signaling.
	CX4 to HSMC Adapter <b>MorethanIP</b>	Daughtercard	This is a passive daughtercard for 10GbE CX-4 copper interconnect prototyping. It features a four-lane differential 3.125-Gbps connector (CX-4) for 10GbE IEEE 802.3ak, a 160-pin HSMC to the main board, and compatibility with Stratix II GX mother boards that use HSMC connectors.

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
Embedded	Industrial Networking Kit <b>Terasic Technologies, Inc.</b>	Cyclone IV E EP4CE115	The Industrial Networking Kit (INK) offers a comprehensive development platform for industrial automation and process control applications. The kit consists of the DE2-115 board featuring the Altera Cyclone IV device and dual 10/100/1000 Mbps Ethernet, 128-MB SDRAM, 8-MB flash memory, 2-MB SRAM, HSMC and GPIO connectors, USB 2.0, an SD card slot, switches and buttons, LEDs, 16x2 display, audio and video, and VGA-out. The kit also includes an Industrial Communications Board (ICB-HSMC) that supports RS-485, RS-232, CAN, and additional I/O expansion.
	Nios II Embedded Evaluation Kit, Cyclone III Edition <sup>1</sup> <b>Altera</b>	Cyclone III EP3C25N	The kit includes a complete hardware and software design environment for a 32-bit microcontroller plus FPGA evaluation. Beginners can check out the pre-built, eye-catching demos displayed on the LCD touch screen or do some lightweight development. Advanced microcontroller designers can learn about the "hottest" techniques, multi-processor systems, hardware acceleration using Nios II C2H Compiler, or about designing a complete system in 30 minutes.
	Cyclone III FPGA Development Kit <b>Altera</b>	Cyclone III EP3C120N	This kit contains 8-MB SSRAM, 256-MB DDR2 SDRAM, 64-MB flash, configuration via USB, 10/100/1000 Ethernet and USB ports, onboard oscillators and SMAs, graphics LCD and character LC displays, two HSMC expansion connectors, three HSMC debug cards, and onboard power measurement circuitry. Complete documentation including reference designs: <i>Create Your First FPGA Design in an Hour</i> and <i>Measure Cyclone III FPGA Power</i> . This kit also includes Quartus II Web Edition design software, an evaluation edition of Nios II processor plus related design suite, and the Altera IP library.
	Nios II Development Kit, Cyclone III Edition <sup>1</sup> <b>Altera</b>	Cyclone III EP3C120N	This development kit has been outfitted with the latest in cutting-edge hardware and software technology. The unique combination of high-performance embedded processor power and easy-to-use integrated design software has been updated to take advantage of Cyclone III devices, the industry's lowest cost, first-to-market 65-nm FPGA family. This development kit provides an ideal environment for developing and prototyping a wide range of price-sensitive, high-performance embedded applications.
	PARIS automotive development platform <b>TRS-STAR</b>	Stratix II EP2S90 or EP2S180 Optional path to HardCopy HC210W	This microcontroller development platform creates scalable reference designs for automotive infotainment (head-end, drivers assistance, navigation, and others.) Add-on modules and reference designs are also available. Designs can be ported to Altera's automotive-grade Cyclone III FPGAs or HardCopy ASICs.
	Lancelot VGA IP Design Kit <b>Microtronix Inc.</b>	Daughtercard	This kit includes a small hardware board with a 24-bit RAMDAC, VGA connector, stereo audio connector, and two PS/2 connectors.
	Compact Flash Expansion Kit <b>Microtronix Inc.</b>	Daughtercard	This inexpensive module allows the addition of compact flash cards to the Microtronix Product Starter Kit development board system.
	Low Power Reference Platform <b>Arrow</b>	Cyclone III EP3C25 MAX IIG EPM240T100	This platform uses the low-power Altera Cyclone III FPGAs and MAX IIG CPLDs. It demonstrates how to minimize power consumption in portable and battery-powered embedded systems and gives you the flexibility to create application-specific low-power solutions.

<sup>1</sup> RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
Embedded (Continued)	MotionFire Arrow	Cyclone III EP3C40F484	This kit contains all you need for developing complex motor control applications based on Cyclone III FPGAs. It includes a Nios II reference design, advanced regulators implemented in hardware, generic current, speed, and position regulators with feedback from incremental encoders or hall sensors, a trajectory generator with linear acceleration and velocity feed-forward implemented in software, and much more.
	BeMicro SDK Arrow	Cyclone IV E EP4CE22F17C7N	The Arrow BeMicro SDK enables a quick and easy evaluation of soft core processors by both embedded software developers and hardware engineers. The kit builds on the success of the original BeMicro evaluation kit by adding features such as mobile DDR memory, Ethernet, and even the option of using a file system by slotting in a micro-SD card. The BeMicro SDK connects to a PC via a USB connection, which is used for power, programming, and debug. Arrow has a number of reference designs and pre-built software templates that can be downloaded for this kit that will highlight the benefits of building embedded systems in FPGAs.
	MimoKit Comsis	Stratix II EP2S180F1020C5 x2	This kit is designed for extensively networked embedded applications that require wireless LAN connectivity and GbE. It provides the multiple input multiple output (MIMO) RF and analog front end consisting of two major sub-blocks. The analog block is made of three IQ CODECs that perform the conversions between the digital and analog domains. The radio block consists of three 2.4-GHz/5-GHz dual-band radio transceivers.
	ARM-MPS Gleichmann Electronics	Stratix III	This platform offers total flexibility for prototyping your Cortex-M3-based designs. It allows unrestricted access to the latest Cortex-M-class processors. It is delivered with a comprehensive range of tools that allow fast and easy system design—drag and drop the supplied IP components to configure the system, or implement your own system blocks. Then synthesize the design and update the board with a single mouse-click. The tool suite also includes system configuration utilities and a JTAG signal monitor together with software development tools and a JTAG debug probe.
	CMCS002M Controller FPGA Module Dallas Logic	Cyclone III EP3C25	This module allows you to implement general logic functions and Nios II processor operations in a compact form factor module. The module uses the Cyclone EP3C25 FPGA, 512K x8 SRAM, EP1S16 FPGA serial loader (FPGA and Nios II boot), and a USB 2.0 peripheral port (low-/full-speed operation). This module also supports the Cardstac specification (master or slave standard card, 128 pins), and can interface with other modules designed to that specification.
ASIC Prototyping	DN7020k10 The Dini Group	Stratix III Stratix IV	This is a complete logic prototyping system that gives ASIC and IP designers a vehicle to prototype logic and memory designs using up to 20 Stratix III or Stratix IV devices.
	DN7006K10PCIe-8T The Dini Group	Stratix III Stratix IV	This is a complete logic prototyping system with a dedicated PCIe interface that gives ASIC and IP designers a vehicle to prototype logic and memory designs using up to six Stratix III or Stratix IV devices.
	DIGILAB SX III El Camino GmbH	Stratix III	This is a universal FPGA prototyping platform based on Altera's largest Stratix III devices. Supports 2-MB flash, 2-MB SRAM, four Samtec expansion connectors, two Mictor connectors, user LEDs and pushbuttons along with RS-232, SPI, and USB interfaces.
	PROC30M , PROC9M GIDEL	Stratix III	This system is for the debug and verification of SOC ASIC designs from 3 to over 100 million gates in size, with the ability to run at system clock speeds up to 300 MHz.

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
ASIC Prototyping (Continued)	PROCStar II, ProcStar III <b>GiDEL</b>	Stratix II Stratix III	This system provides high-capacity, high-speed, multi-FPGA-based prototyping and end system platforms.
	DNMEG S2GX Stratix II GX-Based ASIC Prototyping Kit <b>The Dini Group</b>	Stratix II GX	This is a logic emulation daughtercard enabling ASIC or IP designers to cost-effectively prototype logic and memory designs. The DNMEG_S2GX is hosted on any DN7000 or DN8000 series ASIC Dini Group product, but can also be used alone.
	S3 Compute <b>Iris Technologies</b>	Stratix III Stratix IV	This ASIC prototyping board, compliant with PCI-SIG, features two Altera Stratix III EP3S340SL devices, one Altera Stratix II GX FPGA for PCIe host interface EP2GX90 device, two DDR2 SODIMM, and four HSMC connectors.
	DN7002k10MEG <b>The Dini Group</b>	Stratix IV EP4SE820F43CxN EP4SE530F43CxN	This is a complete logic emulation system that allows you to prototype SOC logic and memory designs. It can operate as a standalone, or hosted via a USB interface. A single system, configured with two Stratix IV EP4SE820 FPGAs, can emulate up to 13 million gates. All FPGA resources are available for the target application. Each FPGA position can use any available speed grade.
	DN7406k10PCIe-8T <b>The Dini Group</b>	Stratix IV EP4SE820F43CxN EP4SE530F43CxN	This is a complete logic prototyping system that allows you to prototype logic and memory designs. The DN7406k10PCIe-8T is hosted in an eight-lane PCIe Gen1 bus, but can be used as a standalone and configured via USB or CompactFlash. A single board configured with six Altera Stratix IV EP4SE820 FPGAs can emulate up to 31 million gates. All of the FPGA resources are available for your application. Use any combination of speed grades.
	DNMEG S2GX <b>The Dini Group</b>	Stratix II GX EP2SGX90EF1152C3N	This daughtercard enables you to prototype logic and memory designs. It is hosted on any DN8000- or DN7000-series ASIC emulation products from the Dini Group, but can be used as a standalone. It contains the Stratix II GX EP2SGX90 (speed grades -5, -4, or -3) and can emulate over 600K gates. One DDR2 SDRAM SODIMM is provided, allowing the FPGA to address up to 2 GB of memory.
	Stratix IV E FPGA Development Kit <b>Altera</b>	Stratix IV E EP4SE530	This kit allows rapid and early development of designs for high-performance Stratix IV FPGAs. The development board provides general I/Os that connect to onboard switches and indicators, and to the included two-line LCD and 128 x 64-pixel graphics display. The board also has non-volatile and volatile memories (64-MB flash, 4-MB pseudo-SRAM, 36-Mb QDR II SRAM, 128-MB DDR2 DIMM, and 16-MB DDR2 device), HSMC, and triple-speed Ethernet interfaces. The kit is delivered with Quartus II software and all of the cabling required to start using the board straight out of the box.
	Stratix III FPGA Development Kit <b>Altera</b>	Stratix III EP3SL150	This kit allows rapid and early development of designs for high-performance Stratix III FPGAs. The development board provides general I/Os that connect to onboard switches and indicators, and to the included two-line LCD and 128 x 64-pixel graphics display. The board also has non-volatile and volatile memories (64-MB flash, 4-MB pseudo-SRAM, 36-Mb QDR II SRAM, 128-MB DDR2 DIMM, and 16-MB DDR2 device), HSMC, and triple-speed Ethernet interfaces. The kit is delivered with Quartus II software and all of the cabling required to start using the board straight out of the box.

<sup>1</sup>RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
General Purpose	Arria II GX FPGA Development Kit <b>Altera</b>	Arria II GX EP2AGX120F1152	This kit provides a full-featured hardware development platform for prototyping and testing of high-speed serial interfaces to an Arria II GX FPGA. PCIe x4 form factor, one HSMC connector, 32-MB DDR2 SDRAM, and 512-MB flash.
	Cyclone III FPGA Starter Kit <sup>1</sup> <b>Altera</b>	Cyclone III EP3C25N	This kit contains 1-MB SSRAM, 16-MB DDR SDRAM, 16-MB parallel flash, configuration via USB, four user push buttons, four user LEDs, and power measurement circuitry. Complete documentation including reference designs: <i>Create Your First FPGA Design in a Hour</i> , <i>Measure Cyclone III FPGA Power</i> , and <i>Create Your First Nios II</i> . This kit also includes Quartus II Web Edition design software, the evaluation edition of Nios II processor plus related design suite, and Altera IP library.
	Video Development Kit <b>Bitec</b>	Cyclone III FPGA	This kit contains the Cyclone III FPGA Development Kit and two HSMC video interface cards together with a collection of IP cores and reference designs. The kit provides a variety of video interface standards including both digital and analog up to HD resolutions.
	ViClaro III HD Video Enhancement Development Platform <b>Microtronix</b>	Cyclone III FPGA	This is a video enhancement development platform supporting 100/120-Hz HDTV that is 1080p bandwidth-capable and features 32-bit DDR2 SDRAM memory, a HDMI transmitter, an analog/HDMI receiver, and dual LVDS links.
	Stratix IV GX FPGA Development Kit <b>Altera</b>	Stratix IV GX EP4SGX230F1517	This kit provides a full-featured hardware development platform for prototyping and testing of high-speed serial interfaces to a Stratix IV GX FPGA. This kit includes PCIe x8 form factor, two HSMC connectors for expandability, Ethernet, USB, SDI, and HDMI interfaces. Onboard memory includes one x64 DDR3 SDRAM, two x32 DDR3 SDRAM, two x18 QDR II+ SRAM, flash, and SSRAM. This kit also includes five SMA connectors for differential transmitter/receiver, along with 155.52-, 156.25-, 125-, 100-, and 50-MHz clock oscillators and power and temperature measurement circuitry. User interfaces include six user push buttons, eight DIP switches, eight user LEDs, and a 7-segment LCD display.
	MAX II Micro <b>Terasic Technologies, Inc.</b>	MAX II CPLD	This kit, equipped with an Altera MAX II EPM2210F324C3 device (largest CPLD in the MAX II series) and an onboard USB-Blaster™ cable, functions as a development and education board for CPLD designs. This kit also includes reference designs with source code.
	DIGILAB picoMAX Prototyping Board and Starter Kit <b>El Camino GmbH</b>	MAX EPM3032A to EPM7160S	This is a MAX 3000/MAX 7000 starter kit which includes downloading and programming hardware.
	DB3128 <b>EBV</b>	MAX EPM3128A	This is a low-cost MAX 3000A CPLD development board with 128 macrocells that provides an easy entry point into Altera's CPLD technology.
	DB3256 <b>EBV</b>	MAX EPM3256A	This is a 5.2-megapixel camera daughtercard with selectable frame rates and resolutions.
	PM410 StarFabric Compact PCI Carrier Board <b>Parsec</b>	MAX EPM3256A	This board consists of two 3.3-V PMC sites, 32-/64-bit 33-/66-MHz PCI buses, 2.5-Gbps StarFabric links on J3, and supports full PCI bandwidth.
TRDB_DC2 1.3 Megapixel Camera Module <b>Terasic Technologies, Inc.</b>	Daughtercard	This module consists of complete digital camera reference designs with source code in Verilog HDL and a user manual with live demo examples. It supports exposure, light-control, and motion capture.	

<sup>1</sup> RoHS compliant

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
General Purpose (Continued)	TRDB_LCM Digital Panel Daughtercard <b>Terasic Technologies, Inc.</b>	Daughtercard	This 3.6" digital panel development kit consists of reference designs (TV player and color pattern generator) with source code in Verilog HDL.
	HSMC DVI Input/Output Module <b>Bitec</b>	Daughtercard	This DVI transmitter/receiver module for the HSMC interface enables you to interface FPGA projects to real-world DVI signals.
	SC DVI Input Module <b>Bitec</b>	Daughtercard	This DVI module for the Santa Cruz interface enables you to interface FPGA projects to real-world DVI signals.
	SC DVI Output Module <b>Bitec</b>	Daughtercard	This DVI module for the Santa Cruz interface enables you to drive high-resolution displays with digital clarity.
	SC Camera <b>Bitec</b>	Daughtercard	This board features a 5.2-megapixel camera daughtercard with selectable frame rates and resolutions.
	SC Proto <b>Bitec</b>	Daughtercard	This is a prototyping board for the Santa Cruz interface with convenient access points to power and ground with connector break-out.
	Hpe-midiv2 <b>Gleichmann Electronics</b>	Stratix III EP3SL150	This is a complete development environment with a large number of onboard PHY and a range of child boards with various auxiliary functions for developing large and complex systems. It consists of a motherboard with the latest Stratix III modules and all of the latest interfaces on a single platform. It comes with a graphical user interface for access to a set of free tools including system configuration utilities, JTAG debugger and scanner, and clock factory programmer.
	DE0 Development Board <b>Terasic Technologies, Inc.</b>	Cyclone III EP3C16F484C6N	This board provides all the essential tools for you to learn about digital logic and FPGAs. It is equipped with an Altera Cyclone III EP3C16 FPGA, which offers 15,408 LEs. The board provides 346 user I/O pins and is loaded with a rich set of features. It suitable for advanced university and college courses as well as the development of sophisticated digital systems, and includes software, reference designs, and accessories.
	DE1 Development Board <b>Terasic Technologies, Inc.</b>	Cyclone II EP2C20 FPGA	This is a smaller version of the DE2 board. It is useful for learning about digital logic and FPGAs. Featuring an Altera Cyclone II EP2C20 FPGA, it is designed for university and college laboratory use, and is suitable for a wide range of exercises in courses on digital logic and computer organization.
	DE2 Development Board <b>Terasic Technologies, Inc.</b>	Cyclone II EP2C35 FPGA	This board was designed by professors, for professors. It is an ideal vehicle for learning about digital logic and FPGAs. Featuring an Altera Cyclone II EP2C35 FPGA, the DE2 board is designed for university and college laboratory use. It is suitable for a wide range of exercises in courses on digital logic and computer organization.
DE2-70 Digital Camera and Multimedia Development Platform <b>Terasic Technologies, Inc.</b>	Cyclone II EP2C70F896C6N	This is a modified version of the Altera DE2 board with a larger FPGA and more memory. It is an excellent vehicle for learning about digital logic and FPGAs. Featuring an Altera Cyclone II EP2C70 FPGA, the DE2 board is designed for university and college laboratory use.	
DE2-115 Development and Education Board <b>Terasic Technologies, Inc.</b>	Cyclone IV E EP4CE115	This board is part of the DE2 educational development board series and features the Cyclone IV E EP4CE115 FPGA. The DE2-115 offers an optimal balance of low cost, low power and a rich supply of logic, memory and DSP capabilities, as well as interfaces to support mainstream protocols including GbE. A HSMC connector is provided to support additional functionality and connectivity via HSMC daughtercards and cables.	

## Altera and Partner Development Kits

	Product and Vendor Name	Device	Description
General Purpose (Continued)	MAX II/MAX IIZ Development Kit System Level Solutions	MAX II EPM240 EPM240Z	This board provides a hardware platform for designing and developing simple and low-end systems based on Altera MAX II/ MAX IIZ devices. The board features a MAX II/MAX IIZ EPM240T100Cx/EPM240ZM100Cx device with 240 LEs and 8,192 bits of user flash memory (UFM). The board also supports vertical migration into EPM570T100Cx devices with 570 LEs and 8,192 bits of UFM.
	MAX V CPLD Development Kit Altera	MAX V 5M570Z	Altera's MAX V CPLD Development Kit is a low-cost platform to help you quickly begin developing low-cost, low-power CPLD designs. Use the kit as a stand-alone board or combined with a wide variety of daughtercards that are available from third parties.
	CoreCommander Development Kit System Level Solutions	Cyclone III EP3C25F256C8	This kit features the Altera Cyclone III FPGA that provides more than enough room for almost any embedded design. This flexible board comes with a suite of SLS IP Cores, drivers, and application software. Delivered as a complete package, this kit ensures quick and easy implementation of industry-leading cores with reduced risk, at a very low cost.
	Cyclone III LS FPGA Development Kit Altera	Cyclone III LS EP3CLS200F780C7N	This kit combines a high-density, low-power Cyclone III LS FPGA with a complete suite of security features implemented at the silicon, software, and IP levels. These security features provide passive and active protection of your IP from tampering, reverse engineering, and counterfeiting. It uses the EP3CLS200 FPGA—200K LEs at less than 1/4 W static power.
	DB Start 3C10 EBV Elektronik GmbH & Co. KG	Cyclone III EP3C10E144C8N	This starter kit is ideal for starting your first experiments based on Cyclone III FPGAs. It is designed for ease of use, with embedded USB-Blaster and pin header for peripherals. It can be powered via USB, and it features Linux BSP, a PCI solution for high data throughput, a local bus solution for low-latency data transmission including a local bus IP core, and several industry-standard interfaces such as CAN and RS485.
	DB1270-144 EBV Elektronik GmbH & Co. KG	MAX II DB1270T144C5N	This kit enables you to evaluate the MAX II feature set or begin prototyping a design prior to receiving custom hardware. It includes all software, cables, and accessories needed to ensure an easy and productive evaluation of the MAX II CPLD. It includes the MAX II EPM1270T144C5ES CPLD, eight LEDs, four push buttons, a 7-segment display, serial I/O connectors (RS-232 DB9 port), and an 8-bit DIP switch.
	HSMC Prototyping Board Bitec	Daughtercard	This board provides a solution for prototyping circuits and testing them together with the latest Altera FPGA development kits. The board provides access to the complete set of HSMC signals via a footprint of standard 0.1" pitch headers. The HSMC power pins are accessed via fuses for added security. The main prototype matrix comprises a 0.1" grid interleaved with +3.3-V and GND access points. Footprints for commonly used 25-way and 9-way D-type connectors are included on the board.

## Online, Instructor-led, and Virtual Classes

[www.altera.com/training](http://www.altera.com/training)

We offer an extensive curriculum of classes to deepen your expertise. Our classes are beneficial whether you're new to FPGA and CPLD design, or are an advanced user wanting an update on the latest tools, tips, and tricks. Choose a training path delivered in three different ways:

- Online training, typically one to two hours long, features pre-recorded presentations and demonstrations. Online classes are free and can be taken at any time.
- Instructor-led training, typically lasting one to two days, involves in-person instruction with hands-on exercises from an Altera or Altera partner subject matter expert. Fees vary.
- Virtual classrooms, involving live instructor-taught training over the Web, allow you to benefit from the interactivity with an instructor from the comfort of your home or office. Classes are taught in 4.5-hour sessions across consecutive days.

To help you decide which courses might be most useful to you, we've grouped classes into specific curricula. Curricula paths include CPLD Designer, FPGA Designer, SOC Designer, Embedded Hardware Designer, and many more.

Learn more about our training program or sign up for classes at [www.altera.com/training](http://www.altera.com/training). Start sharpening your competitive edge today!

Protocols, Devices, and Data Rates							
Protocol	Stratix V GX/ GS/GT Data Rates (Gbps per Lane)	Stratix IV GT Data Rates (Gbps per Lane)	Stratix IV GX Data Rates (Gbps per Lane)	Stratix II GX Data Rates (Gbps per Lane)	HardCopy IV GX Data Rates (Gbps per Lane)	Arria II GX Data Rates (Gbps per Lane)	Cyclone IV GX Data Rates (Gbps per Lane)
3G-SDI	2.97	2.97	2.97	2.97	2.97	2.97	2.97
SDI SD/HD	0.2/1.485	0.2/1.485	0.27/1.485	0.27/1.485	0.27/1.485	0.27/1.485	0.27/1.485
ASI	0.27	0.27	0.27	0.27	0.27	0.27	-
Basic (proprietary)	0.6 – 12.5	0.6 – 11.3	0.6 – 8.5	0.6-6.375	0.6 – 6.5	0.6 – 6.375	2.5 – 3.125
CEI-6G/SR/LR	4.976 – 6.375	4.976 – 6.375	4.976 – 6.375	4.976-6.375	4.976 – 6.375	-	-
CPRI	0.6144, 1.2288, 2.4876, 3.072, 4.9152, 6.144, 9.8304	0.6144, 1.2288, 2.4876, 3.072, 4.9152, 6.144	0.6144, 1.2288, 2.4576, 3.072, 4.9152, 6.144	0.6144, 1.2288, 2.4576, 3.072, 6.144	0.6144, 1.2288, 2.4576, 3.072	0.6144, 1.2288, 2.4576, 3.072, 6.144	0.6144, 1.2288, 2.4576, 3.072
Display Port	-	-	-	-	-	-	1.62, 2.7
10G Ethernet (XAUI)	3.125	3.125	3.125	3.125	3.125	3.125	3.125
10G Ethernet (XFI)	10.3125	10.3125	-	-	-	-	-
40G/100G Ethernet	10.3125	10.3125	-	-	-	-	-
GbE	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Fibre Channel	1.0625, 2.125, 4.25, 8.5, 10.52	1.0625, 2.125, 4.25, 8.5, 10.52	1.0625, 2.125, 4.25, 8.5	1.0625, 2.125, 4.25	1.0625, 2.125, 4.25	1.0625, 2.125	-
GPON	1.244 uplink, 2.488 downlink	1.244 uplink, 2.488 downlink	1.244 uplink, 2.488 downlink	-	1.244 uplink, 2.488 downlink	1.244 uplink, 2.488 downlink	-
G.709 OTU-2	10.7	10.7	-	-	-	-	-
OTN, 10GbE with FEC	11.1, 11.3	11.1, 11.3	-	-	-	-	-
HiGig+	3.75	3.75	3.75	3.75	3.75	3.75	-
HiGig2	4.0625	4.0625	4.0625	4.0625	4.0625	-	-

## Protocols, Devices, and Data Rates (Continued)


Protocols, Devices, and Data Rates							
Protocol	Stratix V GX/ GS/GT Data Rates (Gbps per Lane)	Stratix IV GT Data Rates (Gbps per Lane)	Stratix IV GX Data Rates (Gbps per Lane)	Stratix II GX Data Rates (Gbps per Lane)	HardCopy IV GX Data Rates (Gbps per Lane)	Arria II GX Data Rates (Gbps per Lane)	Cyclone IV GX Data Rates (Gbps per Lane)
HyperTransport 3.0	0.4, 2.4, 2.8, 3.2	0.4, 2.4, 2.8, 3.2	0.4, 2.4, 2.8, 3.2	-	0.4, 2.4, 2.8, 3.2	-	-
IEEE 802.3ba 10GBASE-KR	10.3125	-	-	10.3125	-	-	-
Interlaken	3.125 – 12.5	3.125 – 11.3	3.125 – 6.375	3.125 – 6.375	3.125 – 6.375	-	-
OBSAI	0.768, 1.536, 3.072	0.768, 1.536, 3.072	0.768, 1.536, 3.072	0.768, 1.536, 3.072	0.768, 1.536, 3.072	0.768, 1.536, 3.072	0.768, 1.536, 3.072
PCIe Gen1, Gen2, Gen3	2.5, 5, 8	2.5, 5, NA	2.5, 5, NA	2.5, 5, NA	2.5, 5, NA	2.5, NA, NA	2.5, NA, NA
PCIe Cable	2.5	2.5	2.5	2.5	2.5	2.5	2.5
RXAUI	6.25	6.25	6.25	6.25	6.25	-	-
QDR Infiniband	10.0	-	-	-	-	-	-
QPI	6.4	-	-	-	-	-	-
SAS	1.5, 3, 6	1.5, 3, 6	1.5, 3, 6	-	1.5, 3, 6	1.5, 3.0, 6.0	-
SATA	1.5, 3, 6	1.5, 3, 6	1.5, 3, 6	-	1.5, 3, 6	1.5, 3.0, 6.0	3.0
SerialLite II	0.6 – 6.375	0.6 – 6.375	0.6 – 6.375	0.6 – 6.375	0.6 – 6.375	0.6 – 3.75	-
Serial RapidIO	1.25, 2.5, 3.125, 5.0, 6.25	1.25, 2.5, 3.125, 5.0, 6.25	1.25, 2.5, 3.125, 5.0, 6.25	1.25, 2.5, 3.125	1.25, 2.5, 3.125	1.25, 2.5, 3.125	1.25, 2.5, 3.125
SFI-5.1	2.488 – 3.125	2.488 – 3.125	2.488 – 3.125	2.488 – 3.125	2.488 – 3.125	-	-
SFI-5.2	9.9-11.3	9.9-11.3	-	-	-	-	-
SONET OC-3/OC-12/ OC-48/OC-192	0.155, 0.622, 2.488, 9.953	0.155, 0.622, 2.488, 9.953	0.155, 0.622, 2.488, NA	0.155, 0.622, 2.488, NA	0.155, 0.622, 2.488, NA	0.155, 0.622, 2.488, NA	-
SPAUI	3.125, 6.25	3.125, 6.25	3.125, 6.25	3.125, 6.25	3.125, 6.25	3.125	-
V-by-One	-	-	-	-	-	-	3.0

The following is an overview of our configuration devices. To determine the right configuration device for your FPGA, check out our Configuration Handbook or the configuration chapter of the handbook of your selected FPGA.


Altera's serial configuration devices store the configuration file for our SRAM-based FPGAs. We designed our serial configuration devices to minimize cost and board space while providing a dedicated FPGA configuration solution. Serial configuration devices are recommended for new designs. For information on additional configuration devices supporting older products, see our Configuration Handbook.

Serial Configuration Device	Memory Size (Bits)	Package
EPCS1	1,048,576	SOIC8
EPCS4	4,194,304	SOIC8
EPCS16	16,777,216	SOIC16
EPCS64	67,108,864	SOIC16
EPCS128	134,217,728	SOIC16


## Ordering Codes



## Ordering Codes



## Ordering Codes







# Cool Value

You won't find a better CPLD value than in MAX<sup>®</sup> V CPLDs. With a unique, non-volatile architecture and one of the largest density CPLDs on the market, the MAX V family gives you:

- Lower total system cost
- Up to 50 percent lower total power vs. competitive CPLDs
- Robust new features

And with Altera, you know you'll get devices in volume when you need them.

How can you resist such a value?

**MAX V CPLDs:**  
Cool Value

[www.altera.com/maxv](http://www.altera.com/maxv)





[www.altera.com/twitter](http://www.altera.com/twitter)



[www.altera.com/facebook](http://www.altera.com/facebook)



[www.alteraforum.com](http://www.alteraforum.com)

**Altera Corporation**

101 Innovation Drive  
San Jose, CA 95134  
USA

[www.altera.com](http://www.altera.com)

**Altera European Headquarters**

Holmers Farm Way  
High Wycombe  
Buckinghamshire  
HP12 4XF  
United Kingdom  
Telephone: (44) 1 494 602 000

**Altera Japan Ltd.**

Shinjuku I Tower 32F  
6-5-1, Nishi Shinjuku  
Shinjuku-ku, Tokyo 163-1332  
Japan  
Telephone: (81) 3 3340 9480  
[www.altera.co.jp](http://www.altera.co.jp)

**Altera International Ltd.**

Unit 11- 18, 9/F  
Millennium City 1, Tower 1  
388 Kwun Tong Road  
Kwun Tong  
Kowloon, Hong Kong  
Telephone: (852) 2 945 7000  
[www.altera.com.cn](http://www.altera.com.cn)



FSC logo

Copyright © 2010 Altera Corporation. All rights reserved. Altera, the stylized Altera logo, specific device designations, and all other words and logos that are identified as trademarks and/or service marks are, unless noted otherwise, the trademarks and service marks of Altera Corporation in the U.S. and other countries. RapidIO is a trademark of the RapidIO Trade Association. HyperTransport is a trademark of the HyperTransport Consortium. ModelSim is a registered trademark of Mentor Graphics Corporation. All other product or service names are the property of their respective holders. Altera products are protected under numerous U.S. and foreign patents and pending applications, mask work rights, and copyrights. Altera warrants performance of its semiconductor products to current specifications in accordance with Altera's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Altera assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Altera. Altera customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services. 6K January 2011

SG-PRDCT-9.0