



### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### General

|                    |  |
|--------------------|--|
| Provided equipment | Documentation CD<br>Installation guide<br>Rack mounting brackets |
|--------------------|--|

### Physical

|              |         |
|--------------|---------|
| Cable length | 3.66 m  |
| Colour       | Black   |
| Depth        | 25.4 cm |
| Height       | 8.9 cm  |
| Net weight   | 6.32 kg |
| Width        | 44.4 cm |

### Input

|                      |                         |
|----------------------|-------------------------|
| [In] rated current   | 24 A                    |
| Permissible voltage  | 200...240 V             |
| Input current limits | 30 A                    |
| Load capacity        | 4992 VA                 |
| Network frequency    | 50/60 Hz                |
| Plug standard        | NEMA L6-30P             |
| Input voltage        | 200 V<br>208 V<br>230 V |

### Output

|                                |                  |
|--------------------------------|------------------|
| Number of power socket outlets | 16 IEC 60320 C13 |
|--------------------------------|------------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Conformance

|                        |  |
|------------------------|--|
| Product certifications | CUL listed<br>CSA<br>Industry Canada<br>PSE<br>UL listed |
| Standards              | FCC part 15 class A<br>ICES-003<br>UL 60950              |

## Environmental

|                                       |                   |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...45 °C         |
| Relative humidity                     | 0...95 %          |
| Operating altitude                    | 0...10000 ft      |
| Ambient air temperature for storage   | -25...65 °C       |
| Storage altitude                      | 0.00...15240.00 m |

## Packing Units

|                  |         |
|------------------|---------|
| Package 1 Weight | 8.36 kg |
| Package 1 Height | 14.6 cm |
| Package 1 width  | 51.4 cm |
| Package 1 Length | 51.4 cm |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product                            |
| REACH Regulation            | <a href="#">REACH Declaration</a>                |
| EU RoHS Directive           | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free                | Yes  |
| RoHS exemption information  | <a href="#">Yes</a>                              |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>    |
| Circularity Profile         | <a href="#">End of Life Information</a>          |
| Optimized Energy Efficiency | Energy efficient product                         |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|