



## Overview

Lead time	Usually Ships within 3 Weeks
-----------	------------------------------

## General

Provided equipment	Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable
Performance multiplier	1
Number of tare power	70 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S
Value multiplier	1

## Physical

Cable length	2.44 m
Number of rack unit	2U
Colour	Black
Depth	67.1 cm
Height	8.6 cm
Mounting location	Front
Mounting preference	Lower
Net weight	44 kg
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Width	43.2 cm
-------	---------

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA L5-30P
Maximum input current	24 A
Number of cables	1
Input voltage	100 V

## Output

Rated power in W	2400 W
Maximum configurable power in W	2700 W
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R 2 NEMA 5-20R
Graph display	1
Output voltage	100 V
Maximum configurable power in VA	3000 VA
Rated power in VA	2400 VA

## Conformance

Product certifications	VCCI class A
Standards	UL 1778

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Show note OP temperature	No

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	C
Battery charger power	125 W rated
Battery power in VAh	500 VAh runtime
Battery life	4...6 year(s)
Extended runtime	0

## Communications & Management

Free slots	1
Control panel	LED status display with on line : on battery : replace battery and overload indicators Multifunction LCD status and control console

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	459 J
-------------------	-------

## Packing Units

Package 1 Weight	52 kg
Package 1 Height	25.4 cm
Package 1 width	60 cm
Package 1 Length	98 cm
Number of Units in Package 3	8

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product

## Contractual warranty

Warranty	2 years (Japan only)
----------	----------------------