



Overview

Model Name	APC Smart-UPS 750VA LCD 120V
Includes	CD with software , Documentation CD , USB cable
Standard Lead Time	Usually in Stock
Product Distribution	Canada , United States

Output

Output Power Capacity	500 Watts / 750 VA
Max Configurable Power (Watts)	500 Watts / 750 VA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Sine wave
Output Connections	(6) NEMA 5-15R (Battery Backup)

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P
Cord Length	6 feet (1,83 meters)
Input voltage range for main operations	82 - 144 V
Input voltage adjustable range for mains operation	75 - 154V
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0

Typical recharge time	3 hour(s)
Replacement Battery	RBC48
RBC Quantity	1

Communications & Management

Interface Port(s)	SmartSlot , USB
Available SmartSlot™ Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

Surge Protection and Filtering

Surge energy rating	540 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	6.34 inches (161.0 mm)
Maximum Width	5.43 inches (138.0 mm)
Maximum Depth	14.29 inches (363.0 mm)
Rack Height	0 U
Net Weight	29.0 lbs (13.18 kg)
Shipping Weight	31.3 lbs (14.23 kg)
Shipping Height	11.85 inches (301.0 mm)
Shipping Width	10.95 inches (278.0 mm)
Shipping Depth	19.65 inches (499.0 mm)
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
SCC Codes	0
Units per Pallet	24.0

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)
Audible noise at 1 meter from surface of unit	40.000 dB
Online Thermal Dissipation	90.000 BTU/hr

Conformance

Approvals	CSA , ENERGY STAR V1.0 (USA) , UL 1778
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery
Equipment protection policy	Lifetime : \$150000

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs