



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Documentation CD Smart UPS signalling RS-232 cable
Performance multiplier	1
Number of tare power	15 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom Workstation
UPS size	S
Value multiplier	1

Physical

Cable length	1.83 M
Colour	Black
Depth	35.9 Cm
Height	16.7 Cm
Mounting location	Front
Mounting preference	No preference
Net weight	13 Kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Width	14 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Input voltage limits	70...125 V adjustable 80...123 V
Maximum input current	8 A
Number of cables	1
Input voltage	100 V

Output

Rated power in W	500 W
Maximum configurable power in W	500 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R
Graph display	1
Output voltage	100 V
Maximum configurable power in VA	750 VA
Rated power in VA	750 VA

Conformance

Product certifications	VCCI class A
Standards	UL 1778

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 M
Acoustic level	40 dBA
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 H
Number of battery replacement quantity	1
Liquid value	0
Battery curve	B
Battery charger power	36 W rated
Battery power in VAH	146 VAh runtime
Battery life	4...6 Year(S)
Extended runtime	0

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	540 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	14.8 Kg
Package 1 Height	30.1 Cm
Package 1 width	27.8 Cm
Package 1 Length	49.9 Cm
Number of Units in Package 3	24

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years (Japan only)
----------	----------------------

Product Life Status : **Commercialised**