



Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

General

Provided equipment	CD with software Installation guide Smart UPS signalling RS-232 cable
Product web sub-family	TAA Compliant
Performance multiplier	1
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS
Value multiplier	1
Variant option	Shipboard

Physical

Cable length	2.44 m
Number of rack unit	2U
Colour	Black
Depth	45.7 cm
Height	8.9 cm
Mounting location	Front
Mounting preference	Lower
Net weight	28.64 kg
Mounting mode	Rack-mounted

Two post mountable	0
USB compatible	Yes
Width	48.3 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Input voltage limits	82...144 V
Number of cables	1
Input voltage	120 V

Output

Rated power in W	980 W
Maximum configurable power in W	980 W
Harmonic distortion	Less than 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R
Curve equation	Efficiency
Curve fixed loss	0.0232
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0
Curve square loss	0.0152
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	1440 VA
Rated power in VA	1440 VA

Conformance

Product certifications	CSA TAA compliance
Standards	UL 1778

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m

Acoustic level	46 dBA
Heat dissipation	171 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Liquid value	0
Battery curve	Z
Battery charger power	144 W rated
Battery power in VAH	432 VAh runtime
Battery life	4...6 year(s)
Extended runtime	0

Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	31.91 kg
Package 1 Height	25.1 cm
Package 1 width	59.4 cm
Package 1 Length	60.3 cm
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------