



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Rack mounting brackets Rack mounting support rails User guide in japanese
Performance multiplier	1
Number of power module	480
Number of tare power	37 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Cable length	2.44 m
Number of rack unit	1U
Colour	Black
Depth	66 cm
Height	4.4 cm
Mounting location	Front
Mounting preference	Lower
Net weight	21.8 kg

Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Width	48.3 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Maximum input current	10 A
Switching current capacity	12 A
Number of cables	1
Input voltage	100 V

Output

Rated power in W	480 W
Maximum configurable power in W	480 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	4 NEMA 5-15R
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	100 V
Maximum configurable power in VA	750 VA
Rated power in VA	750 VA

Conformance

Product certifications	VCCI
Standards	UL 1778

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	A
Battery charger power	67 W rated
Battery power in VAH	202 VAh runtime
Battery life	2...4 year(s)
Extended runtime	0

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Packing Units

Package 1 Weight	25.4 kg
Package 1 Height	19.1 cm
Package 1 width	55.9 cm
Package 1 Length	77.5 cm
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------