



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

General

| | |
|-------------------------------------|---|
| Provided equipment | CD with software Rack mounting support rails Smart UPS signalling RS-232 cable User manual Web/SNMP management card |
| Performance multiplier | 1 |
| Number of tare power | 175 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| Size UPS version | Internetworking Server Telecom |
| UPS size | S |
| Value multiplier | 1 |

Physical

| | |
|---------------------|--------------|
| Number of rack unit | 12U |
| Colour | Black |
| Depth | 77.3 cm |
| Height | 53.3 cm |
| Mounting location | Front |
| Mounting preference | Lower |
| Net weight | 247.73 kg |
| Mounting mode | Rack-mounted |
| Two post mountable | 0 |

| | |
|----------------|---------|
| USB compatible | No |
| Width | 43.2 cm |

Input

| | |
|----------------------------|--|
| Network frequency | 40...70 Hz auto-sensing |
| Number of input connectors | 1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E) |
| Input voltage limits | 160...280 V |
| Inputvolt_other | 220 V 240 V |
| Maximum input current | 90 A |
| Switching current capacity | 100 A |
| Input harmonic distortion | Less than 5 % for full load |
| Input current | 90 A (1 phase) 30 A per phase (3 phases) |
| Input voltage | 230 V 400 V 3 phases |
| Load power factor | 0.8 |
| Cos phi | 0.95 |

Output

| | |
|---------------------------------|---|
| Rated power in W | 12000 W |
| Maximum configurable power in W | 12000 W |
| Harmonic distortion | Less than 5 % |
| Output frequency | 50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains |
| Outputvolt_other | 220 V 240 V |
| Crest factor | 3 : 1 |
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Output connector type | Hard wire 3-wire (H N + E) 1 Hard wire 5-wire (3P + N + E) 1 |
| Nb of power socket outlets | 2 IEC Jumpers 8 IEC 60320 C19 |
| Output overload operation | 60 seconds at 125% and 30 seconds at 150% |
| Bypass type | Built-in static bypass Internal bypass (automatic and manual) Optional external bypass |
| Curve equation | Efficiency |
| Curve fixed loss | 0.017 |
| Curve load maximum | 100 % |
| Curve load minimum | 2 % |
| Curve proportional loss | 0 |
| Curve square loss | 0.036 |
| Curve X-axis maximum | 100 % |
| Curve test cond ID | Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output. |
| Curve X-axis minimum | 0 % |
| Curve X-axis title | Load |
| Curve X-axis units | Percentage |
| Curve Y-axis maximum | 100 % |
| Curve Y-axis minimum | 50 % |
| Curve Y-axis title | Efficiency |
| Curve Y-axis units | Percentage |
| Efficiency | 93 % (in battery operation) |

| | |
|----------------------------------|----------|
| Graph display | 1 |
| Output voltage | 230 V |
| Maximum configurable power in VA | 15000 VA |
| Rated power in VA | 15000 VA |

Conformance

| | |
|------------------------|------------------------------------|
| Product certifications | VDE |
| Standards | EN/IEC 62040-2 EN/IEC 62040-1-1 |

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % Non-condensing |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 50 dBA |
| Heat dissipation | 2800 Btu/h |
| Show note OP temperature | No |
| IP degree of protection | IP20 |

Batteries & Runtime

| | |
|--|---|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 4 |
| Number of battery free slots | 0 |
| Battery recharge time | 2.5 h |
| Number of battery replacement quantity | 4 |
| Additional information | Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage |
| Liquid value | 0 |
| Battery voltage | +/- 192 V (split battery referenced to neutral) |
| Battery curve | C |
| Battery charger power | 1530 W rated |
| Battery power in VAh | 3840 VAh runtime |
| Battery life | 3...5 year(s) |
| Battery option | SURT192RMXLBP2 1 7680 VAh SURT192RMXLBP2 2 11520 VAh SURT192RMXLBP2 3 15360 VAh SURT192RMXLBP2 4 19200 VAh SURT192RMXLBP2 5 23040 VAh SURT192RMXLBP2 6 26880 VAh SURT192RMXLBP2 7 30720 VAh SURT192RMXLBP2 9 38400 VAh |
| Extended runtime | 1 |

Communications & Management

| | |
|---------------------|---|
| Free slots | 0 |
| Preinstalled device | Network management card 2 with environmental monitoring |
| Control panel | Multifunction LCD status and control console |
| Alarm | Audible and visible alarms : configurable delays |
| Emergency power off | Yes |

Surge Protection and Filtering

| | |
|-------------------|--|
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |
|-------------------|--|

Packing Units

| | |
|------------------------------|-----------|
| Package 1 Weight | 314.09 kg |
| Package 1 Height | 99 cm |
| Package 1 width | 61 cm |
| Package 1 Length | 100.3 cm |
| Number of Units in Package 3 | 1 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|