



Overview

Presentation	A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission critical environments.
Lead time	Usually Ships within 6 Weeks

General

Provided equipment	Assembly service Installation guide Start-up service User manual Web/SNMP management card
Product web sub-family	Symmetra PX 250/500kW
Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Performance multiplier	0.350208
Number of power module free slots	5
Number of power module filled slots	5
Redundant	Yes
Size UPS version	Internetworking Server Telecom
UPS size	L
Value multiplier	0.81

Physical

Colour	Black
Depth	107 cm
Height	199.1 cm
Mounting preference	No preference
Net weight	1227 kg
Mounting mode	Not rack-mountable
Two post mountable	0

USB compatible	No
Width	160 cm

Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	408...552 V 480 V
Inputvolt_other	415 V
Max short time withstand current	50 kA
Input harmonic distortion	Less than 5 % for full load
Input protection type	3-pole circuit breaker
Input voltage	480 V 3 phases 400 V 3 phases
Load power factor	0.5 leading to 0.5 lagging
Cos phi	0.99

Output

Rated power in W	125000 W
Maximum configurable power in W	500000 W
Harmonic distortion	Less than 2 %
Output frequency	50 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz sync to mains
Outputvolt_other	415 V
UPS type	Double conversion online
Wave type	Sine wave
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
Output harmonic distortion	< 2% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in maintenance bypass Built-in static bypass
Curve equation	Efficiency
Curve fixed loss	0.0082
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0.0156
Curve square loss	0.0162
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 480V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	96 % (in battery operation)
Graph display	0
Output voltage	480 V 3 phases

	400 V 3 phases
Maximum configurable power in VA	500000 VA
Rated power in VA	125000 VA
Transfer time	2 ms typical

Conformance

Product certifications	CUL listed UL listed
Standards	CSA C22.2 No 107.3-05 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 OSHDP UL 1778 UL 60950-1

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-30...70 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	54 dBA
Heat dissipation	15473 Btu/h
Show note OP temperature	No
NEMA degree of protection	NEMA 1
IP degree of protection	IP20

Batteries & Runtime

Battery type	External battery system
Number of battery free slots	0
Liquid value	0
Battery curve	P
Battery power in VAH	0 VAh runtime
Extended runtime	1

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus
Control panel	Touch screen LCD user interface
Emergency power off	Optional

Packing Units

Package 1 Weight	1377 kg
Package 1 Height	215 cm
Package 1 width	187 cm
Package 1 Length	127 cm

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Not compliant
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---