

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.

Property of FCI. Copyright FCI. Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du propi Propriete de c FCI. Broits de reproduction FCI. Φ 6.20 ±0.10 (2X) 10028542-002LF .0028542-003LF .0028542-001LF POS. 1 12 Ф 0.05 Z U V PCB assassassassas C0.8X0.6±0.1 3.18 ± 0.10 l.57±0.10 .57±0.10 THICKNESS 381 Ø0,65 1.65 0 → Ø0.05 0 RECOMMENDED PCB LAYOUT 0 TYP. 0 <u> FOLERANCES</u> DIMENSION 'A' U V 2.75±0.20 2.75±0.20 4.35±0.20 0 SECTION A-A Ф 0.10 ф 0.20 X Y 51.73 ± 0.15 44.54 ± 0.08 54.79 ± 0.30 -46.00 52,23 <u>-</u> XYZ 00 6 DIMENSION 'B' 0 ို 3.20±0.10 3.20±0.10 4.80±0.10 CENTERLINE OF HOLES FOR 2 POSTS ro 0 Ø2.20 IMENSION 'C' 3.65±0.10 3.65 ± 0.10 2.10±0.10 25. 0.385 ಜ -5.40 ± 0.08 1.27 -3.75 ± 0.10 Ļ title DIMENSION Catalog 0.79±0.10 .43±0.10 .,43±0.10 ω NOTES MATERIAL:
HOUSING: HIGH TEMPERATURE PLASTIC, BLACK OR GRAY, UL94V-0
CONTACT: COPPER ALLOY
HOLD DOWN: COPPER ALLOY
FINISH: 1.27um MIN NICKEL UNDERPLATE DVERALL,
1.91um MIN TIN (LEAD-FREE) DN SOLDER TAIL,
0.76um MIN GOLD IN CONTACT AREA
THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
THE HOUSING VILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE
FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOCONTACT WIPE: 2.07 MIN FOR SIGNAL AND 2.52 MIN FOR GROUND <u>-</u> Ą ω ω LANE VERTICAL -2.75 ± 0.05 FIT HEADER CONTACT 1.75±0.05 -1.63 ±0.05 PLASTIC R0.20 ±0.05 SECTION -Z-- -4.20 ±0.15 (SIGNAL PIN) (GROUND PIN) 4.65 ± 0.15 dwg no) PEAK TEMPERATURE ? VAPOR PHASE REFLOW OVEN I FOR GROUND LUSTOMER 4 9 Ф .0028542 1.27 0.15 ±0.03 Sheet 2 of TYP. Rev. ₩ C J ₩ ⊳