

L9WCTXXX-CXXX-SSU1 Series

15-23W, 120-277Vac Input, Constant Current Triac Dimming LED Driver

Features

- Power rating: 15-23W
- Input Voltage: 120-277Vac
- Constant current design
- Output Current (420mA-700mA)
- Max. 45V output
- Triac Dimming, leading or trailing phase control
- Efficiency up to 80%
- Isolated output for lamp safety
- SCP and OCP
- Tc = 90°C
- UL Class P / Class 2 Output
- SELV Output
- 3-year warranty

Application

• High Brightness Light-Emitting Diode Products

Model List*(See part number scheme for model number details)



*Product images are for illustrative purposes only and may vary from actual design.

Model Number	Input Voltage Range	Output Power	Power Factor	Output Voltage	Output Current Min.	Output Current Max.	Efficiency	Certification
L9WCT015-C042-SS1U	120-277Vac	15W	>0.9	30-40V	420mA	420mA	>80%	CE/UL/cUL
L9WCT018-C050-SS1U	120-277Vac	18W	>0.9	30-40V	500mA	500mA	>80%	CE/UL/cUL
L9WCT023-C070-SS1U	120-277Vac	23W	>0.9	25-32V	700mA	700mA	>80%	CE/UL/cUL

*150mA-820mA with a max output voltage of 45V options available, contact Autec Sales for all available options.


Disclaimer:

Autec Power Systems' (Autec) LED Drivers are Hi-Pot tested during the manufacturing process. Autec assumes no responsibility for secondary Hi-Pot testing at customer location or designated production line(s). Should customer require further Hi-Pot testing, at their own production line, following assembly of the LED Driver into the customer's assembled fixture, Autec requests advance notice. This request must be communicated to Autec in a timely manner and is recommended to be requested at time of issuing each purchase order.




L9WCTXXX-CXXX-SSU1 Series

15-23W, 120-277Vac Input, Constant Current Triac Dimming LED Driver



Mechanical Diagram



60mm

71mm

Dimensions				
Length	60mm			
Width	54mm			
Height	30mm			
Mounting	71mm			


 Technical Sales / Customer Service:
 +1-818-338-7788
 •
 Email: sales@autec.com

 31328 Via Colinas Suite 102
 •
 Westlake Village, CA 91362 USA
 •
 www.autec.com

 January 29, 2020
 2 / 3
 2 / 3
 •
 •



15-23W, 120-277Vac Input, Constant Current Triac Dimming LED Driver



*Product images are for illustrative purposes only and may vary from actual design. *Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.