

■ Features

- Power Rating: 5W
- Input Voltage: 120Vac
- Constant current design
- Output current (130mA-200mA)
- Fixed output current
- Efficiency up to 74%
- Dimming: Triac trailing edge dimming option
- UL Class 2, Class P, Type HL
- OVP, SCP, & Open Circuit Protection
- IP20
- 5-year warranty

RoHS
Compliant



*Product images are for illustrative purposes only and may vary from actual design.


■ Application

- Indoor lights

■ Model List*(See part number scheme for model number details)

Model Number	Input Voltage Range	Output Power	Output Voltage	Output Current Min.	Output Current Max.	Efficiency	Certification
LXLCT005S013PS-20	120Vac \pm 10%	5W	19-38V	130mA	130mA	74%	UL/cUL
LXLCT005S015PS-20	120Vac \pm 10%	5W	16-33V	150mA	150mA	74%	UL/cUL
LXLCT005S020PS-20	120Vac \pm 10%	5W	14-28V	200mA	200mA	74%	UL/cUL

■ Wiring Diagram



Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com


31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

June 14, 2019

1 / 5

■ Wiring Diagram(Cont.)

Wire Specifications	
Input Wire	12" UL 1316 #18AWG (Black and White)
Output Wire	12" UL 1316 #22AWG (Red and Blue)



■ Technical Data

Input voltage range	120Vac \pm 10%
Frequency	60Hz
Power factor	> 0.9 under 120Vac input with 80-100% load condition
Inrush current	20A@120V
Max input current	0.07A @120V
THD	< 20%
Load Regulation	\pm 2%
Line Regulation	\pm 1%
Output Tolerance	\pm 5% at full load condition
Turn-on Delay Time	< 0.5s at full load condition
Overshoot	< 10% at full load condition
No Load Power Consumption	< 1W
Withstand voltage	Input to output, 2,800Vdc, 2mA
Leakage current:	Maximum 0.5mA at 120Vac, 60Hz input
Protection	Over voltage protection: Hiccup mode. Protection will trigger when load voltage exceed specified output voltage and will auto recover after the fault mode is removed. Over current protection: Hiccup mode. Protection will trigger when load current exceed specified output current and will auto recover after the fault mode is removed. Short circuit protection: Hiccup mode. Protection will trigger when short circuit and will auto recover after the fault mode is removed.
Operating Temperature	-40° to 60°C
Storage Temperature	-40° to 85°C
Humidity	5% to 95%

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

June 14, 2019

2 / 5

■ Technical Data(cont.)

MTBF	570,000 hours at 40°C ambient (~70°C Case temp.)
Life rating	80,000 hours at 120Vac input, 100% load and 60°C case temperature
Maximum case Temperature	90°C
Length (L)	3.71" (94.3mm)
Width (W)	1.3" (33mm)
Height (H)	0.79" (20mm)
Mounting (M)	3.42" (86.8mm)
Weight	9kg
Packing	0.08kg /unit; 100pcs/carton; 4,200pcs/pallet

■ Safety Compliance


UL/cUL	UL 8750, Class P, Type HL
CE	EN61347-1, EN61347-2-13
FCC, 47CFR Part 15	ANSI C63.4:2009 Class B (Consumer Limit)
EN61000-3-2	Harmonic Current Emissions Class C

Disclaimer:

Autec Power Systems' (Autec) LED Drivers are Hi-Pot tested during the manufacturing process. Autec assumes no responsibility for secondary Hi-Pot testing at customer location or designated production line(s). Should customer require further Hi-Pot testing, at their own production line, following assembly of the LED Driver into the customer's assembled fixture, Autec requests advance notice. This request must be communicated to Autec in a timely manner and is recommended to be requested at time of issuing each purchase order.

■ Lifetime/Case Temp

Lifetime vs Case Temperature




Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com


June 14, 2019

3 / 5

■ Power Derating vs Case Temperature



■ Power Factor vs Load





Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

June 14, 2019

4 / 5

■ **Efficiency vs Load**



Product images are for illustrative purposes only and may vary from actual design.

***Specifications are subject to change without notice. Autec is not Responsible for issues arising from errors or omissions.**

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

June 14, 2019

5 / 5