



**Product:** [9541](#) 

RS232, #24-15c, SR-PVC, O/A Foil, PVC Jkt, CMG

## Product Description

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

## Technical Specifications

### Product Overview

Product Category:	Computer RS-232
Suitable Applications:	RS-232 Applications; Computer Communications; Low Voltage Analog Signals (4-20mA, 0-10V, ...); Low Voltage Digital Control (24V, ...); Line Level Audio; Panel Wiring

### Construction Details

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	15	24	7x32	TC - Tinned Copper

#### Insulation

Element	Material	Thickness [in]	Color
Conductor(s)	S-R PVC - Semi-Rigid Polyvinyl Chloride	0.0105	Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Blue/Black Stripe, Black/White Stripe, Red/White Stripe, Green/White Stripe, Blue/White Stripe

#### Outer Shield Material

Type	Material	Coverage
Tape	Alum / Poly	100%

#### Outer Jacket Material

Material	Nominal Wall Thickness	Nominal Diameter
PVC - Polyvinyl Chloride	0.032 in	0.284 in

### Electrical Characteristics

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Grnd	Max. Current
Conductor(s)	25 Ohm/1000ft	30 pF/ft	55 pF/ft	1.75 Amps per conductor @ 25°C ambient

#### Voltage

UL Voltage Rating
300 V

### Mechanical Characteristics

#### Temperature

UL Rating	Operating
80°C (UL AWM 2464)	-30°C to +80°C

#### Bend Radius

-

Stationary Min.
3 in

Max Recommended Pulling Tension:	82.5 lbs
----------------------------------	----------

### Standards and Compliance

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65 (CJ for Wire and Cable)=Yes
Flammability / Fire Resistance:	UL1685 FT4 Loading, FT4, IEC 60332-1-2
NEC / UL Compliance:	800, CMG
AWM Compliance:	2464, AWM I A
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS 2

### History

Update and Revision:	Revision Number: 0.298 Revision Date: 05-22-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.