

145 Adams Avenue, Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N5303

NPN SILICON POWER TRANSISTOR

JEDEC TO-3 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5303 type is a NPN Silicon Epitaxial Planar Transistors designed for power amplifier and switching applications.

MAXIMUM RATINGS (T_C = 25°C)

	SYMBOL		<u>UNITS</u>
Collector-Base Voltage	V _{CBO}	80	V
Collector-Emitter Voltage	V _{CEO}	80	V
Collector Current	IC	20	Α
Base Current	ΙΒ	7.5	Α
Power Dissipation	P_{D}	200	W
Operating and Storage	_		
Junction Temperature	T_J, T_stg	-65 to +200	oC
Thermal Resistance	θ_{JC}	0.875	°C/W

ELECTRICAL CHARACTERISTICS ($T_C = 25^{\circ}C$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	<u>MAX</u>	<u>UNITS</u>
ICBO	V _{CB} =80V		1.0	mA
ICEO	V _{CE} =80V		5.0	mA
ICEX	$V_{CE} = 80V, V_{BE} = 1.5V$		1.0	mA
^I CEX	$V_{CE} = 80V$, $V_{BE} = 1.5V$, $T_{C} = 150^{\circ}C$		10	mA
I _{EBO}	V _{BE} = 5.0V		5.0	mA
BV CEO	1 _C = 200mA	80		V
VCE(SAT)	$I_{C} = 10A$, $I_{B} = 1.0A$		1.0	V
VCE(SAT)	$I_{C} = 15A$, $I_{B} = 1.5A$		1.5	V
VCE(SAT)	$I_{C} = 20 I_{B} = 4.0A$		2.0	V
V _{BE} (SAT)	$I_C = 10A$, $I_B = 1.0A$		1.7	V
V _{BE} (SAT)	$I_{C} = 15A$, $I_{B} = 1.5A$		2.0	V
V _{BE} (SAT)	$I_{C} = 20 I_{B} = 4.0A$		2.5	V
V _{BE} (ON)	$V_{CE} = 2.0V, I_{C} = 10A$		1.5	V
V _{BE(ON)}	$V_{CE} = 4.0V, I_{C} = 20A$		2.5	V

ELECTRICAL CHARACTERISTICS (Continued)

<u>SYMBOL</u>	TEST CONDITIONS	<u>MIN</u>	MAX	Ulvr1S
h _{FE}	$V_{CE} = 2.0V, I_{C} = 1.0A$	40		
h _{FE}	$V_{CE} = 2.0V, I_{C} = 10A$	15	60	
h _{FE}	$V_{CE} = 4.0V, I_{C} = 20A$	5.0		
f _T	$V_{CE} = 10V$, $I_{C} = 1.0A$, $f = 1.0MHz$	2.0		MHz
h _{fe}	$V_{CE} = 10V$, $I_{C} = 1.0A$, $f = 1.0kHz$	40		
t _r	$V_{CC} = 30V$, $I_C = 10A$, $I_{B1} = I_{B2} = 1.0A$		1.0	μs
t _s	$V_{CC} = 30V$, $I_C = 10A$, $I_{B1} = I_{B2} = 1.0A$		2.0	μs
tf	$V_{CC} = 30V$, $I_{C} = 10A$, $I_{B1} = I_{B2} = 1.0A$		1.0	μs



145 Adams Avenue Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824 www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: 2N5303