



10258.4

PK 550/13/3,50-V DG

PK 550/13/3,50-V DG



PCB terminal, Wire protection, No. of poles: 13, Width: 45.5 mm, Colour: Dark grey

Business data

|                                            |          |
|--------------------------------------------|----------|
| Packaging unit                             | 50       |
| Quantity unit                              | PC       |
| Packaging type                             | Carton   |
| Type of banding                            | Without  |
| Weight per piece (not including packaging) | 5.53     |
| Weight per piece (including packaging)     | 6.03     |
| Unit of weight                             | G        |
| Customs number                             | 85369010 |
| Country of origin                          | QU       |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Technical Data

---

### Dimensions

|                            |         |
|----------------------------|---------|
| Length                     | 6.5 mm  |
| Length of the pin          | 3.5 mm  |
| Width                      | 45.5 mm |
| Width left                 | 1.75 mm |
| Width right                | 1.75 mm |
| Height                     | 8.2 mm  |
| Drill hole diameter        | 1.2 mm  |
| Diameter of connecting pin | 0.9 mm  |
| Pitch                      | 3.5 mm  |

### Ratings

|                       |                   |
|-----------------------|-------------------|
| Rated voltage         | 130 V             |
| Rated current         | 13.5 A            |
| Rated cross-section   | 1 mm <sup>2</sup> |
| Rated impulse voltage | 1.25 kV           |
| Overvoltage category  | III               |
| Contamination degree  | 3                 |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Technical Data

---

### Connection data

|                                                          |                      |
|----------------------------------------------------------|----------------------|
| Connection principle                                     | Wire protection      |
| Connection type of PCB                                   | Solder connection    |
| Type of attachment to circuit board                      | Connecting contact   |
| Angle of PCB/wire connection                             | 0°/180° (horizontal) |
| No. of poles                                             | 13                   |
| Number of levels                                         | 1                    |
| Wire cross-section single-core (rigid) / stranded, min.  | 0.08 mm <sup>2</sup> |
| Wire cross-section single core (rigid)/stranded, max.    | 1.5 mm <sup>2</sup>  |
| Wire cross-section stranded, min.                        | 0.08 mm <sup>2</sup> |
| Wire cross-section stranded, max.                        | 1 mm <sup>2</sup>    |
| Wire cross-section stranded with wire-end ferrules, min. | 0.14 mm <sup>2</sup> |
| Wire cross-section stranded with wire-end ferrules, max. | 0.5 mm <sup>2</sup>  |
| Wire cross-section AWG, min.                             | 28                   |
| Wire cross-section AWG, max.                             | 16                   |
| Stripping length                                         | 5.5 mm               |
| Screw threading                                          | M 2                  |
| Torque                                                   | 0.2 Nm               |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Technical Data

---

### Materials

|                           |                 |
|---------------------------|-----------------|
| Insulation housing        | Polyamide 6.6   |
| Flammability class UL 94  | V-0             |
| Working temperature, min. | -30 °C          |
| Working temperature, max. | 105 °C          |
| Clamping element          | Brass           |
| Screws                    | Steel           |
| Wire protection           | Stainless steel |

### Further technical data

|                                                |                             |
|------------------------------------------------|-----------------------------|
| Storage temperature, min.                      | -40 °C                      |
| Storage temperature, max.                      | 105 °C                      |
| Insulation resistance                          | 1*10 <sup>13</sup> Ohm x cm |
| Creepage-current resistance                    | CTI 600                     |
| Glow wire flammability index GWFI              | GWFI 850                    |
| GWFI after-glow time                           | 30 Sek.                     |
| Glow wire ignition temperature GWIT            | GWIT 775 °C                 |
| GWIT exposure time                             | 5 Sek.                      |
| Connection cycles, in compliance with standard | 5                           |
| Recommended wave soldering temperature         | 265 °C                      |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Technical Data

---

### Further technical data

---

|                                           |        |
|-------------------------------------------|--------|
| Recommended wave soldering duration, min. | 3 Sek. |
|-------------------------------------------|--------|

|                                           |        |
|-------------------------------------------|--------|
| Recommended wave soldering duration, max. | 4 Sek. |
|-------------------------------------------|--------|

---

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Approvals

---

### cUL Recognized

|                                                      |                 |
|------------------------------------------------------|-----------------|
| cUL Recognized                                       | CSA 22.2 No.158 |
| cUL Recognized                                       | ✓               |
| cUL Usegroup B: rated voltage                        | 125 V           |
| cUL Usegroup B: rated current                        | 6 A             |
| cUL wire cross-section single-core (rigid) AWG, min. | 28              |
| cUL wire cross-section single-core (rigid) AWG, max. | 16              |
| cUL wire cross-section stranded AWG, min.            | 16              |
| cUL wire cross-section stranded AWG, max.            | 28              |
| cUL torque                                           | 0.25 Nm         |
| cUL wire material                                    | Cu              |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Approvals

---

### UL Recognized

|                                                     |            |
|-----------------------------------------------------|------------|
| UL Recognized                                       | UL 1059    |
| UL Recognized granted                               | ✓          |
| UL Usegroup B: rated voltage                        | 125 V      |
| UL Usegroup B: rated current                        | 6 A        |
| UL wire cross-section single-core (rigid) AWG, min. | 28         |
| UL wire cross-section single-core (rigid) AWG, max. | 16         |
| UL wire cross-section stranded AWG, min.            | 16         |
| UL wire cross-section stranded AWG, max.            | 28         |
| UL torque                                           | 2.21 Lb In |
| UL wire material                                    | Cu         |
| UL factory wiring                                   | ✓          |
| UL field wiring                                     | ✓          |

**10258.4**

**PK 550/13/3,50-V DG**

**PK 550/13/3,50-V DG**

## Approvals

---

### VDE approval

|                                                     |                     |
|-----------------------------------------------------|---------------------|
| VDE approval                                        | DIN EN 60998        |
| VDE approval granted                                | ✓                   |
| VDE rated voltage                                   | 130 V               |
| VDE rated current                                   | 13.5 A              |
| VDE rated current wire cross-section rigid, max.    | 13.5 A              |
| VDE rated current wire cross-section stranded, max. | 13.5 A              |
| VDE rated impulse voltage                           | 1.25 kV             |
| VDE wire cross-section rigid, min.                  | 0.5 mm <sup>2</sup> |
| VDE wire cross-section rigid, max.                  | 1 mm <sup>2</sup>   |
| VDE wire cross-section stranded, min.               | 0.5 mm <sup>2</sup> |
| VDE wire cross-section stranded, max.               | 1 mm <sup>2</sup>   |
| VDE screw threading                                 | M 2                 |
| VDE torque                                          | 0.2 Nm              |
| VDE overvoltage category                            | III                 |
| VDE contamination degree                            | 3                   |






10258.4

PK 550/13/3,50-V DG

PK 550/13/3,50-V DG

Media

---



**CR<sup>®</sup> US**

