


## 15532.2

### PSCU 1/240V AC/24V DC

### PSCU 1/240V AC/24V DC



Plug-Solid-State-Compact (PSC) Complete, Consisting of base PRC... with screw connection and plug-in miniature SSR PSC..., Mounting type: Mounting rail TS 35, 1 NO contact, Input voltage: 240 VAC

#### Business data

Product description	Solid-state terminal
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	33.2
Weight per piece (including packaging)	35
Unit of weight	G
Customs number	85364900
Country of origin	QU

## 15532.2

PSCU 1/240V AC/24V DC

PSCU 1/240V AC/24V DC

### Technical Data

---

#### Dimensions

---

Length	87.3 mm
Width	6.2 mm
Height	79.9 mm

#### Connection data

---

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Stripping length	10 mm
Torque	0.5 Nm

## 15532.2

PSCU 1/240V AC/24V DC

PSCU 1/240V AC/24V DC

### Technical Data

---

#### Input data

---

Input voltage	230 VAC
Drop-out voltage	44 VAC
Control current	3 mA
Number of channels	1
Operating range	184-264 VAC
Power consumption	0,9 W

#### Output data

---

Output voltage range	1,5-24 VDC V
Voltage drop at 20 °C and rated current, max.	0,12 V
Switching current, min.	0,001 A
Continuous current max. / Inrush current max.	2 / 40 A
Residual current at 55 °C, max.	0,001 mA

#### Materials

---

Working temperature, min.	-20 °C
Working temperature, max.	55 °C

**15532.2**

**PSCU 1/240V AC/24V DC**

**PSCU 1/240V AC/24V DC**

## Technical Data

---

### Further technical data

---

Status display	✓
Response/release time	0,1 / 0,6 ms
Test voltage	2.5 kV

---

15532.2

PSCU 1/240V AC/24V DC

PSCU 1/240V AC/24V DC

## Media

---

