

16407.2 GSM-PRO2E GSM-PRO2E



Compact signaling system for mobile networks to monitor analog and digital values as well as remotely switch relay outputs, Mounting type: Mounting rail TS 35, Supply voltage range: 10 - 30 VDC.

Business data

Product description	Controller module
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	195
Weight per piece (including packaging)	230
Unit of weight	G
Customs number	85176990
Country of origin	EEC

16407.2

GSM-PRO2E

GSM-PRO2E

Technical Data

Dimensions

Length	95 mm
Width	88 mm
Height	65 mm

Connection data

Connection principle	Screw connection
Number of outputs	4
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Stripping length	6 mm
Torque	0.4 Nm

16407.2 GSM-PRO2E GSM-PRO2E

Technical Data

Input data

Number of channels	10
Input signal U/I, max.	30 V / -
Input resistance U/I	80K / 500 Ohm
Resolution U (0 ... 10 Vdc)	20mV / $\pm(20\text{mV}+0,3\%)$
Resolution I (0 ... 20 mA)	40 μA / $\pm(40\ \mu + 0,3\%)$
Pulse length, min.	500 ms
Threshold digital inputs	Low <2, High >4V
Counter input (pull-down)	1000 pulses/s, max. pull-down res. 24 kOhm

Output data

Switching voltage / switching voltage max.	250 / 250 VAC
Continuous current max. / Inrush current max.	5 / 5 A
Contact material	AgNi 90/10
Switching capacity, max.	1200 VA
Switching frequency, max.	6/min kHz
Electrical lifespan (AC1)	1,5x10 ⁶
Mechanical lifespan	15x10 ⁶
Relay contact	1CO

16407.2

GSM-PRO2E

GSM-PRO2E

Technical Data

GSM data

SIM card	Nano SIM
2G	Quad-band GSM bands
3G	Five-band UMTS (WCDMA/FDD) bands
Antenna GSM	50 ohm, SMA plug

Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C
Relative humidity, max.	80 (non-condensing) %

16407.2 GSM-PRO2E GSM-PRO2E

Technical Data

Further technical data

Power supply	10-30 VDC
Current consumption	275 @ 24 VDC mA
Protection class	IP20
Storage temperature, min.	-20 °C
Storage temperature, max.	70 °C
Mounting	Mounting rail TS35 / direct mount
Backup power	Interner wartungsfreier Supercap-Kondensator
Electromagnetic properties	Directive 2014/30/EC in compliance with EN 55011 and EN 61326-1
Frequency spectrum	RED 2014/53/EC in compliance with ETSI EN 301-511 V9.0.2 Hz
Number of expansion modules, max.	15

16407.2

GSM-PRO2E

GSM-PRO2E

Approvals

Standards and regulations

Standards / specifications

Low-Voltage Directive (LVD) 2014/35/EC, in compliance with EN 50178. EMC Directive 2014/30/EC, in compliance with EN 61326-1

16407.2

GSM-PRO2E

GSM-PRO2E

Media



16407.2 GSM-PRO2E GSM-PRO2E

Accessories

GSM-PRO I/O-Module



GSM-PRO I/O analogue input module, 8 analogue inputs 0 - 10 V, 0 (4) - 0 mA, NTC, RTD (PT1000 / NI1000), Mounting type: Mounting rail TS 35, Supply voltage range: 20 - 28 VDC

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16377.2	GSM-PRO-8AI	4044211207779	1 PC



GSM-PRO I/O digital input module, 10 digital inputs 24V with LED display, Mounting type: Mounting rail TS 35, Supply voltage range: 20 V - 28 VDC

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16375.2	GSM-PRO-10DI	4044211207755	1 PC

16407.2 GSM-PRO2E GSM-PRO2E

Accessories

GSM-PRO I/O-Module



GSM-PRO I/O analogue output module, 4 analogue outputs 0 - 10V, Mounting type: Mounting rail TS 35, Supply voltage range: 20 V - 28 VDC

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16376.2	GSM-PRO-4AO	4044211207762	1 PC



Signal converter for converting voltage/current signals to an analogue standard signal, Screw connection, Mounting type: Mounting rail TS 35, Supply voltage: 24 VDC

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16374.2	CAE/I-I/020-010	4044211207502	1 PC

16407.2 GSM-PRO2E GSM-PRO2E

Accessories

Antennen



GSM UMTS antenna with omni-directional characteristic, SMA round plug, Connecting cable length: 3 m

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16061.2	GSM-ANTENNA-EXTERNAL-SMA-3M	4044211145972	1 PC



GSM UMTS antenna with omni-directional characteristic, SMA round plug, Connecting cable length: 5 m

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16172.2	GSM-ANTENNA-EXTERNAL-SMA-5M	4044211187002	1 PC

16407.2 GSM-PRO2E GSM-PRO2E

Accessories

Antennen



GSM UMTS antenna with omni-directional characteristic, SMA round plug, Connecting cable length: 10 m

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16173.2	GSM-ANTENNA-EXTERNAL-SMA-10M	4044211187019	1 PC



GSM omni-directional antenna, 90° with SMA round connector

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16379.2	GSM-ANTENNA-90°	4044211207793	1 PC

16407.2 GSM-PRO2E GSM-PRO2E

Accessories

Anschlusskabel



USB 2.0 connection cable [1 USB 2.0 plug A - 1 USB 2.0 plug Micro-B] Cable length: 1.5 m, gold-plated plug contacts, colour: black

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
16382.2	GSM-USB-MICRO-cable	4044211207823	1 PC
