

28173.6
PVC-TAA 9X50 K GR
PVC-TAA 9X50 K GR



Device and installation marker, Length: 50 mm, Width: 9 mm, Colour: grey

Business data

Product description	Device and installation marker
Packaging unit	200
Quantity unit	PC
Number of markers per card	20
Weight per piece (not including packaging)	0.8
Weight per piece (including packaging)	0.8
Unit of weight	G
Customs number	39199080
Country of origin	IT

28173.6

PVC-TAA 9X50 K GR

PVC-TAA 9X50 K GR

Technical Data

Dimensions

Length	50 mm
Width	9 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	976

28173.6

PVC-TAA 9X50 K GR

PVC-TAA 9X50 K GR

Accessories

Printer



Thermal transfer printer

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28000.0	TTPCard	4044211207397	1 PC

Inlays



Printer inlay

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28041.0	CCI-PC/PVC/PVCF	4044211208097	1 PC