

28183.7
PVC-TAA 20X40 K WH
PVC-TAA 20X40 K WH



Device and installation marker, Length: 40 mm, Width: 20 mm, Colour: White

Business data

Product description	Device and installation marker
Packaging unit	100
Quantity unit	PC
Number of markers per card	10
Weight per piece (not including packaging)	1.86
Weight per piece (including packaging)	1.86
Unit of weight	G
Customs number	39199080
Country of origin	IT

28183.7

PVC-TAA 20X40 K WH

PVC-TAA 20X40 K WH

Technical Data

Dimensions

Length	40 mm
Width	20 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	803

28183.7

PVC-TAA 20X40 K WH

PVC-TAA 20X40 K WH

Accessories

Printer



Thermal transfer printer

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28000.0	TTPCard	4044211207397	1 PC

Inlays



Printer inlay

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
28041.0	CCI-PC/PVC/PVCF	4044211208097	1 PC