


3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Business data

Product description	Feed-through terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	3.75
Weight per piece (including packaging)	4.25
Unit of weight	G
Customs number	85369010
Country of origin	DE

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Technical Data

Dimensions

Length	40 mm
Width	5.1 mm
Height	32 mm
Height TS 15/5.5	33 mm
Pitch	5 mm

Ratings

Rated voltage	500 V
Rated current	24 A
Rated cross-section	2.5 mm ²
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Technical Data

Connection data

Connection principle	Tension-spring connection
Connection position	Top
Connections	1
Number of terminals per level	1
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.5 mm ²
Wire cross-section single core (rigid)/stranded, max.	4 mm ²
Wire cross-section stranded, min.	0.5 mm ²
Wire cross-section stranded, max.	4 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.5 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	12
Stripping length	10 mm

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Technical Data

Materials

Working temperature, max.	120 °C
---------------------------	--------

Further technical data

Mounting type	TS 15
---------------	-------

Gauge plug acc. to EN 60 947-1	A3
--------------------------------	----

End plate required	✓
--------------------	---

Number of test pick-off options	1
---------------------------------	---

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

CSA approval

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA Usegroup C: rated voltage	300 V
-------------------------------	-------

CSA Usegroup C: rated current	20 A
-------------------------------	------

CSA wire cross-section AWG, min.	20
----------------------------------	----

CSA wire cross-section AWG, max.	12
----------------------------------	----

CSA stripping length	10 mm
----------------------	-------

CSAus approval

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus Usegroup C: rated voltage	300 V
---------------------------------	-------

CSAus Usegroup C: rated current	20 A
---------------------------------	------

CSAus wire cross-section AWG, min.	20
------------------------------------	----

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Approvals

CSAus approval

CSAus wire cross-section AWG, max.	12
CSAus stripping length	10 mm

cUL Recognized

cUL Recognized	C22.2 No 158
cUL Recognized	✓
cUL Usegroup B: rated voltage	300 V
cUL Usegroup B: rated current	20 A
cUL Usegroup C: rated voltage	300 V
cUL Usegroup C: rated current	20 A
cUL Usegroup D: rated voltage	300 V
cUL Usegroup D: rated current	20 A
cUL wire cross-section single-core (rigid) AWG, min.	20
cUL wire cross-section single-core (rigid) AWG, max.	12
cUL wire cross-section stranded AWG, min.	20
cUL wire cross-section stranded AWG, max.	12
cUL wire material	Cu

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Approvals

KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-1
KEMA KEUR approval granted	✓
KEMA rated voltage	500 V
KEMA rated current	24 A
KEMA rated impulse voltage	6 kV
KEMA wire cross-section single core (rigid), min.	0.5 mm ²
KEMA wire cross-section single-core (rigid), max.	4 mm ²
KEMA wire cross-section stranded, min.	0.5 mm ²
KEMA wire cross-section stranded, max.	4 mm ²

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Approvals

UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	300 V
UL Usegroup B: rated current	20 A
UL Usegroup C: rated voltage	300 V
UL Usegroup C: rated current	20 A
UL Usegroup D: rated voltage	300 V
UL Usegroup D: rated current	20 A
UL wire cross-section single-core (rigid) AWG, min.	20
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	20
UL wire cross-section stranded AWG, max.	12
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Media



EAC



3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Accessories

End plate



End plate, Width: 0.6 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3686.2	ZAPSK 2,5/1A/1S	4044211177645	50 PC

Actuating tool



Actuating tool, No. of poles: 1, Colour: Black

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3808.0	BWMA 1 (0,5 x 3,5 mm)	4044211078850	1 PC


3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Accessories

Coding



Coding, Colour: Orange

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3689.3	ZST-C	4044211177805	50 PC

End bracket



End stop, Mounting type: Mounting rail TS 15/5.5,
Width: 5 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3812.2	ZES 15	4044211080617	50 PC


3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Accessories

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 5 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4600.7	PMC SB 5/50 WH	4044211088903	500 PC

Mechanical latch



Locking mechanism, Colour: Orange

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3687.3	ZST-V	4044211177911	50 PC

3668.2

ZSTK 2,5/1A/1S-H/Z/B/15 BG

ZSTK 2,5/1A/1S-H/Z/B/15 BG

Accessories

Fourfold-cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3706.0	ZAD 2,5/4/B	4044211060244	20 PC

ZST-strain relief



Strain relief, Colour: Orange

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3688.3	ZST-Z	4044211177928	50 PC
