


# EAO – Your Expert Partner for Human Machine Interfaces

## 14-437.036K - Keylock switch actuator 2 positions

### 14-437.036K - Keylock switch actuator 2 positions



*Attention: The preview is based on a sample product. This can differ from your current configuration.*

#### Mounting

Design	flush
Mounting cut-out	Ø 30,5 mm

#### Front

Front dimension	Ø 35 mm
Front shape	round

#### Other Attributes

Weight	0,030 kg
--------	----------

#### Operating-/Indication part

Switching angle	42° right
-----------------	-----------

#### IP-Rating

Front protection	IP65
------------------	------

#### Connection Method

Terminal	Universal 2.0 x 0.5 mm
----------	------------------------

#### Actuator

Switching action	Rest(a) - Momentary
------------------	---------------------

#### Switching element

Rotary positions	2
Switching system	Low-level element
Contacts	2 NO
Switching voltage	42 V AC/DC
Switching current	0.1 A
Contact material	


#### Function

Keylock switch
----------------

# EAO – Your Expert Partner for Human Machine Interfaces


## 14-437.036K - Keylock switch actuator 2 positions

### Dimensions



H = Universal terminal 2.0 x 0.5 mm


### Mounting cut-outs



### Wiring diagram



### Component layout



### Additional information

Lock numbers 1001, lock type KABA  
Two keys are supplied with each keylock switch.  
Optional lock numbers on request

### Legend

Contacts: NO = Normally open  
Switching action: A = Rest, B = Momentary

# EAO – Your Expert Partner for **Human Machine Interfaces**

14-437.036K - Keylock switch actuator 2 positions

## Switching positions

