






STYLE 1

PART NO.	"A" ±.03 [0.8] UNCOMPRESSED	"B" REF	HOLE DIAMETER	TOTAL BOARD THICKNESS	STYLE	TARGET LOAD
VD-2	.73 [18.5]	.62 [16.3]	.250 [6.35] ±.003 [0.08]	.07-.31 [1.8-7.9]	1	1.0 LBF [4.4N]
VD-3	.97 [24.7]	.87 [22.0]				
VD-4	1.21 [30.7]	1.10 [28.0]				
VD-5	.49 [12.4]	.38 [9.7]				
VD-6	.73 [18.5]	.62 [16.3]			2	1.6 LBF [7.1N]
VD-7	.97 [24.7]	.87 [22.0]				
VD-8	1.21 [30.7]	1.10 [28.0]				



STYLE 2



- NOTES:
 1. MOUNT MATERIAL: FLAME RETARDANT NYLON 6/6 (RMS-169).
 COLOR: NATURAL.
 2. DAMPER MATERIAL: THERMOPLASTIC ELASTOMER (RMS-167).
 HARDNESS: 35A.
 COLOR: BLACK.

C	"A" DIMS REVISED. SEE ECN #1000 FOR CHANGES	SK	05/09/05
B	SEE ECN #934 FOR CHANGES	SK	02/04/05
A	RELEASED FOR PRODUCTION	SM	12/01/04
REV.	DESCRIPTION	ENGR.	DATE

TITLE: VIBRATION DAMPER				DWG IN IN [MM]	
CREATED USING SOLIDWORKS	FILE #: VD	DWN: SM	APP: DJJ	FINAL	
TOLERANCES UNLESS NOTED XX±.010 XXX±.005 FRAC ±1/64 ANG ±1°	SHEET: 1 OF 1	SHEET SIZE: C	CHKD: SJ		
RE: RICHCO, INC.	RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		PART #	SEE TABLE	PRINT TYPE CA