

MM80C95 • MM80C97 • MM80C98

3-STATE Hex Buffers • 3-STATE Hex Inverters

General Description

The MM80C95, MM80C97 and MM80C98 gates are monolithic complementary MOS (CMOS) integrated circuits constructed with N- and P-channel enhancement mode transistors. The MM80C95 and the MM80C97 convert CMOS or TTL outputs to 3-STATE outputs with no logic inversion, the MM80C98 provides the logical opposite of the input signal. The MM80C95 has common 3-STATE controls for all six devices. The MM80C97 and the MM80C98 have two 3-STATE controls; one for two devices and one for the other four devices. Inputs are protected from damage due to static discharge by diode clamps to V_{CC} and GND.

Features

- Wide supply voltage range: 3.0V to 15V
- Guaranteed noise margin: 1.0V
- High noise immunity: 0.45 V_{CC} (typ.)
- TTL compatible: Drive 1 TTL Load

Applications

- Bus drivers: Typical propagation delay into 150 pF load is 40 ns


Ordering Code:

Order Number	Package Number	Package Description
MM80C95N	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
MM80C97M	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow
MM80C97N	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
MM80C98N	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide


Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Connection Diagrams


Pin Assignments for DIP



Top View




Top View




Top View

Schematic Diagrams


MM80C95 3-STATE



MM80C97 3-STATE



MM80C98 3-STATE



Truth Tables

MM80C95

Disable DIS ₁	Input DIS ₂	Input	Output
0	0	0	0
0	0	1	1
0	1	X	H-z
1	0	X	H-z
1	1	X	H-z

MM80C97

Disable DIS ₄	Input DIS ₂	Input	Output
0	0	0	0
0	0	1	1
X	1	X	H-z (Note 1)
1	X	X	H-z (Note 2)

MM80C98

Disable DIS ₄	Input DIS ₂	Input	Output
0	0	0	1
0	0	1	0
X	1	X	H-z (Note 1)
1	X	X	H-z (Note 2)

X = Irrelevant

Note 1: Output 5–6 only

Note 2: Output 1–4 only





Absolute Maximum Ratings (Note 3)		Power Supply Voltage (V _{CC})	18V			
Voltage at Any Pin	-0.3V to V _{CC} + 0.3V	Lead Temperature (Soldering, 10 seconds)	260°C			
Operating Temperature Range	-40°C to +85°C					
Storage Temperature Range	-65°C to +150°C					
Power Dissipation (P _D)						
Dual-In-Line	700 mW					
Small Outline	500 mW					
Note 3: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the device should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.						
DC Electrical Characteristics						
Min/Max limits apply across temperature range unless otherwise noted						
Symbol	Parameter	Conditions	Min	Typ	Max	Units
CMOS TO CMOS						
V _{IN(1)}	Logical "1" Input Voltage	V _{CC} = 5V V _{CC} = 10V	3.5 8.0			V
V _{IN(0)}	Logical "0" Input Voltage	V _{CC} = 5V V _{CC} = 10V			1.5 2.0	V
V _{OUT(1)}	Logical "1" Output Voltage	V _{CC} = 5V V _{CC} = 10V	4.5 9.0			V
V _{OUT(0)}	Logical "0" Output Voltage	V _{CC} = 5V V _{CC} = 10V			0.5 1.0	V
I _{IN(1)}	Logical "1" Input Current	V _{CC} = 15V		0.005	1.0	µA
I _{IN(0)}	Logical "0" Input Current		-1.0	-0.005		µA
I _{OZ}	Output Current in High Impedance State	V _{CC} = 15V, V _O = 15V V _{CC} = 15V, V _O = 0V		0.005 -0.005	1.0	µA
I _{CC}	Supply Current	V _{CC} = 15V		0.01	15	µA
TTL INTERFACE						
V _{IN(1)}	Logical "1" Input Voltage	V _{CC} = 4.75V	V _{CC} = 1.5			V
V _{IN(0)}	Logical "0" Input Voltage	V _{CC} = 4.75V			0.8	V
V _{OUT(1)}	Logical "1" Output Voltage	V _{CC} = 4.75V, I _O = -1.6 mA	2.4			V
V _{OUT(0)}	Logical "0" Output Voltage	V _{CC} = 4.75V, I _O = 1.6 mA			0.4	V
OUTPUT DRIVE (Short Circuit Current)						
I _{SOURCE}	Output Source Current	V _{CC} = 5V, V _{IN(1)} = 5V T _A = 25°C, V _{OUT} = 0V	-4.35			mA
I _{SOURCE}	Output Source Current	V _{CC} = 10V, V _{IN(1)} = 10V T _A = 25°C, V _{OUT} = 0V	-20			mA
I _{SINK}	Output Sink Current	V _{CC} = 5V, V _{IN(0)} = 0V T _A = 25°C, V _{OUT} = V _{CC}	4.35			mA
I _{SINK}	Output Sink Current	V _{CC} = 10V, V _{IN(0)} = 0V T _A = 25°C, V _{OUT} = V _{CC}	20			mA

AC Electrical Characteristics (Note 4) $T_A = 25^\circ\text{C}$, $C_L = 50 \text{ pF}$, unless otherwise noted.


Symbol	Parameter	Conditions	Min	Typ	Max	Units
t_{pd0}, t_{pd1}	Propagation Delay Time to a Logical "0" or Logical "1" from Data Input to Output MM80C95, MM80C97 MM80C98	$V_{CC} = 5\text{V}$		60	100	ns
		$V_{CC} = 10\text{V}$		25	40	ns
		$V_{CC} = 5\text{V}$		70	150	ns
		$V_{CC} = 10\text{V}$		35	75	ns
t_{pd0}, t_{pd1}	Propagation Delay Time to a Logical "0" or Logical "1" from Data Input to Output MM80C95, MM80C97 MM80C98	$V_{CC} = 5\text{V}, C_L = 150 \text{ pF}$		85	160	ns
		$V_{CC} = 10\text{V}, C_L = 150 \text{ pF}$		40	80	ns
		$V_{CC} = 5\text{V}, C_L = 150 \text{ pF}$		95	210	ns
		$V_{CC} = 10\text{V}, C_L = 150 \text{ pF}$		45	110	ns
t_{1H}, t_{0H}	Delay from Disable Input to High Impedance State, (from Logical "1" or Logical "0") MM80C95 MM80C97 MM80C98	$R_L = 10\text{k}, C_L = 5 \text{ pF}$				
		$V_{CC} = 5\text{V}$		80	135	ns
		$V_{CC} = 10\text{V}$		50	90	ns
		$V_{CC} = 5\text{V}$		70	125	ns
		$V_{CC} = 10\text{V}$		50	90	ns
		$V_{CC} = 5\text{V}$		90	170	ns
		$V_{CC} = 10\text{V}$		70	125	ns
t_{H1}, t_{H0}	Delay from Disable Input to Logical "1" Level (from High Impedance State) MM80C95 MM80C96 MM80C98	$R_L = 10\text{k}, C_L = 50 \text{ pF}$				
		$V_{CC} = 5\text{V}$		120	200	ns
		$V_{CC} = 10\text{V}$		50	90	ns
		$V_{CC} = 5\text{V}$		130	225	ns
		$V_{CC} = 10\text{V}$		60	110	ns
		$V_{CC} = 5\text{V}$		120	200	ns
C_{IN}	Input Capacitance	Any Input (Note 5)		5.0		pF
	C_{OUT}	Output Capacitance 3-STATE		11		pF
C_{PD}	Power Dissipation Capacitance	(Note 6)		60		pF

Note 4: AC Parameters are guaranteed by DC correlated testing.

Note 5: Capacitance is guaranteed by periodic testing.

Note 6: C_{PD} determines the no load AC power consumption of any CMOS device. For complete explanation see Family Characteristics application note AN-90.**AC Test Circuits and Switching Time Waveforms**


AC Test Circuits and Switching Time Waveforms (Continued)




Note: Delays measured with input t_r , $t_f \leq 20$ ns.

Typical Performance Characteristics


Propagation Delay vs Load Capacitance




$\Delta t_{pd}/pF$ vs Power Supply Voltage




N-Channel Output Drive at 25°C




P-Channel Output Drive at 25°C



Physical Dimensions inches (millimeters) unless otherwise noted

16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow
Package Number M16A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
Package Number N16E

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com