

NOTE:

1. FOR VISUAL, MECHANICAL, AND FUNCTIONAL, REQUIREMENTS SEE PRODUCT SPEC. 110-015.
2. HOUSING MAT'L: GLASS REINFORCED NYLON 66 ZYTEL-FR50, UL 94 V-0.
3. GOLD WIRE MAT'L: PHOSPHOR BRONZE 0.46 DIA.
4. A. STANDARD PACKAGING METHOD(USE TRAY): SEE GS-14-351.
B. NON-STANDARD PACKAGING METHOD(USE TUBE): SEE GS-14-358.

THE PART NO. SHOULD BE SUFFIXED WITH "T" OR "TLF".

(E.G.67968-001T OR 67968-001TLF)

5. MATALE PLUG: PLUG CONFORMED TO FCC TYPE 623.
6. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
7. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm MINIMUM THICK CIRCUIT BOARD.
8. IF LF P/N PACKAGING MEETS GS-14-920 SPECIFICATION.