

HF 4 channel Multiplexer ID ISC.ANT.MUX.M4



Features

- Communication between reader and Multiplexer via antenna cable
- Multiplexer outputs are controlled by the reader or the host system
- Non-wearing electronic switching of the outputs
- High switching speed (< 1ms)
- Also available: 8 channel Multiplexers



Description

The 4 channel Multiplexer Module ID ISC.ANT.MUX-M4 facilitates switching between RFID antennas with an operating frequency of 13.56 MHz. With one Multiplexer several single antennas and gate solutions can be operated with only one reader.

The Multiplexer is controlled via the antenna cable connected with the reader. An additional connection to the Multiplexer is not necessary which guarantees an easy installation.

The advanced communication between the reader and multiplexer allows direct switching to any output.

Additionally, FEIG ELECTRONIC offers an 8 channel Multiplexer Module and an 8 channel Multiplexer with housing.

Order descriptions:

ID ISC.ANT.MUX	HF Multiplexer (8 channels)
ID ISC.ANT.MUX.M8	HF Multiplexer Module (8 channels)
ID ISC.ANT.MUX.M4	HF Multiplexer Module (4 channels)

FEIG ELECTRONIC reserves the right to change specification without notice at any time.
Stand of information: November 2016



FEIG ELECTRONIC GmbH · Lange Straße 4 · D-35781 Weilburg
Tel.: +49 6471 3109-0 · Fax: -99 · E-Mail: OBID@feig.de · www.feig.de

Technical Data

Dimensions (W x H x D)	137mm x 77 mm x 15 mm (5.39 inch x 3.03 inch x 0.59 inch)
Weight	approx. 80 g
Operating frequency	13.56 MHz
Supply voltage	12 – 24 V DC
Power consumption	max. 4.0 W
Attenuation per channel	max. 0,5 dB
Max. permissible switching power	8 W
RF connections	
1 x input	SMA jack (50Ω)*
4 x output	SMA jack (50Ω)*
RF switches	electronic switches (non-wearing); switching speed < 1ms
Triggering	
Reader	communication via RF input 1
Signal indicator	1 x LED per channel 3 x LED (Run / HF / Communication)
Temperature range	
Operation	-25°C to 65°C (-13°F to +149°F)
Storage	-40°C to 80°C (-40°F to +176°F)

*Maximum tightening torque: 0.45 Nm (4.0 lbf in)

STANDARD CONFORMITY

EMC	EN 61000-6-3 EN 61000-6-2
Vibration	EN 60068-2-6 10 Hz to 150 Hz; 0.075 mm / 1g
Shock	EN 60068-2-27 Acceleration: 30g

FEIG ELECTRONIC reserves the right to change specification without notice at any time.
Stand of information: November 2016