

Specification Sheet

Part Number: 109-00101



Q Tie, 9.8" Long, 30lb Tensile Strength, PA66HS, Black, 100/pkg

Article Number	109-00101
Type	Q30LR
Color	Black (BK)
Features & Benefits	• PA66HS cable ties are heat stabilized for excellent heat resistance. • Open-head design with easily detectable slot opening allows for fast and easy insertion. • Pre-lock feature allows for a temporary hold while preparing bundle. • Large ribbed tail ensures simple, ergonomic installation.
Quantity Per	bag

Product Description	Q-Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head provides ease of placement when working with gloves or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q-Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.
Short Description	Q Tie, 9.8" Long, 30lb Tensile Strength, PA66HS, Black, 100/pkg
Global Part Name	Q30LR-PA66HS-BK
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	130
Length L (Imperial)	9.8
Length L (Metric)	250
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6

Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	3.0
Bundle Diameter Max (Imperial)	2.6
Bundle Diameter Max (Metric)	65.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100

Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.