


Specification Sheet

Part Number: 151-01422



Ratchet P-Clamp, 0.24" - 0.54" Bundle Dia, 180° Long, .33" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 200/ctn

| | |
|---------------------|---|
| Article Number | 151-01422 |
| Type | RCA180LM8 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• One-piece ratchet closure allows for easy installation during pre- or final assembly.• Easy release feature simplifies quick adjustments and maintenance.• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.• Zinc-plated steel mounting plate tolerates high torque and is treated to resist chemicals and salt spray.• Straight, 180° mounting plate is ideal for applications requiring a flush mount set off from the mounting hole. |
| Quantity Per | carton |

| | |
|--|--|
| Product Description | The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. |
| Short Description | Ratchet P-Clamp, 0.24" - 0.54" Bundle Dia, 180° Long, .33" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 200/ctn |
| Global Part Name | RCA180LM8-PA66HIRHSUV/ST/ZN-BK |
| Minimum Tensile Strength (Imperial) | 100.0 |
| Minimum Tensile Strength (Metric) | 445.0 |
| Length L (Imperial) | 6.58 |
| Length L (Metric) | 167.2 |
| Fixation Method | Screw Mounting |
| Variant | Long |
| Width W (Imperial) | 1.37 |
| Width W (Metric) | 34.9 |
| Bundle Diameter Min (Imperial) | 0.24 |
| Bundle Diameter Min (Metric) | 6.2 |

| | |
|--|--|
| Bundle Diameter Max (Imperial) | 0.54 |
| Bundle Diameter Max (Metric) | 13.7 |
| Cable Tie Width Max (Imperial) | 0.52 |
| Cable Tie Width Max (Metric) | 13.2 |
| Mounting Hole Diameter D (Imperial) | 0.327 |
| Mounting Hole Diameter D (Metric) | 8.31 mm |
| Mounting Hole Diameter D Max (Metric) | 8.31 |
| Stud Diameter (Metric) | M8 |
| Mounting Hole Centers (Imperial) | 3.99 |
| Material | Zinc plated (ZN) Steel (ST) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV ST ZN |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| Reach Complaint(Article 33) | Yes |

| | |
|-----------------------|-----|
| ROHS Complaint | Yes |
|-----------------------|-----|

| | |
|----------------------------------|-----|
| UL Listed (US and Canada) | Yes |
|----------------------------------|-----|

| | |
|----------------------|-----|
| UL Listed (US | Yes |
|----------------------|-----|

| | |
|-----------------------------------|-----|
| Package Quantity(Imperial) | 200 |
|-----------------------------------|-----|

| | |
|----------------------------------|-----|
| Package Quantity (Metric) | 200 |
|----------------------------------|-----|

| | |
|-----------------------|------------|
| Customs Number | 3926909988 |
|-----------------------|------------|

| | |
|-----------------------------|------|
| Content Unit(BMEcat) | pcs. |
|-----------------------------|------|