

Specification Sheet

Part Number: 155-32602



Connector Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg

Article Number	155-32602
Type	FT6LG.M.St.Aufn.II
Color	Black (BK)
Features & Benefits	• Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
Quantity Per	bag

Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	Connector Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg
Global Part Name	FT6LG.M.St.Aufn.II-PA66HIRHS-BK
Length L (Imperial)	1.06
Length L (Metric)	27
Fixation Method	Fir Tree
Width W (Imperial)	0.63
Width W (Metric)	16
Height H (Imperial)	0.68
Height H (Metric)	17.3
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.2
Panel Thickness Min (Metric)	0.75
Panel Thickness Max (Metric)	1.5

Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.26
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	16
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500

Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.8