

Specification Sheet

Part Number: 156-01877



LOC Locking Clamp, 15-19 mm, to MOC Clip, 6 mm, PA66HIRHSUV, Black, 1000/ctn

Article Number	156-01877
Type	MOC6LOC15-19
Color	Black (BK)
Features & Benefits	• Patented retention design of clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement. • Clip and clamp both offer easy bundle installation. • Independent rotation allows for adjustable routing orientation. • Locking clamp dynamically fits a range of bundle sizes.
Quantity Per	carton
Product Description	The MOC to LOC is a rotatable dual routing clip and clamp combination that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

Short Description	LOC Locking Clamp, 15-19 mm, to MOC Clip, 6 mm, PA66HIRHSUV, Black, 1000/ctn
Global Part Name	MOC6LOC15-19-PA66HIRHSUV-BK
Length L (Imperial)	1.62
Length L (Metric)	41.10
Variant	Clip to Clamp
Bundle Diameter Min (Imperial)	0.22
Bundle Diameter Min (Metric)	5.5
Bundle Diameter Max (Imperial)	0.27
Bundle Diameter Max (Metric)	6.8
Height H (Imperial)	1.31
Height H (Metric)	33.4
Depth D (imperial)	0.47
Depth D (metric)	12.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988
Weight (Metric)	3.81
Weight (Imperial)	0.13