

157-00118



Article Number: 157-00118

Offset Fir Tree, 12.5 mm, M6, 8" Tie, 50lb Tensile Strength, PA66HIRHS, Gray, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00118

Type T50ROSFTM6SO12.5A

Color Gray (GY)

- Features and Benefits**
- One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.8mm to 7.0mm or threaded blind holes.
 - The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.
 - The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Product Description HellermannTyton's offset fir tree cable tie family creates an offset routing solution for our customers who are moving away from using tape. The offset branch creates a strong offset that reduces flexing and shifting of the bundle.

Short Description Offset Fir Tree, 12.5 mm, M6, 8" Tie, 50lb Tensile Strength, PA66HIRHS, Gray, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 222.0 N

Length L (Imperial) 8.4 "

Length L (Metric) 215.5 mm

Fixation Method Fir Tree

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.96 "

Bundle Diameter Max. (Metric) 50.0 mm

Panel Thickness Max. (Imperial) 0.2 "

Panel Thickness Max. (Metric) 5.5 mm

Panel Thickness Min. (Imperial) 0.02 "

Panel Thickness Min. (Metric) 0.6 mm

Mounting Hole Diameter D (Imperial) M6 Threaded "

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
ROHS Compliant	Yes