

Specification Sheet

Part Number: 170-03136



Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 400 ft/bulk reel

Article Number	170-03136
Type	BSPSW100LB
Color	Black (BK)
Features & Benefits	• Center-slit overlapping design allows quick and easy access to the wires and cables for future maintenance or inspection without disassembly. • Flexible material allows it to easily wrap around a variety of component shapes and sizes, making it easier to use than slit-loom tubing or spiral-wrap materials. • A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris. • Overlapping design enhances flexibility, allowing it to shift and bend without exposing wire and cables.
Quantity Per	reel

Product Description	A lateral split semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
Short Description	Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 400 ft/bulk reel
Global Part Name	BSPSW100LB-PET-BK
Length L (Imperial)	400.0
Length L (Metric)	121.9
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.0
Bundle Diameter Max (Metric)	25.4
Diameter D (imperial)	1.0
Diameter D (metric)	25.4
Nominal Diameter (Imperial)	1
Nominal Diameter (Metric)	25.4
Wall Thickness WT (Imperial)	0.038

Wall Thickness WT (Metric)	0.97
Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL 94 V0
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	400
Package Quantity (Metric)	121.92
Customs Number	5808100000
Weight (Metric)	3.6
Weight (Imperial)	8.0

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)