

Specification Sheet

Part Number: 170-03154



Braided Sleeving, Hook & Loop, Flame Retardant, 0.75" Dia, PET, Black, 100 ft/bulk reel

Article Number	170-03154
Type	BSHKLPFR340B
Color	Black (BK)
Features & Benefits	• Flexible construction that conforms to irregular shapes and contours. • Hook and loop feature wraps over cable bundle allowing future access to cables. • Easy access saves assembly time and allows for easy splicing or insertion of additional wires. • Meets military specifications (Mil-202 approved.) • Cuts easily with a benchmount hot knife. • Resists chemicals and cleaning solvents.
Quantity Per	reel

Product Description	Flame retardant expandable braided sleeving with hook and loop strip for wrapping around cable assemblies. Color matched hook and loop closure provides an easy on and off installation, as well as convenient access for harness break-outs and when maintenance is necessary. Material is self-extinguishing and complies with UL VW-1 standards.
Short Description	Braided Sleeving, Hook & Loop, Flame Retardant, 0.75" Dia, PET, Black, 100 ft/bulk reel
Global Part Name	BSHKLPFR340B-PET-BK
Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.75
Bundle Diameter Max (Metric)	19.1
Diameter D (imperial)	0.75
Diameter D (metric)	19.1
Nominal Diameter (Imperial)	0.75
Nominal Diameter (Metric)	19.1
Wall Thickness WT (Imperial)	0.025

Wall Thickness WT (Metric)	0.635
Material	Polyester (PET)
Material Shortcut	PET
US MIL SPEC	MIL-STD-202
Flammability	UL VW-1
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	MIL-STD 202 UL
UL Recognized (US)	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	5808100000

Weight (Metric) 0.82

Weight (Imperial) 1.8