

Specification Sheet

Part Number: 170-03190



Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 0.25" Dia, AL/GF, Silver, 50/box

Article Number	170-03190
-----------------------	-----------

Type	BSHTTSW14SB
-------------	-------------

Color	Silver (SR)
--------------	-------------

Features & Benefits	• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application.
--------------------------------	--

Quantity Per	box
---------------------	-----

Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. Sold in 4-foot sticks.
----------------------------	---

Short Description	Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 0.25" Dia, AL/GF, Silver, 50/box
Global Part Name	BSHTTSW14SB-GF-AL-SR
Length L (Imperial)	4.0
Length L (Metric)	1.22
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.20
Bundle Diameter Max (Metric)	5.1
Diameter D (imperial)	0.25
Diameter D (metric)	6.35
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.35
Wall Thickness WT (Imperial)	0.042
Wall Thickness WT (Metric)	1.06

Material	Glass fiber with aluminium foil (GF-AL)
Material Shortcut	GF-AL
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	7019905050