

Specification Sheet

Part Number: 181-11502



Solid Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, White, 120ft/Carton

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 181-11502                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Type                | SD1X1.5                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Features & Benefits | <ul style="list-style-type: none"><li>• Solid wall construction provides excellent coverage to keep wires clean.</li><li>• Durable material protects wires from damage, with long-lasting performance.</li><li>• Available standard colors complement or contrast in light and dark environments.</li><li>• Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.</li></ul> |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                                         |                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>              | HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6-foot lengths. |
| <b>Short Description</b>                | Solid Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, White, 120ft/Carton                                                                                                                                                                                                                                                                                  |
| <b>Global Part Name</b>                 | SD1X1.5-PVC-WH                                                                                                                                                                                                                                                                                                                                             |
| <b>Technical Description</b>            | Non-Adhesive                                                                                                                                                                                                                                                                                                                                               |
| <b>Length L (Imperial)</b>              | 6.0                                                                                                                                                                                                                                                                                                                                                        |
| <b>Length L (Metric)</b>                | 1.83                                                                                                                                                                                                                                                                                                                                                       |
| <b>Width W (Imperial)</b>               | 1.0                                                                                                                                                                                                                                                                                                                                                        |
| <b>Width W (Metric)</b>                 | 25.4                                                                                                                                                                                                                                                                                                                                                       |
| <b>Height H (Imperial)</b>              | 1.57                                                                                                                                                                                                                                                                                                                                                       |
| <b>Height H (Metric)</b>                | 39.9                                                                                                                                                                                                                                                                                                                                                       |
| <b>Mounting Hole Centers (Imperial)</b> | 4.0                                                                                                                                                                                                                                                                                                                                                        |
| <b>Material</b>                         | Polyvinylchloride (PVC)                                                                                                                                                                                                                                                                                                                                    |
| <b>Material Shortcut</b>                | PVC                                                                                                                                                                                                                                                                                                                                                        |

|                                        |                                                  |
|----------------------------------------|--------------------------------------------------|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No                                               |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No                                               |
| <b>ROHS Complaint</b>                  | Yes                                              |
| <b>Certification/Specification WEB</b> | CSA EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes                                              |
| <b>Package Quantity(Imperial)</b>      | 120                                              |
| <b>Package Quantity (Metric)</b>       | 36.58                                            |
| <b>Customs Number</b>                  | 3925900000                                       |