HellermannTyton

Specification Sheet

Part Number: 181-13007



Slotted Wall Wiring Duct, 1" x 3", Non-Adhesive, PVC, White, 30ft/Box

Article Number 181-13007

Type SL1X3

Color White (WH)

Features & Benefits

• Strong fingers prevent unwanted breaking. • Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. • Restricted opening design in the finger of the duct helps keep wires in place. • Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection. • Supplied with mounting holes to streamline installation. • Optional covers enhance protection and appearance.

Quantity Per box

Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and Ts.
Short Description	Slotted Wall Wiring Duct, 1" x 3", Non-Adhesive, PVC, White, 30ft/Box
Global Part Name	SL1X3-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	3.07
Height H (Metric)	77.9

MaterialPolyvinylchloride (PVC)

4.0

Material Shortcut PVC

Mounting Hole Centers (Imperial)

Flammability Self-Extinguishing

Halogen free No

Operating Temperature (Metric) +122°F (+50°C)

Reach Complaint(Article 33) No

ROHS Complaint Yes

Certification/Specification WEB EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A CSA UL

UL Recognized (US) Yes

Package Quantity(Imperial) 30

Package Quantity (Metric) 9.14

Customs Number 3925900000

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions