## **HellermannTyton**

## **Specification Sheet**

Part Number: 181-34002



Slotted Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Black, 120ft/Carton

| Article Number      | 181-34002  |
|---------------------|--|
| Туре                | SL3X4  |
| Color               | Black (BK)   |
| Features & Benefits | • Strong fingers prevent unwanted breaking. • Fingers are easily<br>deflected outward, allowing ready positioning of the wires within the<br>slotted wall duct. • Restricted opening design in the finger of the duct<br>helps keep wires in place. • Restricted opening prevents unintended<br>removal of wires and permits any individual wire to be traced without<br>disconnection. • Supplied with mounting holes to streamline<br>installation. • Optional covers enhance protection and appearance. |
| Quantity Per        | carton   |

| Product Description              | Pro-Duct slotted wall wiring duct features break-away fingers which<br>provide additional access for wire leads. Each section of the duct is<br>provided with two score lines. The upper score line is used to break<br>away fingers when a greater opening is required. The lower score line<br>allows the sidewall to be smoothly cut for joints and Ts. |
|----------------------------------|--|
| Short Description                | Slotted Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Black, 120ft/Carton  |
| Global Part Name                 | SL3X4-PVC-BK   |
| Technical Description            | Non-Adhesive   |
|                                  |  |
| Length L (Imperial)              | 6.0  |
| Length L (Metric)                | 1.83   |
| Width W (Imperial)               | 3.0  |
| Width W (Metric)                 | 76.2   |
| Height H (Imperial)              | 4.07   |
| Height H (Metric)                | 103.4  |
| Mounting Hole Centers (Imperial) | 4.0  |

Material

Polyvinylchloride (PVC)

| Flammability                    | Self-Extinguishing                               |  |  |
|---------------------------------|--|--|--|
| Halogen free                    | No   |  |  |
| Operating Temperature (Metric)  | +122°F (+50°C)                                   |  |  |
| Reach Complaint(Article 33)     | No   |  |  |
| ROHS Complaint                  | Yes  |  |  |
| Certification/Specification WEB | CSA UL EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 |  |  |
| UL Recognized (US)              | Yes  |  |  |
|                                 |  |  |  |
| Package Quantity(Imperial)      | 120  |  |  |
| Package Quantity (Metric)       | 36.58  |  |  |
| Customs Number                  | 3925900000                                       |  |  |
|                                 |  |  |  |

| © 2020 HellermannTyton. All Rights Reserved. |                             |            |                      |  |  |  |
|--|-----------------------------|------------|----------------------|--|--|--|
| Contact Us                                   | <b>RoHS/WEEE</b> Compliance | Disclaimer | Terms and Conditions |  |  |  |