HellermannTyton

Specification Sheet

Part Number: 184-11002



High Density Slotted Wall Wiring Duct, 1" x 1", Adhesive, PVC, White, 30ft/Box

Article Number 184-11002

SLHDA1X1 **Type**

Color White (WH)

Features & Benefits

• Narrow fingers reduce fanning of wires to terminal blocks, providing a neater appearance. • Each finger features a double restriction to hold wires in the bottom portion of the duct, simplifying installation. • Mounting holes are uniform in size to those in slotted and solid wall duct but are provided every two inches to accommodate compact designs and provide ease of installation. • Nonpermanent adhesive allows repositioning prior to final installation.

Quantity Per box

Product Description	HellermannTyton High Density Slotted Wall Duct features narrow breakaway fingers, designed at a 2-to-1 ratio compared to standard slotted duct, providing additional access for wire leads. Narrower fingers better accommodate compact designs and components. Pressure-sensitive, rubber-based adhesive backing aids in temporary positioning.
Short Description	High Density Slotted Wall Wiring Duct, 1" x 1", Adhesive, PVC, White, 30ft/Box
Global Part Name	SLHDA1X1-PVC-WH
Technical Description	Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	1.06
Height H (Metric)	26.9
Mounting Hole Centers (Imperial)	2.0

Material

Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability Self-Extinguishing

Halogen free No

Operating Temperature (Metric) +122°F (+50°C)

Reach Complaint(Article 33) No

ROHS Complaint Yes

Certification/Specification WEB EN 50085-2-3_1A CSA UL EN 50085-1:2005 + A1:2013

UL Recognized (US) Yes

Package Quantity(Imperial) 30

Package Quantity (Metric) 9.14

Customs Number 3925900000