HellermannTyton

Specification Sheet

Part Number: 184-11011



High Density Slotted Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, White, 30ft/Box

Article Number	184-11011
Туре	SLHD1X1.5
Color	White (WH)
Features & Benefits	• Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. • Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. • Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation. • Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

Product Description	Pro-Duct high-density slotted-wall wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
Short Description	High Density Slotted Wall Wiring Duct, 1" x 1.5", Non-Adhesive, PVC, White, 30ft/Box
Global Part Name	SLHD1X1.5-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	1.57
Height H (Metric)	39.9
Mounting Hole Centers (Imperial)	2.0

Material

Polyvinylchloride (PVC)

Material Shortcut

Flammability	Self-Extinguishing		
Halogen free	No		
Operating Temperature (Metric)	+122°F (+50°C)		
Reach Complaint(Article 33)	No		
ROHS Complaint	Yes		
Certification/Specification WEB	EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013		
UL Recognized (US)	Yes		
Package Quantity(Imperial)	30		
Package Quantity (Metric)	9.14		
Customs Number	3925900000		

© 2020 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions