

Specification Sheet

Part Number: 184-14004



High Density Slotted Wall Wiring Duct, 1" x 4", Non-Adhesive, PVC, White, 120ft/Carton

|                     |   |
|---------------------|---|
| Article Number      | 184-14004   |
| Type                | SLHD1X4   |
| Color               | White (WH)  |
| Features & Benefits | <ul style="list-style-type: none"><li>• Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li><li>• Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li><li>• Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.</li><li>• Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.</li></ul> |
| Quantity Per        | carton  |

|   |   |
|---|---|
| <b>Product Description</b>              | Pro-Duct high density, slotted wall wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| <b>Short Description</b>                | High Density Slotted Wall Wiring Duct, 1" x 4", Non-Adhesive, PVC, White, 120ft/Carton  |
| <b>Global Part Name</b>                 | SLHD1X4-PVC-WH  |
| <b>Technical Description</b>            | Non-Adhesive  |
| <b>Length L (Imperial)</b>              | 6.0   |
| <b>Length L (Metric)</b>                | 1.83  |
| <b>Width W (Imperial)</b>               | 1.0   |
| <b>Width W (Metric)</b>                 | 25.4  |
| <b>Height H (Imperial)</b>              | 4.07  |
| <b>Height H (Metric)</b>                | 103.4   |
| <b>Mounting Hole Centers (Imperial)</b> | 2.0   |
| <b>Material</b>                         | Polyvinylchloride (PVC)   |
| <b>Material Shortcut</b>                | PVC   |

|  |  |
|--|--|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No   |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No   |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | UL EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 CSA |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 120  |
| <b>Package Quantity (Metric)</b>       | 36.58  |
| <b>Customs Number</b>                  | 3925900000                                       |