

Specification Sheet

Part Number: 596-00242



Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", V, Clear, 50/roll

Article Number	596-00242
Type	LAM1
Color	Clear (CL)
Features & Benefits	<ul style="list-style-type: none"><li>• Made with UV stable inks and materials for durability and weather resistance.</li><li>• The labels are supplied with aggressive adhesive to ensure long life.</li><li>• Solar Installation labels meet NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul>
Quantity Per	roll

<b>Product Description</b>	HellermannTyton printable Solar Installation labels are designed to meet the requirements of the 2014 and 2017 National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
<b>Short Description</b>	Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", V, Clear, 50/roll
<b>Global Part Name</b>	LAM1-443/281-CL
<b>Technical Description</b>	Clear Laminate Label, UV stable, 4.2" X 2.25", Clear
<b>Local Order Number 2</b>	Cross Reference = 10 per pack: 596-00670
<b>Width W (Imperial)</b>	4.2
<b>Width W (Metric)</b>	106.6
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.25
<b>Height H (Metric)</b>	57.10
<b>Material</b>	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)

<b>Material Shortcut</b>	443/281
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +174°F (-40°C to +79°C)
<b>Operating Temperature (Metric)</b>	-40°F to +174°F (-40°C to +79°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL 969 NEC2011 IFC 2012
<b>Warranty (US)</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919102055
<b>Content Unit(BMEcat)</b>	pcs.
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1

<b>Weight (Metric)</b>	0.521
------------------------	-------

<b>Weight (Imperial)</b>	3.2
--------------------------	-----