HellermannTyton

Specification Sheet

Part Number: 596-00251

Solar Circuit Marker, CAUTION: SOLAR CIRCUIT, 7.25" x 5", V, Red, 25/pkg

Article Number	596-00251
Type	CSCSNAP72R
Color	Red (RD)
Features & Benefits	• Pre-printed solar labels are made using high performance UV stable materials and adhesives for long outdoor life. • Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection. • Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes. • The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.

Quantity Per	pack
Product Description	These photovoltaic caution and power source markers are preprinted, non-adhesive, coiled markers that can be opened and snapped over cables for long-term, reflective, permanent identification. Made of a UV stable vinyl, the coiled markers come 25 per bag and will fit on all standard PV cables or electrical metallic tubing (EMT) conduits.
Short Description	Solar Circuit Marker, CAUTION: SOLAR CIRCUIT, 7.25" x 5", V, Red, 25/pkg
Global Part Name	CSCSNAP72R-V-RD
Technical Description	Pre-Printed Solar Marker, Reflective, Non-Adhesive, Coiled, "CAUTION: SOLAR CIRCUIT", 7.25" X 5", Red
Width W (Imperial)	7.25
Width W (Metric)	184.15
Height H (Imperial)	5.0
Height H (Metric)	127.0
Material	Vinyl
Material Shortcut	V
Halogen free	No

Operating Temperature (Metric)	-18°F to +200°F (-29°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969 NEC2011 IFC 2012 NEC2017 NEC2014
Package Quantity(Imperial)	25
Package Quantity (Metric)	25
Customs Number	3919905060
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.074
Weight (Imperial)	0.16