Specification Sheet

Part Number: 596-00372

SAFETY

Pre-Printed Header Label, SAFETY, 3.0" x 2.0", PET, Green, 250/roll

Article Number	596-00372
Type	3X2SAFETY
Color	Green (GN)
Features & Benefits	• Pre-printed solar labels are made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Pre-Printed Header Label, SAFETY, 3.0" x 2.0", PET, Green, 250/roll

Global Part Name

3X2SAFETY-336/926-GN

Technical Description

Pre-Printed Header Label, SAFETY, 3" X 2", Green

Width W (Imperial)

3.0

Width W (Metric)

76.2

Thickness T (Metric)

64.0

Height H (Imperial)

2.0

Height H (Metric)

50.4

Width of Liner (Metric)

81.2

Width of Liner (imperial)

3.2

Material	Type 336/926, Polyester, UV-stabilized, clear polyester laminate (336/926)
Material Shortcut	336/926
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	250
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521

Weight (Imperial)   3.2

Contact Us   RoHS/WEEE Compliance   Disclaimer   Terms and Conditions