

## Specification Sheet

Part Number: 596-00498



Solar Label, WARNING GROUNDED CONDUCTORS ENERGIZED..., 4.125" x 2.0", V, Orange/White, 50/roll

**Article Number** 596-00498

**Type** WGCME

**Color** Orange (OG)

**Features & Benefits**

- Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.
- Supplied with an aggressive adhesive to ensure long life.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
- Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

**Quantity Per** roll

<b>Product Description</b>	HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
<b>Short Description</b>	Solar Label, WARNING GROUNDED CONDUCTORS ENERGIZED..., 4.125" x 2.0", V, Orange/White, 50/roll
<b>Global Part Name</b>	WGCME-443/281-OG
<b>Technical Description</b>	Pre-Printed Solar Label, "WARNING- GROUNDED CONDUCTORS ENERGIZED...", 4.125" X 2.0", Orange/White
<b>Local Order Number 2</b>	Cross Reference = 10 per pack: 596-00663; Metal Solar Placard 5 pack: 596-00830
<b>Length L (Imperial)</b>	2.0
<b>Length L (Metric)</b>	50.8
<b>Width W (Imperial)</b>	4.125
<b>Width W (Metric)</b>	104.6
<b>Thickness T (Imperial)</b>	0.0025
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.0

<b>Height H (Metric)</b>	50.8
<b>Material</b>	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)
<b>Material Shortcut</b>	443/281
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +174°F (-40°C to +79°C)
<b>Operating Temperature (Metric)</b>	-40°F to +174°F (-40°C to +79°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL 969 NEC2014
<b>Warranty (US)</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50

**Customs Number** 3919102055

**Content Unit(BMEcat)** pcs.

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.521

**Weight (Imperial)** 1.12