

Specification Sheet

Part Number: 596-00652



Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 596-00652                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Type                | PVACDIS-1                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Color               | Red (RD)                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Features & Benefits | <ul style="list-style-type: none"><li>• Made with UV-stable inks and materials for durability and weather resistance.</li><li>• Reflective properties to meet applicable NEC code requirements for reflective identification.</li><li>• Supplied with an aggressive adhesive to ensure long life.</li><li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul> |
| Quantity Per        | roll                                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>   | Designed in a one-across landscape format to fit into the compact TT130SMC thermal transfer printer, these labels allow for code-compliant marking of variable information including disconnecting means, breaker series and voltage data. Made with cross-laminated UV stable materials, labels are ideal for use in solar installation applications. Use with the TT130SMC or any HellermannTyton thermal transfer printer. |
| <b>Short Description</b>     | Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll                                                                                                                                                                                                                                                                                                                                           |
| <b>Global Part Name</b>      | PVACDIS-1-840/281-RD                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Technical Description</b> | Printable Solar Label, PV AC RATING LABEL, 1.0" X 3.75", Red                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Width W (Imperial)</b>    | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Width W (Metric)</b>      | 25.4                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Thickness T (Metric)</b>  | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Height H (Imperial)</b>   | 3.75                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Height H (Metric)</b>     | 95.25                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Material</b>              | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)                                                                                                                                                                                                                                                                                                                                                    |
| <b>Material Shortcut</b>     | 840/281                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Adhesive</b>              | Acrylic                                                                                                                                                                                                                                                                                                                                                                                                                       |

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| <b>Halogen free</b>                    | No                                |
| <b>Adhesive Operating Temperature</b>  | -40°F to +302°F (-40°C to +150°C) |
| <b>Operating Temperature (Metric)</b>  | -40°F to +302°F (-40°C to +150°C) |
| <b>Reach Complaint(Article 33)</b>     | Yes                               |
| <b>ROHS Complaint</b>                  | Yes                               |
| <b>Certification/Specification WEB</b> | UL 969                            |
| <b>UL Recognized (US)</b>              | Yes                               |
| <b>Package Quantity(Imperial)</b>      | 50                                |
| <b>Package Quantity (Metric)</b>       | 50                                |
| <b>Customs Number</b>                  | 3919102055                        |
| <b>Labels per Column</b>               | 1                                 |
| <b>Labels per Row</b>                  | 1                                 |
| <b>Weight (Metric)</b>                 | 0.521                             |
| <b>Weight (Imperial)</b>               | 1.14                              |

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)