

Specification Sheet

Part Number: 596-00795



Peel-Off Paint Shield, UV Stable, 5.38" x 1.63", PET, Clear, 10/pkg

Article Number 596-00795

Type PAINTSHIELD4

Color Clear (CL)

Features & Benefits

 Made with UV stable inks and materials for durability and weather resistance.
Supplied with aggresive adhesive to ensure long life.
Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers.

Quantity Per pack

Pi	rn	dп	ıct	Des	cri	ption	۱
	•	чu	IVL	$\boldsymbol{\nu}$		DUIDI	ı

HellermannTyton offers Paint Shield laminates that can be applied over Metal Solar Placards as a barrier against unintentional painting or graffiti. Paint Shields can also be used to provide additional protection for hand-written markings using a paint pen. HellermannTyton offers several sizes of Paint Shields designed to match all sizes of Metal Solar Placards. If a Paint Shield (covering placard) has been painted over, simply remove the shield to reveal original marking. Replace shield as needed.

Short Description

Peel-Off Paint Shield, UV Stable, 5.38" x 1.63", PET, Clear, 10/pkg

Global Part Name

PAINTSHIELD4-240-CL

Technical Description

5.37" X 1.625" Peel-off paint shield, UV Stable Clear Polyester, for use with 596-00860 and 596-00861, 596-00243, 596-00255, 596-00474

Width W (Imperial)

5.375

Width W (Metric)

136.39

Thickness T (Metric)

64.0

Height H (Imperial)

1.625

Height H (Metric)

41.14

Material

Type 240, 2.0 Mil Polyester, Clear (240)

Material Shortcut

240

Adhesive 1.0 Mil Aggressive Removable Halogen free No from +50°F (from +10°C) **Adhesive Operating Temperature Operating Temperature (Metric)** -20°F to +302°F (-29°C to +150°C) Reach Complaint(Article 33) Yes **ROHS Complaint** Yes Warranty (US) Yes Package Quantity(Imperial) 10 **Package Quantity (Metric)** 10 **Customs Number** 3919905060 1 Labels per Column 1 Labels per Row Weight (Metric) 0.521

1.14

Weight (Imperial)

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions