

Specification Sheet

Part Number: 596-00796



Peel-Off Paint Shield, UV Stable, 3.6" x .9", PET, Clear, 10/pkg

Article Number 596-00796

Type PAINTSHIELD5

Color Clear (CL)

Features & Benefits

 Made with UV stable inks and materials for durability and weather resistance.
Supplied with aggresive adhesive to ensure long life.
Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers.

Quantity Per pack

		- 4		
Ρr	വ	uct	Descr	intion
	vu	uvi		· Pulvii

HellermannTyton offers Paint Shield laminates that can be applied over Metal Solar Placards as a barrier against unintentional painting or graffiti. Paint Shields can also be used to provide additional protection for hand-written markings using a paint pen. HellermannTyton offers several sizes of Paint Shields designed to match all sizes of Metal Solar Placards. If a Paint Shield (covering placard) has been painted over, simply remove the shield to reveal original marking. Replace shield as needed.

Short Description

Peel-Off Paint Shield, UV Stable, 3.6" x .9", PET, Clear, 10/pkg

Global Part Name

PAINTSHIELD5-240-CL

Technical Description

3.60" X .90" Peel-off paint shield, UV Stable Clear Polyester, for use with 596-00838, 596-00841, 596-00842, 596-00857, 596-00858, 596-00237, 596-00238, 596-00239

Width W (Imperial)

3.6

Width W (Metric)

91.44

Thickness T (Metric)

64.0

Height H (Imperial)

0.90

Height H (Metric)

22.86

Material

Type 240, 2.0 Mil Polyester, Clear (240)

Material Shortcut

240

Adhesive 1.0 Mil Aggressive Removable Halogen free No from +50°F (from +10°C) **Adhesive Operating Temperature Operating Temperature (Metric)** -20°F to +302°F (-29°C to +150°C) Reach Complaint(Article 33) Yes **ROHS Complaint** Yes Warranty (US) Yes Package Quantity(Imperial) 10 **Package Quantity (Metric)** 10 **Customs Number** 3919905060 1 Labels per Column 1 Labels per Row Weight (Metric) 0.521

1.14

Weight (Imperial)

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions