

Specification Sheet

Part Number: 596-00817

CORRIENTE NOMINAL MÁXIMA	
VOLTAJE NOMINAL MÁXIMO	
VOLTAJE MÁXIMO DEL SISTEMA	
CORRIENTE MÁXIMA DEL CIRCUITO	
CORRIENTE MÁXIMA NOMINAL DEL	
CONTROLADOR DE CARGA, SI FUE	
INSTALADO	

Solar Label, Printable, Spanish, DC Module, 4.0" x 2.0", PET, Red, 50/roll

Article Number	596-00817
Type	DC2011S
Color	Red (RD)
Features & Benefits	• Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description	Designed with cross-laminated UV stable materials, these variable print solar installation labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.
Short Description	Solar Label, Printable, Spanish, DC Module, 4.0" x 2.0", PET, Red, 50/roll
Global Part Name	DC2011S-840/281-RD
Technical Description	Printable Solar Label, Spanish Version, DC Module Label, 4.0" X 2.0", Red
Local Order Number 2	English Version: 596-00253
Width W (Imperial)	4.0
Width W (Metric)	101.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8

Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen free	Yes
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	CSA 66956 UL 969
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

Weight (Metric)	0.521
------------------------	-------

Weight (Imperial)	1.14
--------------------------	------