

Specification Sheet

Part Number: 596-00838

PHOTOVOLTAIC AC DISCONNECT							
MAXIMUM AC OPERATING CURRENT:							
NOMINAL OPERATING AC VOLTAGE:							

Metal Solar Placard, Hand Writable, PHOTOVOLTAIC AC DISCONNECT..., 3.75" x 1.0", AA, Black, 5/pkg

Article Number	596-00838
----------------	-----------

Type PVACDISM5

Color Black (BK)

Features & Benefits

 Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.
 Aggressive adhesive ensures strong bond, even on powder coated surfaces.
 Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.
 Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Quantity Per pack

_			-	_			
P	rn	Мı	IC+	Des	cri	nti	n
	v	u	JUL			vi	UII

Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.

Short Description

Metal Solar Placard, Hand Writable, PHOTOVOLTAIC AC DISCONNECT..., 3.75" x 1.0", AA, Black, 5/pkg

Global Part Name

PVACDISM5-AA-BK

Technical Description

3.75" X 1" Silver aluminum text on black background that reads as: "PHOTOVOLTAIC AC DISCONNECT. MAXIMUM AC OPERATING CURRENT. NOMINAL OPERATING AC VOLTAGE." 5 per pack. Nameplate is also printable using a paint pen to add the variable voltage information on demand.

Local Order Number 2

Cross Reference = Paint Shield: 596-00796

Length L (Imperial)

1.0

Length L (Metric)

25.4

Width W (Imperial)

3.75

Width W (Metric)

95.25

Height H (Imperial)

1.0

Height H (Metric)

25.40

Material

Anodized Aluminum (AA)

Material Shortcut

AA

Adhesive

Ultra High Bond Permanent Acrylic Adhesive

Halogen free

No

Adhesive Operating Temperature

from +50°F (from +10°C)

Operating Temperature (Metric)

-40°F to +203°F (-40°C to +95°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

NEC2014

Warranty (US)

Yes

Package Quantity(Imperial)

5

Package Quantity (Metric)

5

Customs Number

7616995195

Labels per Column

1

Labels per Row

1

Weight (Metric) .104
Weight (Imperial) 0.23

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions