

Specification Sheet

Part Number: 596-00850

|                                    |  |
|------------------------------------|--|
| RATED MAX POWER-POINT CURRENT      |  |
| RATED MAX POWER-POINT VOLTAGE      |  |
| MAXIMUM SYSTEM VOLTAGE             |  |
| MAXIMUM CIRCUIT CURRENT            |  |
| MAX RATED OUTPUT CURRENT OF        |  |
| THE CHARGE CONTROLLER IF INSTALLED |  |

Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 10/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 596-00850                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Type                | DC201110                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Color               | Red (RD)                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Features & Benefits | <ul style="list-style-type: none"><li>• Made with UV-stable inks and materials for durability and weather resistance.</li><li>• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li><li>• High abrasion and scuff resistance for high-performance labeling.</li><li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul> |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>    | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| <b>Short Description</b>      | Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 10/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Global Part Name</b>       | DC201110-840/281-RD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Technical Description</b>  | Printable Solar Label, DC Module Label, 4.0" X 2.0", Red                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Local Order Number 2</b>   | Cross Reference = 50 per roll: 596-00253; Printable Metal Solar Placard 5 pack: 596-00839; Engravable Metal Solar Placard 5 pack: 596-00863; Spanish version 50 per roll: 596-00817                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Length L (Imperial)</b>    | 2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Length L (Metric)</b>      | 50.8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Width W (Imperial)</b>     | 4.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Width W (Metric)</b>       | 101.6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Thickness T (Imperial)</b> | 0.0025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Thickness T (Metric)</b>   | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                                        |                                                                            |
|----------------------------------------|----------------------------------------------------------------------------|
| <b>Height H (Imperial)</b>             | 2.0                                                                        |
| <b>Height H (Metric)</b>               | 50.80                                                                      |
| <b>Material</b>                        | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| <b>Material Shortcut</b>               | 840/281                                                                    |
| <b>Adhesive</b>                        | Acrylic                                                                    |
| <b>Halogen free</b>                    | Yes                                                                        |
| <b>Adhesive Operating Temperature</b>  | -40°F to +302°F (-40°C to +150°C)                                          |
| <b>Operating Temperature (Metric)</b>  | -40°F to +302°F (-40°C to +150°C)                                          |
| <b>Reach Complaint(Article 33)</b>     | Yes                                                                        |
| <b>ROHS Complaint</b>                  | Yes                                                                        |
| <b>Certification/Specification WEB</b> | NEC2014 CSA 66956                                                          |
| <b>Warranty (US)</b>                   | Yes                                                                        |
| <b>UL Recognized (US)</b>              | Yes                                                                        |
| <b>Package Quantity(Imperial)</b>      | 10                                                                         |

|                                  |            |
|----------------------------------|------------|
| <b>Package Quantity (Metric)</b> | 10         |
| <b>Customs Number</b>            | 3919905060 |
| <b>Labels per Column</b>         | 1          |
| <b>Labels per Row</b>            | 1          |
| <b>Weight (Metric)</b>           | 0.521      |
| <b>Weight (Imperial)</b>         | 1.14       |