## **HellermannTyton**

## **Specification Sheet**

Part Number: 596-00861



Metal Solar Placard, MAIN PV SYSTEM AC DISCONNECT, 5.5" x 1.75", AA, Red, 5/pkg

Article Number	596-00861
Туре	MPVACDISM5
Color	Red (RD)
Features & Benefits	<ul> <li>Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.</li> <li>Aggressive adhesive ensures strong bond, even on powder coated surfaces.</li> <li>Meets or exceeds NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability.</li> <li>Optional Paint Shields provide additional protection for pre-printed and variable data placards.</li> </ul>
Quantity Per	pack

Product Description	Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.
Short Description	Metal Solar Placard, MAIN PV SYSTEM AC DISCONNECT, 5.5" x 1.75", AA, Red, 5/pkg
Global Part Name	MPVACDISM5-AA-RD
Technical Description	5.5" X 3.0" Black text on red background that reads as: "MAIN PV SYSTEM AC DISCONNECT." in 3/8" tall characters. 10 per pkg.

Length L (Imperial)	5.5
Length L (Metric)	139.7
Width W (Imperial)	5.5
Width W (Metric)	139.7
Height H (Imperial)	1.75
Height H (Metric)	44.40

Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive
Halogen free	Νο
Adhesive Operating Temperature	from +50°F (from +10°C)
Operating Temperature (Metric)	-40°F to +203°F (-40°C to +95°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2017
Warranty (US)	Yes
Package Quantity(Imperial)	5
Package Quantity (Metric)	5
Customs Number	7616995195
Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23

© 2020 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions